

Length	37'	BODY SPECIFICATIONS		Body	
Width	102" INBOARD	Tarp NONE		Accessories	
Side Height	66" SOLID	Bow Holders	NONE		
Top Rail	4.5" DUMP	Tarp Bows	NONE		
Side Matl-front	8'100 WALL	Tarp Basket	NONE		
-middle	23'140 WALL	Tarp Hooks	NONE		TAILGATE
-mane -rear	6'180 WALL	Bulkhead Mat'l	3/16"	Height	FULL - GENESIS
Side Options	NONE	Bulkhead	D/S-MANDOOR (15)	Mat'l Thkness	.140 WALL
Floor Mat'l	1/4" FULL LENGTH				NONE
FIOOF MALI	1/4 FULL LEINGTH	Options	5" SLOPE PLATES SQUARED OFF	Slope	HIGH LIFT GATE
Cuamba Cuasina	4.01	Body Fenders		Hinges Side Swimm	
Crsmbr Spacing	12"	Ladders (Out)	D/S-REAR	Side Swing	NONE
				Gateseal	RUBBER
Floor Options	STUB LONGITUDINALS	Inside	NONE		
	ADD 1/4" X 8" CLEANOUT			Safety Latch	ONE EACH SIDE
	557-99348	Shovel Hgr	D/S-FRAME		
Tailgate Control	AIR / FRAME + ELEC CC (4)			Coal/Grain Door	12" SINGLE HANDLE
Body Pkg	NONE	Light Panel	FULL - LED; X=LED B/U LIGHTS		
Options			000X 000 X000	Coal Chute	NONE
Vibrator	NONE	Marker Lights	LED - 14 PR TOP & BOTTOM	Gate Options	REMARK (9)
Mudflaps	STD + ACROSS REAR (1)	MMTS	BELOW RAIL - LED		
		Apron	NONE		
			CHASSIS SPECIFICATIONS		
Model	TRIAXLE-2 FIXED-FRONT LIFT	ABS	2S/1M	Tire Carrier	NONE
Beam Mat'l	ALUMINUM			Landing Gear	2 SPEED JOST AX150
Length	36' 6" FLUSH MOUNT			Ĭ	D/S CRANK
Width	102"	Independ. Susp(s)		Chassis Lights	NONE
Hoist	85-285 (2)(12)	······································			
Chassis Neck	STD			Elec Coupler	7 WAY + ISO 7 WAY LABELED
King Pin Setting	18"	Distance:			.'AUXILIARY'
5th Whi Plate	3/8" W/ 3/8"X 3" X 7" MOUNT	From:		Hyd Tank	NONE
5th Whi Ht	50"			Hyd Hose Fitting	WINGNUT
Overhang	6"	Controls		Hyd Hose Length	108"
Rear Axle Setting	21.5"	00111015		Tow Hooks	TWO-ONE EACH SIDE
K/P To Rear Axle	398.5"			Paint	BLACK SOFTCOAT
Suspension	AAT30K / E3-2 L LIFT-E1 (3)(5)	Location		Failt	BLACK SOI TCOAT
Susp Control	FRAME + ELEC CC (4)(10)	Axle(s)			NONE
		Axie(S)			NONE
Susp Spacing	52" - 52" (6) (16)	A		Chassis	
Susp Options	GALVANIZED HANGERS	Accessories		Chassis	CHASSIS REAR CM: TAPERED
Springs	AIR			Options:	W/ DIAMOND PLATE COVER
Axles	TP SPINDLES	Brakes			
Accessories	NONE	Drums			REMARK (13)(14)
Brakes	HENDRICKSON MAXX 22T	Hubs			
Drums	N/A				86,000 GVWR
Hubs	10 STUD STEEL - PILOT	Wheels			
	W/ HXL-5; GREASED HUBS				
Wheels	8.25 x 24.5 6 HP/ 6 MP	Tires			
Tires	11R 24.5 HSR2 16 PLY CONT.(11)				
	CE SUBJECT TO CHANGE 12 WEE	KS PRIOR TO BUIL	D DATE		

1. BLACK RUBBER FLAP AHEAD OF AXLE #1 IN THE CENTER.-MUDFLAP 4" FORWARD OF STANDARD POSITION.

2. REMOTE GREASE ZERK FROM TOP PIN TO BOTTOM D/S FACING FORWARD.

3. RIGHT WEIGH OIL FILLED GAUGE (LBS.)(FLUSH MOUNT) ON FRONT CHASSIS CROSSMEMBER.

4. WIRED TO AUXILIARY ISO 7 WAY PLUG

5. HEIGHT CONTROL VALVE ON AXLE #2.

6. LIFT AXLE TO BE CONTROLLED THROUGH FRAME SWITCH & ELEC CC (WIRED TO AUX. PLUG) AND TO HAVE BRAKE RELEASE (LIFT AXLE TO SPIN FREELY). CHANGE 1, 2, 3

WEIGHT: 15,256

7. ALL FRAME SWITCHES TO BE IN POLYCARBONATE BOX ON D/S NEAR LANDING GEAR.

8. PLASTIC INSULATORS BETWEEN WHEEL/DRUM & WHEEL/HUB ALL AXLES.

9. REMOTE GREASE ZERKS FOR LATCH BAR

## **10. USE CROSSOVER KITS**

11. TIREMAXX PRO INFLATION SYSTEM ON ALL THREE AXLES

- 12. NO ACCESS ON OUTSIDE OF BULKHEAD OR FLAP, ACCESS ONLY ON DOGHOUSE IN INSIDE.
- 13. HINGE SHOE GREASE ZERKS-REMOTE ZERKS TO D/S MANIFOLD
- 14. REAR PIN BUSHING LUBE-REMOTE GREASE ZERKS TO D/S MANIFOLD
- 15. 073-20176-01 HALE KNURLED MANDOOR STEP

16. 86.000 GVWR RATING

17. ALL EAST LOGOS TO BE DECALS ONLY- NOT RIVETTED OR WELDED

18. HIGH LIFT GATE OPERATED BY FRAME SWITCH AND ELEC CAB CONTROL WIRED TO AUXILIARY ISO 7 WAY PLUG