	SALES	RENTALS	PARTS	SERVICE
	Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
	Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
TRAILER	Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
BRAKE & WHEEL	Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
	Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
A014962-A014964	Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
	Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
VINS: 000682, 000684	com @hale	etrailer f 🎔 🛅 🞯 🎬	in 0 🖮	
& 000686	800-232	2-6535 *	FINANCING	AVAILABLE
20NTT 20 Ton Tan	dem Non Tilt	Faqs		

Base Weight	7,960	
RAILER		
	Overall Length	34 ft. 8 in.
	Overall Width	102 in.
	Weight lbs +/- 2%	9337, including options
	A-Frame	6 ft. 11 in. Hi-Tensile Cold Formed Wide Flange Beam
	Hitch	3 in. pintle eye, adjustable 5 position 23 1/2 in. to 32 1/2 in.
DECK		
	Deck Length	<u>21 ft.</u>
	Loaded Deck Height	34 in.
	Main Frame	Hi-Tensile Wide Flange 14 in. @ 22
	Cross Members	Hi-Tensile 5 in. Channel @ 6.7
	Side Rail	Hi-Tensile 7 in. Channel @ 9.8 open on inside
	Floor	1 3/8 in. x 7 in. Keruing Shiplapped
	Landing Gear	Dual 2 Speed
	Landing Gear	<u>*NPO*: Painted gray</u>
	Step	Bolt on, Located on Front Corner of deck, Driver side
SUSPENSION/A	AXLES	
	Axles	25,000 lbs Capacity 77.5 in. Track
	Spread	49 in.
	Suspension	Heavy Duty spring ride
	Alum Air Tank	*NPO*: Drain plug with cable
	Brakes	Quick Change 12 1/4 in. x 7 in.
	Brake Chamber	#3030, All Axles
	Air Brake System	2S/1M
	Air Tank(s)	Aluminum
	Bearings	Oil Bath
	Slack Adjusters	Automatic
	Hubs & Drums	8 Stud Unimount C / W Cast Drums
	Tires	235/75R17.5 16 ply
	Wheels	Alum. Wheel Pkg. 17.5 (4 steel, 4 polished)
BEAVERTAIL		
	Length	6 ft. Beavertail, Planked
RAMPS		
	Length	<u>* 38 in. x 76 in. Wood Filled Air Operated Ramp</u>
	Ramp Support	*NPO*: Ramp Support
	Brackets	*NPO*: To hold ramp brace when not in use, 1 per side
GENERAL SPEC		
	Electrical System	Modular, Vapor Proof GROTE Ultra Blue
	Lights	LED CMVSS 108 / FMVSS 108
	Front Connector	SAE J560 7 Pin

		20NTT			
20 Ton Tandem Non Tilt Tags					
SENERAL S	PECIFICATIONS				
	Color	Galvanized			
	Mudflaps	1 set of BWS at rear			
	Toolbox	Full A Frame mounted with solid bottom and aluminum cover			
	Load Securement	7 pair of D-rings: 5 pr main deck, evenly spaced; 1 pr on B/T; 1 pr on main beam at headboard			
Fenders		3/16 in. deck plate			
		GVWR Rating is based on standard configuration and a 15% Tongue weight distribution			

DISCLAIMER