

HALE TRAILER BRAKE & WHEEL



A014974-A014978
VINS: 77859-77863

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

1250C PNEUMATIC DRY BULK TANKER

Weight 12135 lbs. *** **Cubic Feet** 1250

BODY

REGION	DOMESTIC
LOAD PROFILE	102K
	REF 68540
VESSEL THICKNESS	0.190 5454-H32 ALUMINUM
	.219 HOPPERS AND END END CONES,
CUBIC FT CAPACITY	1250
	HD 12" C-CHANNEL FRAME RAILS
COMMODITY	CEMENT
MODEL SUB TYPE	NONE
TRAILER OPERATION TYPE	PNEUMATIC
FOOD GRADE	NONE
VESSEL FINISH	MILLED
LENGTH	44 FT. / 12.80 M.
	44 FT
WIDTH	102
OPERATING TEMPERATURE	185 F / 85 C
OPERATING PRESSURE	14.7 PSI / 101.35 KPA
COMPARTMENT OPTIONS	SINGLE COMPARTMENT
LOWER HOPPER CONES	WELD-ON 45 DEG (STANDARD)
MANLID QUANTITY	3
MANLID LOCATION LAYOUT	OVER EACH HOPPER
FIRST MANLID TYPE	KNAPPCO 20IN. ALUMINUM MANLID
SECOND MANLID TYPE	KNAPPCO 20IN. ALUMINUM MANLID
THIRD MANLID TYPE	KNAPPCO 20IN. ALUMINUM MANLID

AERATION

AERATOR FORMAT	3 PER HOPPER (STANDARD)
AERATOR TYPE	BTI SPIN FLOW AERATION KIT W/ WEAR PLATES AND 2 IN. BTI BLACKMAXX INDIVIDUAL AERATION CONTROLS AT EACH HOPPER
AERATION LOCATION	DRIVER SIDE
AERATOR LINE CONTROL	3" BTI BLACKMAX BUTTERFLY VALVE
AERATOR SEAT	WHITE RUBBER (FOOD GRADE) SEAT
AERATOR DISK	ALLOMAXX DISC
AERATOR HANDLE TYPE	ALUMINUM
AERATOR HANDLE POSITION	MANUAL 10 - POSITION

AIR INLET

AIR INLET SIZE	3 IN. SCH. 10 ALUMINUM PIPE
AIR INLET LOCATION	DRIVER SIDE
CHECK VALVES	(2) BTI OPTIMA CHECK VALVES - (1) AT AIR INLET & (1) UP STREAM OF FRONT HOPPER DISCHARGE
AIR INLET SILENCER	NONE

PROP / PRES CONTROL VALVE

CONTROL VALVE HOUSING	3" BTI BLACKMAX BUTTERFLY VALVE
CONTROL VALVE DISK	ALLOMAXX DISC
CONTROL VALVE HANDLE TYPE	ALUMINUM
CONTROL VALVE HANDLE POSITION	MANUAL 10 - POSITION

BLOW DOWN LINE

BLOW DOWN LINE HOUSING	3" BTI BLACKMAX BUTTERFLY VALVE
BLOW DOWN LINE DISK	ALLOMAXX DISC
BLOW DOWN LINE SEAT	WHITE RUBBER (FOOD GRADE) SEAT
BLOW DOWN LINE HANDLE TYPE	ALUMINUM
BLOW DOWN LINE LOCATION	DRIVER SIDE FRONT
BLOW DOWN LINE HANDLE POSITION	MANUAL 10 - POSITION
BLOW DOWN RELIEF PRESSURE	15 P.S.I.

TOP AIR

TOP AIR VALVE HOUSING	3" BTI BLACKMAX BUTTERFLY VALVE
TOP LINE LOCATION	DRIVER SIDE FRONT

PRODUCT & DISCHARGE

PRODUCT / DISCHARGE LINE SIZE	4 IN
PRODUCT / DISCHARGE LINE MATERIAL	ALUMINUM
PRODUCT / LINE MATERIAL GAUGE	SCHD.40
PRODUCT VALVE SIZE	5" BTI BLACKMAXX BUTTERFLY VALVES
PRODUCT VALVE SEAT	WHITE RUBBER (FOOD GRADE) SEAT
PRODUCT VALVE DISK	ALLOMAXX DISC
PRODUCT LINE CONNECTION	GROOVE TO GROOVE CLAMPS AT FRONT AND REAR
CLAMPS	WORM GEAR CLAMPS W/ RUBBER SLEEVES BETWEEN HOPPERS
PRODUCT VALVE HANDLE TYPE	ALUMINUM
PRODUCT VALVE HANDLE POSITION	MANUAL 5 - POSITION
PRODUCT TEE TYPE	5 X 4 ALUMINUM STRAIGHT TEE
REAR DISCHARGE LOCATION	EXTEND OVER AXLES TO REAR
NO. OF GAUGE ENCLOSURE	1
GAUGE LOCATION	Driver Side -Rear- Forward of Tandem

PRIMARY AXLES

MODEL	TRI-AXLE
NO. OF PRIMARY AXLES	3
SUSPENSION	HEND. INTRAAX AAT W/ RAISED AXLE - TP SPINDLE
	AAT 250 STRAIGHT AXLES
NO. OF LIFT KITS	0
AXLES	71.5" AXLES
	77.5" AXLES
LIFT KIT_	NONE
	25,000 POUND RATED SUSPENSIONS
LIFT CONTROLS	NONE
	BRAKE LINING TO BE NAB-456 FOR 25K RATING
WHEEL END PACKAGE	YES (HXL5)
BRAKES	7 IN. XL, W/ 30-30 CHAMBERS
	LONG STROKE CHAMBERS WITH 6" AUTO SLACKS
CAM GUARDS	HEND. INTRAAX

HUB AND DRUM CENT W/ DURALITE HUB HP OB 10 STUD TP, LS, 7 IN.

CAST STEEL DRUMS

TIRES CONTINENTAL HSR2 11R 22.5 16 PLY
WHEELS ALUMINUM HP 22.5X8.25 - ALL POLISHED (XP)
PRIMARY AXLE TIRE INFLATION SYSTEM NONE

CHASSIS

5TH WHEEL PLATE GALVANIZED STEEL, ADJUSTABLE
5TH WHEEL PLATE HEIGHT 48 IN. HIGH
SUSPENSION CONTROL AUTOMATIC DUMP ON EMERGENCY GLADHAND
SCALE SYSTEM LOAD GAUGE - DRIVER SIDE REAR
ABS FOR TRAILER (1) 4S2M MERITOR / WABCO
SLACKS AUTO
HUBODOMETER NONE
AXLE LUBRICATION NONE
DOLLIES - LANDING GEAR - LANDING LEGS JOST - 5 YEAR NO LUBE- D.S.
AIR TANKS ALUMINUM TANK

LIGHTS

LIGHT TYPE GROTE L.E.D. W/ GROMMET
REAR I.D. LIGHTS (3) I.D. LIGHTS TOP
3 PENNY LIGHTS ADDED TO SECOND RUNG FROM BOTTOM
LIGHT PANEL (TURN) (STOP) (STOP) - (STOP) (STOP) (TURN)
STD. MARKER LIGHTS 2 EACH SIDE FRONT & REAR
MID-TURNS (2 PAIR) LED-BOXED IN
3- PENNY LIGHTS AS MID TURNS PER SIDE
BACK-UP LIGHTS NONE
BACK-UP LIGHT LOCATION NONE
AUXILIARY CABLE NONE
NO. OF WORK LIGHTS 2
WORK LIGHT MODEL L.E.D. CUBE WORK LIGHTS
WORK LIGHT LOCATION NONE
WORK LIGHT SWITCH LOCATION OUTSIDE

PAINT

SUSPENSION COLOR MAC BLACK
MAC MACHINE FINISH LOGOS BLACK (931716)

ACCESSORIES

FOLDING LADDER RAIL NONE
FOLDING LADDER RAIL OPERATION TYPE NONE
TOE RAIL FULL LENGTH ON BOTH SIDES
TOP RAIL
CABINET NONE
CENTER WALKWAY ADHESIVE BACKED, SKID-RESISTANT TAPE BETWEEN TOE RAILS
HOSE STORAGE TUBE (1) 8 IN. X 21 FT. MOUNTED ON CS
GAUGES 1 - LINE P.S.I. / 1 TANK P.S.I. - (INSIDE ILLUMINATED ENCLOSURE)
MUD FLAPS ANTI-SAIL FLAPS (REAR OF FRONT FENDERS AND REAR OF BACK FENDERS)
PRODUCT DISCHARGE HOSE NONE
FENDERS_ ALUMINUM ROLLED EDGE - SINGLE CONTOUR AT FRONT, DOUBLE CONTOUR AT REAR
DOCUMENT HOLDER LOCATED DRIVER SIDE NEAR LANDING GEAR
AIR INLET ACCESSORIES PTO HOSE HOLDER, MAST, HOOK AND DUMMY ADAPTER LOCATED DRIVER SIDE ABOVE FRONT FENDER

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.