



Hale Trailer Brake & Wheel 015020-015031

CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)
OVERALL LENGTH 48' - Base Weight 12,200#
UPPER DECK LENGTH 10'
LOWER DECK LENGTH 38'
OVERALL WIDTH 8' 6"
KING PIN SETTING 18" - Squared Front
UPPER COUPLER PLATE 1/4"
UPPER COUPLER HEIGHT 48"
BULKHEAD None
MAIN FRAME 26" Fab.-PreCamb.I-Beams
SIDE RAILS 6" - 6.5# Per Foot
TOP DECK FLOOR SILLS 4" Steel I-Beam - 18" O.C.
LOWER DECK FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg
COIL HAUL PACKAGE None
FLOOR DECKING 1-1/8" Apitong
WINCHES 12
STRAPS None
WINCH TRACK Steel Slide Entire Length of Drivers Side
LANDING GEAR Two Speed
SUSPENSIONS Air Ride - Hendrickson Intraax 23K - Fixed
SUSPENSION LOCATION Set at Rear most Position
AXLES (2) 22.5K Capacity - Type 30 Chambers - Auto Slacks - ABS - 22.5 Tires
AXLE SPACING 10'2" Wide Spread
LIFT AXLE None
DUMP VALVE None
SCALES None
PARKING BRAKES All Axles
ABS SYSTEM ABS System 2S/1M
DUST SHEILDS None
WHEELS Disc - Hub Piloted - 22.5 - Steel (672#)
TIRES 255/70R 22.5 - 41" Loaded Deck Height - Double Coin
TIRE INFLATION SYSTEM None
ANTI-SAIL MUD FLAPS Behind All Axles
STAKE POCKETS 24" O.C. Sides & 4 Across Front, 5 Across Rear
PIPE SPOOLS Double
RUB BAND STEEL 3/8" X 2-1/2" Recessed for DOT Tape
OILFIELD FRONT None
DOCK BUMPERS Rubber Inboard
OILFIELD REAR NECK None
OILFIELD - PIN POCKETS None
DECK ROLLERS None
TAILROLLERS None
CARGO TIE DOWN None
CONTAINER TWIST LOCKS NONE
TIRE CARRIERS None
TOOLBOX MATERIAL None
TOOLBOX TYPE None
TOOLBOX LOCATION None
LIGHTS Sealed Wiring Harness w/ LED Pkg
CUSTOM LIGHTS None
PAINT Black

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.