

2019 Trail King Blade Hauler

TK85EFX Extendable Blade Hauler; 13223-TK85EFX

STANDARD EQUIPMENT Remote can be used wireless or cord type 85,000-lb. capacity 44 deg max steer angle (3rd axle) 8'-6" wide Self-contained hydraulics 9'-2" gooseneck (detachable, low profile) Hydraulic support leg to aid in closing and 20" kingpin setting opening 49" 5th wheel height Individual aluminum fenders 58" front platform height (102" wide, 28" long) 3 axle-72" axle spacing Slide-able rear platform (102' wide, 36" long) 4S2M Anti-lock brakes 45 deg. tapered front corners Steel hub-piloted - cast drums Heavy duty front pullout/rotate down stabilizing legs 6.75 x 17.5 8-hole disc wheels Narrow Mono-beam design with 4 stages 235/75R X 17.5 tires Kingpin steering Red & white conspicuity markings 15 ft. non-loadbearing pull-out rear extension Blasted prior to paint Tritronic remote control with auto align function Color: Trail King 2-part polyurethane

			Weight	
Item #	Category	Description	(lbs)	Qty
68983	Open Deck	TK85EFX Extendable Blade Hauler; 53' closed OAL, 177' 9"open OAL (194'-9" including pull-out)		
13230	Landing Gear	2-speed landing gear		
13232	Suspensions	Air ride suspension HT250		
13234	Axles	25,000 lb. cap. Axle (5/8" wall)		
13257	Wheel Finish (inside)	6.75 x 17.5 8-hole machined aluminum wheel		6

13261	Wheel Finish (outside)	6.75 x 17.5 8-hole polished aluminum wheel (per wheel) ILO Std 6.75 x 17.5 8-hole machined aluminum wheel	6	
07907	Tire Size	235/75R17.5 - 18 ply HTL2 (tire only) (per tire)		
10059	Spare Tires	No spare tire		
13241	Hydraulics & Controls	Hydraulic turntable style steering		
13245	Hydraulics & Controls	13 hp Honda (ILO diesel)		
08024	Paint	Black S7203 with white decals (735-432-039)		

13223-Additional Options

			Weight	
Item #	Category	Description	(lbs)	Qty
68791	Custom Options	68791 TK85EFX, 5 section, 177'-9" open, 102" wide, 11'-8" gooseneck (OAL will change accordingly) with 108" swing clearance, 13HP Honda SCU, (1) 36" X 102" sliding platform at rear, rear pullout (17'), 3 axle		
68983	Custom Options	68983 TK85EFX-5 Move SCU to rear of trailer behind axles. Move axles ahead 56" to allow room for the SCU		
08569	Miscellaneous	DOT Inspection - all Open Deck and Materials Hauling trailers		