



Hale Trailer Brake & Wheel

015576 - 015578

CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)
OVERALL LENGTH 53' - Base Weight 13,000# - Including Length of Beavertail
UPPER DECK LENGTH 10'6"
LOWER DECK LENGTH 38'1"
DOVETAIL 53.13" - Steel Smooth Plate & Traction Bars
Rear End Set Up For Future 3rd Ramp Install.
OVERALL WIDTH 8' 6"
KING PIN SETTING 24" - Tapered Front
UPPER COUPLER PLATE 1/4"
UPPER COUPLER HEIGHT 48"
MAINFRAME 26" Fab.-PreCamb.I-Beams-(80K Pkg 3/8"x 5" Top & 1/2" x 5" Bottom & 3/16" Web)
BULKHEAD None
SIDE RAILS 6"-Alum-Extruded W/Double L Track
TOP DECK FLOOR SILLS 4" Steel I-Beam - 18" O.C.
LOWER DECK FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg
COIL HAUL PACKAGE Single Coil Placement - 5 Extra Stud Sills-Ctr On Trailer
FLOOR DECKING 1-1/8" HD Aluminum w/ 4 Nailers
WINCHES 12 Double L
WINCH TRACK Double L Aluminum - Extruded Siderail R/S Only
Tie Bar Curb Side.
STRAPS None
LANDING GEAR Two Speed
SUSPENSIONS Air Ride - Cush - CP25U - 2 Axles
SUSPENSION LOCATION King Pin to Center of Rear Axle 43'
AXLES (2) 25K Capacity - Type 30 Chambers - Auto Slacks - ABS - 22.5 Tires (1463#)
AXLE SPACING 10'2" Wide Spread
DUMP VALVE Manual-Position In Rear Skirt Gusset D/S-Dump All Axles
LIFT AXLE None
PARKING BRAKES All Axles
ABS SYSTEM ABS System 2S/1M
DUST SHEILDS None
WHEELS Disc - Hub Pilot-22.5 (2-AX)-Polish ALUMINUM 4 Outside Wheels(4-Steel Inside) (-148#)
TIRES 255/70R 22.5 - 41" Loaded Deck Height - Double Coin
TIRE INFLATION SYSTEM None
STAKE POCKETS 24" O.C. & 4 Across Front
ANTI-SAIL MUD FLAPS Behind All Axles
PIPE SPOOLS Double
RUB BAND STEEL 3/8" x 3" - Aluminum - Recessed for DOT Tape
DOCK BUMPERS None
LOADING RAMPS (2)-Spring Assisted
CONTAINER TWIST LOCKS None
CARGO TIE DOWN Recessed Chain Tie Downs - 14 Pair
TOOLBOX MATERIAL Aluminum
Shop Print - Quote: 52417 Page 2 of 2
TOOLBOX TYPE 18Hx18Dx60L-Alum Box-Barn Style Double Door-Dia TP Alum Door(+93#)
TOOLBOX LOCATION Driver Side- Between Spread
LIGHTS Sealed Wiring Harness w/ LED Pkg
CUSTOM LIGHTS None
PAINT Black
CUSTOM 1. Elect.-Wired Thru Aux 7way Plug @ Front of Trailer-Dump Rear Axle
Rear Axle Dump By Aux. 7-Way and Manual Dump All Axles.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.