



A015735-A015740
VIN: 225456-225461

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Jacksonville, FL: 800-828-3055
Baltimore, MD: 888-601-7500	Little Rock, AR: 833-424-8944
Boston, MA: 800-854-5310	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Richmond, VA: 866-839-3495
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235

HaleTrailer.com | @haletrailer

800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE	SEMI-TRAILER, COMBO DROP PLATFORM LEGEND SD
DIMENSIONS	
LENGTH	48'-0"
WIDTH	102", 97" between side rails.
HEIGHT	Floor, approximately 59" high at front and 41" at the bumper.
DROP HEIGHT	20", located at 10'-6" from front.
COUPLING	
COUPLER PLATE	1/4", 80 000 psi steel, plug welded structure.
KING PIN LOCATION	18" from front.
COUPLER HEIGHT	48".
STRUCTURE	44" c/c frame with "CAMBER".
FLANGES	3/8" x 5", 100 000 psi steel, goose neck section.
WEB	1/2" x 5", high tensile, 24" high in center and 16 1/2" above suspension. 1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel. 24" high, with holes, parachute shaped, to lighten trailer.
GOOSENECK	11 1/4" high, 48" straight behind king pin.
CROSSMEMBERS	I beams, 4" @ 3.2 lbs/ft, 80 000 psi steel, galvanized, 16" c/c in gooseneck and the remaining 12" c/c.
FLOOR	Structural aluminum extrusions, flat type, inverted "T", 1 1/8" high with 4 Apitong or equivalent planks.
FLOOR FASTENING	Screws.
SIDE RAILS	4 3/8" x 5 11/16" high, extruded aluminum. ("Legend" model)
SIDE BOXES	3 5/8" x 1 5/8" inside, 4" high, extruded aluminum.
RUB RAILS	CMVSS-905 WLL, 5,500 lbs WLL approved. Aluminum extrusions 3/8" x 2 3/4". Single rub rail spacers 1" x 1 3/4" as anchor.
CORNERS	Bevelled.
FENDERS	Reinforcement over tires at rear, steel tubing structure, galvanized (G164), floor full length.
KNEE BRACES	3/16" formed steel plates, galvanized (G164), bolted in web and a crossmembers located each side.
X BRACES	Between main beams, full length.
ENDS	
FRONT RAIL	Bolted aluminum extrusion, 7" high, overlapped floor to allow floor plank to walk underneath.
BUMPER	CMVSS 223-RIG approved (in accordance with Canada & USA regulation). Galvanized (G164) steel, bolted uprights to frames, 4" x 4" cross bar formed tubing at a maximum height of 22" from under tubing to ground.
POCKETS	2 bolted galvanized pockets at front for removable headboard.
BUMPER	2 Heavy duty rubber dock, at the end of rear rail.
REAR RAIL	Formed steel, galvanized.
ELECTRICAL	
FRONT CONNECTOR	7 way (SAE J560).



ITEM	DESCRIPTION
ELECTRICAL SYSTEM MAIN SYSTEM FLASHERS	Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108. Grote Ultra Blue LED, sealed beams, tail lights, markers lights "Dot", identification lights (2 1/2" dia.), licence light. Sealed beams LED, one lamp including side marker and flasher, each side at middle point, amber.
LANDING GEAR SAND SHOES CRANK	AXN,(LG50DUN) 10" x 10". Road side.
BOGIE BASIC MECHANICAL BOGIE	Fixed, for tandem 122" spread.
MECHANICAL (GROUND AXLES) SUSPENSION SPRINGS AXLE(S) CAM SHAFTS TRACK DUST SHIELDS BRAKES BEARINGS SLACK ADJUSTERS SEALS BRAKE CHAMBERS HUBS AND DRUMS RIMS TIRES	Hendrickson INTRAAX AANL-23K (6.5), tandem. N.B.: Winged suspension bracket. For axles with bearings HM 218248 and HM 212049. Air. LDA, 5 3/4" diameter, 23 000 lbs. capacity. 28 splines with enclosures, 10" long. 77 1/2". None (Intraax axles). 16 1/2" standard, long life H20-HXS Hendrickson lining. HM 218248 and HM 212049. Meritor, automatic, 28 splines. Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90. T.S.E. brake, "Omnibrake" (30-30), (push rod 9 3/4"). (4 years warranty by T.S.E. for parts only). 10 stud disc hubs, balanced drums outboard mount, 285.75mm B.C., single flange nuts. For dual aluminum wheels. 22.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts, 2 hand holes. Continental, 255/70 R 22.5 HSR2 SA 16 ply (36.6")
AIR SYSTEM GLAD HANDS AIR VALVES VALVE(S)	Fixed. Meritor Wabco, ABS, 2 sensors 1 modulator. Automatic blow down valve, WITHOUT control box,
ACCESSORIES REGISTRATION HOLDER MUD FLAPS SLIDING TRACK WINCHES	One plastic, Betts-PS-1 or equivalent. One set, rubber with moose logo and vertical grooves to reduce spray. Full length, "LL" extruded aluminum, road side. Qty: 12, KINEDYNE #1020SV, silver painted slider (low profil 5 7/8").
FINISHING PAINT	Shot blasted, one coat of epoxy primer and one acrylic polyurethane top coats Color: black, code: PPG CCA947255-55.



ITEM	DESCRIPTION
BOGIE	One coat of epoxy primer and one acrylic urethane top coats, Color: black, code: PPG CCA947255-55.
RETROREFLECTIVE TAPES	Axles (wheel end) included. (Tandem).
WHEELS OR RIMS	Conspicuity striping in compliance with CMVSS 108. Gray and red each side, fully covers rear sill and horizontal underride protection bar. White (power top coat).

R

Due to the deep backlogs, material/component availability, price fluctuation and transportation costs, Manac reserves the right to adjust the price based these instabilities. If needed, Manac will contact the dealer or customer app 3 months prior to assembly with revised pricing, or a change in components. At that time, the customer will have the option to accept the change or cancel. This will prevent and any possible cancellation fees from our suppliers.

CONFORMITY

This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.