



Hale Trailer Brake & Wheel 015914-015916, 017170-017172

components description

CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)

OVERALL LENGTH 53' - Base Weight 12,900#

UPPER DECK LENGTH 10'6"

LOWER DECK LENGTH 42'6"

OVERALL WIDTH 8'6"

KING PIN SETTING 24" - Tapered Front

UPPER COUPLER PLATE 1/4"

UPPER COUPLER HEIGHT 48"

BULKHEAD None

MAIN FRAME 26" Fab.-PreCamb.I-Beams-(80K Pkg)**44" Frame Centers**

SIDE RAILS 6" - 6.5# Per Foot

TOP DECK FLOOR SILLS 4" Steel I-Beam - 18" O.C.

LOWER DECK FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg

COIL HAUL PACKAGE None

FLOOR DECKING 1-1/8" Apitong

WINCHES 12

STRAPS None

WINCH TRACK Steel Slide Entire Length of Drivers Side

LANDING GEAR Two Speed

SUSPENSIONS Air Ride - Hendrickson Intraax - 23K - 2 Axles

SUSPENSION LOCATION Set at Rear most Position

AXLES (2) 22.5K Capacity - Type 30 Chambers - Auto Slacks - ABS - 22.5 Tires (1463#)

AXLE SPACING 10'2" Wide Spread

LIFT AXLE None

DUMP VALVE Elect.-Wired Thru Aux 7way Plug @ Front of Trailer-Dump Rear Axle(+9#)

SCALES None

PARKING BRAKES All Axles

ABS SYSTEM ABS System 2S/1M

DUST SHEILDS None

WHEELS Disc - Hub Piloted - 22.5 - Steel (672#)



CUSTOM 1. None CUSTOM 2. None CUSTOM 3. None

TIRES 255/70R 22.5 - 41" Loaded Deck Height - Double Coin TIRE INFLATION SYSTEM None ANTI-SAIL MUD FLAPS Behind All Axles STAKE POCKETS 24" O.C. Sides & 4 Across Front, 5 Across Rear PIPE SPOOLS Double RUB BAND STEEL 3/8" X 2-1/2" Recessed for DOT Tape **OILFIELD FRONT None DOCK BUMPERS Rubber Inboard** OILFIELD REAR NECK None OILFIELD - PIN POCKETS None **DECK ROLLERS None** TAILROLLERS None CARGO TIE DOWN None CONTAINER TWIST LOCKS NONE TIRE CARRIERS None **TOOLBOX MATERIAL None TOOLBOX TYPE None TOOLBOX LOCATION None** LIGHTS Sealed Wiring Harness w/ LED Pkg **CUSTOM LIGHTS None PAINT Black**