

XL 120 Step Deck Extendable

OVERALL LENGTH OVERALL WIDTH CAPACITY WEIGHT +/- 3%

53'

102" 120,000 LB DISTRIBUTED; 100,000 LB IN 10' CLOSED 0.000 LB

GOOSENECK

LENGTH KINGPIN SETTING SWING CLEARANCE **5TH WHEEL HEIGHT** DECKING STAKE POCKETS I ANDING GEAR FLIP NECK

16" REMOVABLE 102" 52" NONE NONE 2 SPEED W/ HANDLE ROAD SIDE PREP FOR 72" FLIP NECK 72" FLIP NECK

11' 6" NARROW GOOSENECK

MAIN DECK

LENGTH	41' 6" EXTENDING TO 64' 4"
LOADED DECK HEIGHT	33" WITH OPEN WHEELS
DECKING	1 1/8" APITONG DECKING, FLUSH
CROSSMEMBER	4" JR. I-BEAM ON 12" CENTERS
BEAMS	6" MILLED SIDE RAILS
STAKE POCKETS	24" CENTERS WITH 5/16" X 2" RUB RAIL W/ SINGLE PIPE SPOOLS
D-RINGS	(7) PAIR OF PAN STYLE D-RINGS ON MAIN DECK - EVENLY SPACED
	(7) PAIR OF FLAT D-RINGS AT BOTTOM KNEE BRACES
AXLES	(3) 25,000 LBS. NOMINAL, (5/8" WALL)
SUSPENSION	HENDRICKSON / 25,000 CAPACITY / AIR RIDE
AXLE SPACING	60"
ABS	NA WITH SPRING BRAKES ON (1) AXLE
TIRES	MICHELIN 245 / 70R / 17.5 (H)
WHEELS	6.75 X 17.5 8-HOLE, PILOT MOUNT, STEEL INSIDE, ALUMINUM POLISHED OUTSIDE DISC
BRAKES	12 1/4" X 7 1/2"
DRUMS	OUTBOARD
ELECTRICAL	12V SEALED GROTE SYSTEM WITH (3) TAILLIGHT ALUMINUM PACKAGE
	4" AMBER STROBE TO BE USED AS 3RD TAILLIGHT
D-RINGS	(1) PAIR OF BENT D-RINGS IN TAIL CHANNEL

PAINT

ADDITIONAL

RAISE AND LOWER VALVE LOCATED IN REAR DRIVER SIDE BOLSTER LIQUID FILLED AIR GAUGE LOCATED IN REAR DRIVER SIDE BOLSTER (1) PAIR OF EXTRA CLEARANCE LIGHT AT START OF MAIN DECK DUST SHIELDS PREP FOR 2 AXLE POWER BOOSTER MANUAL RIDE HEIGHT CONTROL (1) 4-WAY PLUG IN EACH CORNER OF MAIN DECK (1) 4-WAY PLUG IN REAR BOLSTER - BOTH SIDES LIMIT CHAINS ON ALL 3 AXLES PSI TIRE INFLATION SYSTEM ON ALL 3 AXLES

SIMILAR TO 21998

BLACK

DISCLAIMER