



Hale Trailer Brake & Wheel 016709 - 016713

OVERALL LENGTH 45'
OVERALL WIDTH 8'
96" Wide Trailer.
OVERALL HEIGHT FRONT 13' = No Tarp
UPPER COUPLER HEIGHT 48"
UPPER COUPLER PLATE 1/4" Plate
KING PIN SETTING 36"
SWING CLEARANCE 90"= 36KP
LANDING GEAR Two Speed
SUSPENSIONS Spring Ride - Hutchens-2 Axle
SUSPENSION LOCATION Set at Rear Most Position
AXLES (2) 22,500K Capacity - Type 30 Chambers - Auto Slacks - ABS
AXLE SPACING 49"
LIFT AXLE None
WHEELS Disc - Hub Piloted-24.5 - (STD)
TIRES 11R24.5- Manufacturer Choice (Import)
FRONT TYPE 18" Diagonal
FRONT MATERIAL Aluminum .063 - Pre Painted White Aluminum
LADDERS Steel Nose & Rear Door
REAR DOOR TYPE Heavy Duty Aluminum Top Hinged Chip Gate W/Wear Pads
REAR DOOR MATERIAL Heavy Duty Galvanized Mesh
SIDE SHEET MATERIAL .063 Aluminum Smooth
INTERIOR LINING None
SIDE SHEET COLOR Pre-Painted White
SIDE POST Extruded Aluminum on 16" Centers
LOWER RAIL Heavy Duty Aluminum Lower Rail
FLOOR Corr Fabricated Aluminum
FLOOR SILLS 4" Steel - Wax-Dipped I-Beam w/ Undercoating
SILL SPACING 12"/16"/12" STD
PARKING BRAKES All Axles
DUST SHEILDS None
ANTI-SAIL MUD FLAPS Behind Rear Axle
BUMPER H. D. 3" x 4" Push Bumper
TARP SYSTEM None
TARP COLOR BLACK
LIGHTS Sealed Wiring Harness W/ LED PKG
PAINT Black - Ladder, Fifth Wheel, and Rear Frame

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.