



**A016711-A016720**



SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Jacksonville, FL: 800-828-3055
Baltimore, MD: 888-601-7500	Little Rock, AR: 833-424-8944
Boston, MA: 800-854-5310	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Richmond, VA: 866-839-3495
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235

HaleTrailer.com | @haletrailer

**800-232-6535** \*FINANCING AVAILABLE

**A80HDGC (Alpha Series Hydraulic Detachable Double Drop)**

<b>Capacity</b>	80,000 lbs.
<b>Concentrated</b>	70,000 lbs. in 16'
<b>OAL</b>	48' OAW 102" 48' 5" OAL
<b>Gooseneck</b>	<p><b>Sub Frame</b></p> <p>10' 5" Hydraulic Detachable 49" 5th Wheel Height 15" King Pin 80" Swing Clearance 2 Bent D-Rings Per Side lightning holes each side platform 5 Position Ride Height Full Width Platform Stainless Mudflaps</p> <p>9' Long 40" Loaded Deck Height Full Width Decking 1 Pair Flag Holders 1 pair Stake Pockets in Tail Channel Two Pair of Chain Drops in Center One Pair of Pan D-Rings at Rear Frame Reinforcement for Flip Axle</p>
<b>Main Deck</b>	<p><b>Axles and Suspension</b></p> <p>28' 7" Length 12" Fabricated I-Beams 18" Loaded Deck Height 6" Ground Clearance 6"/4" JRI Beam Cross Members ALT on 12" Centers 8 Bent D-Rings per Side Chain Slots on 24" Centers each side 1 1/8" Apitong Flush Decking-Full Width Front Ramps tapered to 4" W/Traction Bars Removable Swingout Outriggers on 12" Centers</p> <p>2 - 25,000 lb Axles 54" Axle Spacing Ridewell Suspension 16 1/2" x 7" Drum Brakes 4S2M ABS Spring Brakes on Both Axles Raise &amp; Lower Valve Manual Ride Height Control 255/70R22.5 Tires 8.25 x 22.5 Steel Wheels</p>
<b>Lighting</b>	<p>2 Tail Light Package with Stainless Steel Covers 2 Pr. Side Markers/ 1 Pr. Mid-Turns in Deck Grote Ultra Blue-Seal Wire Harness</p>

Gooseneck	General
<input checked="" type="checkbox"/> Honda Pony Motor with Stainless Lid	4" Amber Strobe Light
	Liquid Filled Air Gauge
Main Deck	Paint
<input checked="" type="checkbox"/> 29' Well (48' 5" OAL)	Black
<input checked="" type="checkbox"/> 15" LDH/5" GC 10" Beam	
<input checked="" type="checkbox"/> Tool Box in Front of Deck	
<input checked="" type="checkbox"/> Tool Box in Rear of Deck	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.