

# HALE

## TRAILER

### BRAKE & WHEEL



**A016786-A016795**



**VIN: 477611-477620**

#### SALES | RENTALS | PARTS | SERVICE

|                        |                     |                          |                     |
|------------------------|---------------------|--------------------------|---------------------|
| <b>Allentown, PA:</b>  | <b>800-383-8894</b> | <b>Jacksonville, FL:</b> | <b>800-828-3055</b> |
| <b>Baltimore, MD:</b>  | <b>888-601-7500</b> | <b>Little Rock, AR:</b>  | <b>833-424-8944</b> |
| <b>Boston, MA:</b>     | <b>800-854-5310</b> | <b>Portland, ME:</b>     | <b>800-325-4253</b> |
| <b>Concord, NC:</b>    | <b>800-438-2250</b> | <b>Richmond, VA:</b>     | <b>866-839-3495</b> |
| <b>Delmar, DE:</b>     | <b>866-486-1400</b> | <b>Scranton, PA:</b>     | <b>800-569-1400</b> |
| <b>Des Moines, IA:</b> | <b>888-673-5011</b> | <b>Springfield, MA:</b>  | <b>800-854-5306</b> |
| <b>Elkton, MD:</b>     | <b>800-544-7127</b> | <b>Voorhees, NJ:</b>     | <b>866-315-0235</b> |

HaleTrailer.com | @haletrailer

**800-232-6535** \*FINANCING AVAILABLE

#### GVWR

|                |   |
|----------------|---|
| GVWR:          | Trailer to meet 68,000 Pound GVWR   |
| * VIN PLATE:   | Canadian/Transport Canada Compliant - VIN Plate to Read in English and French, Pounds and Kilograms |
| Product Type:  | HT Thermotech-Truck Load w/Swing Door   |
| Product Class: | HT Thermotech TL  |

#### GEOMETRY

|                        |                                 |
|------------------------|---------------------------------|
| Length - Exterior:     | 53'-0"                          |
| ** Length - Interior:  | 52'-2"                          |
| Width - Exterior:      | 102.36"                         |
| ** Width - Interior:   | 97.4"                           |
| Height - Exterior:     | 13'-6"                          |
| ** Height - Interior:  | 105.5" Front                    |
| Deck Height:           | Standard application            |
| Fifth Wheel Height:    | 47"                             |
| King Pin Location:     | 36"                             |
| Landing Gear Location: | 105" from King Pin (+ 1"/-1/4") |

#### TIRES & WHEELS

|                            |   |
|----------------------------|---|
| Tire Furnished:            | Factory Furnished   |
| * Tire Manufacturer:       | Hankook TL21(G), Low Rolling Resistance Tire                              |
| Tire Size:                 | 295/75R22.5   |
| Wheel Furnish:             | Factory Furnished   |
| Wheel Material:            | All Steel Wheel   |
| Wheel Manufacturer:        | HT Standard (TCC 361)   |
| Wheel Size:                | 8.25 x 22.5, 5-Hand Hole (Steel, Inner & Outer)                           |
| Wheel Finish for Steel:    | Powder Coated White Steel Disc  |
| Tire Stem Valve Position:  | Dual Wheel Steel / Aluminum / Combo (STD 180°outboard & straight inboard) |
| Wheel Finish for Aluminum: | None (Due to All Steel Wheel Application)                                 |
| Valve Stem & Cap:          | Valve Stem & Metal Dome Cap   |

#### UPPER COUPLER

|                              |  |
|------------------------------|--|
| Upper Coupler-Reefer:        | 4.00" deep, Floor Over Coupler and Running to Front, Bolting Type        |
| * Approach Plate:            | 5/16" thick 50,000 Lb Yield - 6 Support Channels                         |
| * King Pin (BTM Main) Plate: | 5/16" thick 50,000 Lb Yield  |
| King Pin & Manufacturer:     | Standard (Jost) AAR Cruciform King Pin                                   |
| Front Bottom Rail:           | Stainless Steel & Stainless Steel Wrap-Around Impact Guard Striker Angle |

#### BODY/BASE

|                                |   |
|--------------------------------|---|
| Forward Crossmember:           | 4" Extruded Aluminum I-Beams: 12" C/L   |
| * Landing Gear Crossmember:    | 4" Steel I-Beams (80,000 PSI) : 8" C/L (6" On Forward Edge : 7ea)                 |
| Bay Area Crossmember:          | 5.5" Extruded Aluminum I-Beams : 12" C/L  |
| Running Gear Crossmember:      | 4" Steel I-Beams (80,000 PSI) : 12" C/L with 8" C/L Last 4' (For Reefer Van only) |
| Slider Body Rail (RV):         | 204" Rail Length  |
| Slider Rail Supplier:          | Hutchens Slider Rails   |
| Slider Rail Duty:              | Standard Duty   |
| Slider Rail Hole Space & Dia.: | 4" increments holes with large diameter holes (Hutch & Binkley)                   |
| * Tire Protect Plate:          | Front-12 GA Galv steel x22"x55" long or the nearest XM / Rear-12 GA Galv steel    |

x22"x120" long (Fastener Type)  
\* Tire Protect Install: Behind Upper Coupler & Tandem Area at Both Side  
\* Fuel Tank Location: None, Prepare with fuel line conduit thru landing gear, forward & UC

---

**FLOOR**  
Floor- Assembly Method: Aluminum Floor Assembly with Weld (MIG). Seams to be Continuously / Uniformly Weld  
\* Floor-Detail Spec. - RV: 1.34" Extruded Aluminum (6061-T6) NW Flat Floor  
Floor-Surface Spec. - RV: Ridged Floor Surface with Safety Grip (Knurled)  
\* Rear Gutter & Trough: Flush w/ Top of Floor (Mig) & w/o Trough -> Floor Plank will be extended to rear gutter (FLAT & DIARY TYPE STD)  
Floor Ratings - RV: 18,000lb Rated Floor  
Floor Drain - RV: (4) Drains w/ Kazoo  
Floor Filler Mat'l: I-Filler (Ridge PVC)  
Floor Inserts -RV: Extruded Aluminum (STD)

---

**FRONT**  
Front Corner Radius: 6" Extruded Aluminum STD Duty Post (RV)  
Front Panel & Color - RV: 0.04" Aluminum Prepaint White w/ Aluminum Insert  
\* Corner Radius Insert - RV: 0.035" Stainless Steel  
Front Posts: (4) Posts - (2) 3.15" Deep Steel Hats / (2) AL "Z" Post  
Gladhands: Phillips Qwik-E with Filters Control Line Only. Overlaid(Back open)+ aluminum plate  
Front Receptacle(7-Way): Phillips 7-Way w/ 3" Deep, No Circuit Breaker (HT Reefer STD)  
Gladhand/7-Way Location: Overlaid on Lower Roadside Front  
\* Corner Radius Protector: (2) 0.125" X 12" SMOOTH Alum Each Side at Top  
Reefer Unit Front Frame: Brace for type "A" (Large Opening)

---

**RV-VAN ITEM**  
\* Reefer Unit Manufacturer: Reefer Unit to be determined later  
Reefer Unit Type: Single-Temperature Type  
\* Reefer Unit Spec.: Reefer Unit to be determined later  
\* Reefer Unit Furnish: Prep only for future installation after delivery  
\* Reefer Unit Install: Customer or Other Install. Cut & Seal Hatch w/ Plywood for Shipment  
\* Reefer Commissioning: Commission unit at Others

---

**SIDE**  
Side Material: 0.04" Aluminum Prepainted White w/ natural color rivets  
Side Posts: 1.0" Deep Extruded Aluminum "Z" Post (STD)  
Side Post Centers: 24" C/L with 12" C/L @ Upper Coupler and Support Gear  
Side Top Rail: Standard Side Top Rail for Thermotech  
Side Bottom Rail: Side Bottom Rail for Reefer 5.5" High Bay Crossmember - TL Thermotech  
Fasteners to Bottom Rail: Standard Rivets to attach C/Members to the Side Bottom Rail

---

**REAR**  
Rear Frame: Swing Door Reefer Rear Frame (w/1 Lock Rod per LH & RH Door)  
Rear Door Opening Spec.: Swing Door - HT Standard Reefer Door Opening Application (97.2" Width).  
Corner Post Feature: Standard  
Door Sill Level (RV): Door to Flush with Floor (HT STD)  
Door Sill Feature: Standard  
Door Header Feature: Standard  
Door Type (RV): Swing Door w/ Aluminum Frame & (1) Rubber Door Bumper on Each Door (HT Standard)  
\* Door-Outer Cover (RV): Swing Door-Stainless Steel Outer Cover Sheet w/ Diamond(Quilted) Pattern  
Door-Inner Lining (RV): Swing Door-PP050 (0.043") Polar X  
\* Door Scuff: Install 0.125" Smooth Aluminum x 16" high rear door scuff  
Option - Door Install Instruct (RV): Standard Door Installation Per Manufacturer's Recommendation  
Option - Door Hold Back (RV): Standard for Swing Door  
Hinges: Four (4) Aluminum Hinges per Door  
\* Additional Hinge Option: Additional One(1) Aluminum Hinge (Total 5 Per Door)  
Rear Underride Guard: 4" Tube Bolt on Assembly w/ Welded Perforated(Pooched) Horizontal. Rear Impact Guard (RIG30-NEW)

Option - Horiz Member/Other: One piece roll formed w/continuous welding  
Underide Bolt Spec.: Stainless steel bolts & nuts - Optional  
\* Dock Bumper: Pair 3" X 6" Mold Bolted Bumper  
\* Rubber Bumper Location: Outboard of Light As Close to Edge As Possible

---

**LIFT GATE**

**ROOF**

\* Roof Panel: 0.032" One Piece Corrugated Aluminum  
Roof Bow: 1" Extruded Aluminum  
Roof Bow Centers: 32" Centers Full Length

---

**LINING/SCUFF**

Side Lining - Reefer: Polar X Pp050 0.043"  
Front Lining - Reefer: Polar X PP050 0.043"  
Roof Lining - Reefer: Polar X PP050 0.043"  
Sub-Floor: Polar X Pp030 0.023"  
Side Scuff Mt'g Method: Recessed (STD)  
\* Side Scuff for Reefer: 16" High Extruded Aluminum  
\* Logistic Track for Reefer: (2) Row of "E" Track, Galvanized, Both Side  
\* Logistic Track Mt'g Method: Overlaid (Horizontal)  
\*\* Logistic Track Locate: Customer to advise

---

**URETHANE INSULATION**

Front Insulation: Front Insulation - 4" Polyurethane  
Side Insulation: Side Insulation - 2" Polyurethane  
Roof Insulation: Roof Insulation - 2" Polyurethane  
\* Floor Insulation: Floor Insulation - 2" Polyurethane  
Door Insulation: Swing Door-Insulation - 3" Polyurethane

---

**LANDING GEAR**

L/Gear Spec.: Jost HT421.G3.17.157 5 Year Warranty Full HDG  
L/Gear Mt'g Method: Inboard Mounting (Standard)  
L/Gear Shoes: 10" X 10" RCF (Removable Cushion Foot) Low Profile  
L/Gear Ground Clearance: Nom. 12" Ground Clearance  
L/Gear Mt'g Bracket: Hot Dip Galvanized Large Wing Plate  
L/Gear Crank Handle: Roadside  
L/Gear Options: None (HT STD)  
L/Gear Cross Brace Design: HT Standard Cross Brace attachment Design

---

**RUNNING GEAR**

Bogie Type: Sliding Tandem(2) Axle Bogie  
Axle Spacing: 49" Axle Spacing  
Axle ABS System: Tandem Axle w/2S1M ABS System  
Bogie & Axle Location: Location to be Sliding Tandem Axle for specified slider Length w/Stop Bars @ Front & Rear  
Option-Related Bogie Stopper Feature: STD plug stopper  
Susp. Manufacturer: Hendrickson  
Suspension Capacity: Standard Duty  
Hendrickson Susp. Specification: Hendrickson Vantraxx HKANT40K Air Ride  
Surelok (Anti-Dock): Surelok (Anti-Dock) Installed  
Locking Pin Mechanism: Air-Assist Pin Puller or Quik Draw  
Susp. Sub-Frame: Hendrickson K-2 STD Duty  
Type of Susp Spring: Air Bag  
Spring Specification: Air Bag  
\* Axle Diameter: 5.75"  
Axle Supplier: Hendrickson  
Axle-General Spec.: Axle - Tandem (2) Axle included in Suspension (For 2S1M or 2S2M System)  
Axle-Track Length: 77-1/2"

\* Axle-Spindle Type: Parallel Spindle  
 Brake Lining Size: 16.5" X 7"  
 Brake Lining Spec.: Hendrickson Extended Service (Abex-3030-197)  
 Brake Control System: 2S/1M Wabco ABS  
 Spring Brake Control: Sealco 110500 Springbrake Priority  
 Brake Cont-Hose & etc.: Standard Air Line & Hose Application (US&Canada)  
 \* Slack Adjuster Spec.: Wabco Auto-5.5", 28 Spline EasyFit (No Grease)  
 \* Brake Chamber Spec.: Wabco Premium Chamber  
 \* Stroke Length: 3" Long Stroke Length  
 Hub Specification: HT Standard (KIC) 10 Stud Hub Piloted Outboard Iron Hub  
 Drum Specification: HT Standard (KIC) Cast Drum  
 Hub/Drum-Opt(Nut&Other): Standard  
 Bearing Specification: Stemco  
 Lubrication Spec.: Chev Delo Gear EP5 80-90 oil  
 \* Wheel Seals Spec.: Stemco Discover Seals, Hub Cap included in tire inflation system, Pro-Torq Nut  
 \* Tire Inflation Spec.: Hendrickson Tire Maax Inflation System for Undressed Axle (This kit include  
 Hendrickson Hub Cap for TireMaax)  
 Tire Inflation Pressure: 100 PSI  
 \* Tire Inflation Lamp Location: Indicator PSI Light at Roadside Mounted over corner radius. (STD location)  
 \* Tire Inflation Lamp Spec.: 33 Series Lamp

#### ELECTRICAL

\* Harness-General Spec.: Molded Color Code Grote Harness Oval molds with front terminal rings  
 Harness-Special Feature: Manufacturer's Standard Feature  
 \* Front Light: (4) Trucklite 33275Y LED PC Rated Mounted with Grommet (2-Front & 2-Side)  
 \* Rear ID Header Light: (5) Trucklite 33275R LED (Cluster of 3 & 1 Each Outboard)  
 Rear Side Marker Type(Shape): Mini Button Style Lamp with Antitheft Bracket  
 Rear Side Marker Detail Spec: (2) Trucklite 33275R LED PC Rated Flush w/ Grommet 33725 w/ anti-theft hardware  
 Rear Side Marker MT'G Location: Mounted on Standard Location on Rear Corner Post - HT STD  
 \* S/T/Tail Light-Quantity & Type: (6) Trucklite 40 or 44 Series (Round Style) or Equivalent  
 \* S/T/Tail Light-Detail Spec: (6) Trucklite 44334R LED Mounted w/ SUS Base Rings Anti Theft  
 Main Mid-Turn Light: Install the Mid turn lamp  
 Mid-Turn Mounting Method: Mounting Bracket  
 Main Mid-Turn Light-Detail Spec: (2) Trucklite 60420Y LED Flange Mounted with Stainless Steel Rivets  
 ABS Light Detail Spec: (1) Trucklite 33275Y LED PC Rated w/ Grommet 33725 w/ anti-theft hardware  
 ABS Light MT'G Location: Mounted on Standard Location on Rear Corner Post - HT STD  
 License Light: (1) Trucklite 33210C LED with 33815 Anti-Theft Flange  
 \* Option Related Lamps/Harness: Additional Trucklite 33 LED series Marker Lights. (3) Each Side Top Rail & (2) Each Side Bottom Rail Top and Bottom rail lights to match up (Center Combination to match up with center top rail lamp)  
**Comment:** Top and Bottom rail lights to match up (Center Combination to match up with center top rail lamp)  
 Electrical Related Regulation: Standard Application

#### MARKING/DECALS

HT & Product Type Decal Package: Hyundai Logo & Product Type Decals Application(For not having pre-painted white panels for side/door/front, Apply white HT Corporate decals)  
 Decal Package: Factory Furnished Hyundai Information & Regulatory Decal Package with FMCSA Specified in Notes  
 Decal Opt 2-Decal Location: Standard Application  
 Decal Opt 3-Decal Installation: Standard Application  
 Decal Opt 5-Decal Location-reefer: Standard Application  
 Decal Opt 6-Decal Installation-reefer: Standard Application  
 Conspicuity Vendor: 3M  
 Conspicuity Markings: Hyundai Standard Conspicuity with Logo Applied to Side Bottom Rail  
 License Plate: Temporary For Delivery. Fasten on SUS Mounting Plate

License Plate Brk't Install: Standard Install Location - Roadside Below Door Sill  
Furnish Document Holder: Factory Furnished  
Document Holder Detail Spec: (1) Phillips 16-802  
Document Holder/Manifest Loc.: Overlaid on Lower R/S Front  
\* Vent Door Specification: (1) Bottom Hinged Swing type Vent Door & (1) Side Hinged Swing type Vent Door (with screens)  
\* Vent Door Location: (1) Upper R/S Front, (1) Lower C/S Rear Respectively  
\* Vent Door Step & Handle: (2) Folding Access Steps & Grab Handle (One Side)

**PAIN/FINISH**

Upper Coupler Finish: Stainless Steel-Forward Section w/ Black Undercoating inside of Upper Coupler  
Crossmembers Finish: HDG : ALL Steel Crossmembers including Hat C/M, L/G & Bogie Area (Except any Aluminum)  
\* Axle & Components Finish: Black Undercoating  
\* Susp. Sub-Frame Finish: Black Undercoating  
L/Gear(K-Bracing) Finish: Hot Dip Galvanized  
L/Gear(Upper Leg) Finish: Hot Dip Galvanized  
Rear Frame-Finish: Stainless Steel  
Rear Frame-Paint Color: None (For Galvanized or Stainless Steel)  
Rear Underride-Finish & Spec.: Hot Dip Galvanized  
Rear Underride-Paint Color: None (For Galvanized or Stainless Steel)

**MISCELLANEOUS**

Mudflap Provider: Factory Furnished Mudflaps  
Mudflap Specification: 24"x30" White Plain Plastic with Hyundai Logo 3/8# thick with Anti-spray ribs  
Mudflap Mounting Loc.: Suspension frame (Tandem/Single axle frame without P.H.)  
Mudflap Mounting: STD Location w/ H.D Washer Retainer

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.  
Equipment availability, prices and specifications are subject to change without notice.