

# HALE

## TRAILER

### BRAKE & WHEEL



**A016805-A016808**  
**Vin: 5A3426-5A3429**

#### SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b>	800-383-8894	<b>Jacksonville, FL:</b>	800-828-3055
<b>Baltimore, MD:</b>	888-601-7500	<b>Little Rock, AR:</b>	833-424-8944
<b>Boston, MA:</b>	800-854-5310	<b>Portland, ME:</b>	800-325-4253
<b>Concord, NC:</b>	800-438-2250	<b>Richmond, VA:</b>	866-839-3495
<b>Delmar, DE:</b>	866-486-1400	<b>Scranton, PA:</b>	800-569-1400
<b>Des Moines, IA:</b>	888-673-5011	<b>Springfield, MA:</b>	800-854-5306
<b>Elkton, MD:</b>	800-544-7127	<b>Voorhees, NJ:</b>	866-315-0235

HaleTrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

Renegade N18 Air Tandem, 18 inch Loaded Deck Height, Narrow Hydraulic Gooseneck (Model: RENEGADE N18)	
	Est. Wt.: 17,100# +/- 3%
<b>Capacity:</b> 40 tons (80,000 lbs) evenly distributed - GAWR and GVWR determine legal loads	
<b>Length (Trailer Only):</b> 50 feet 1 inches	
<b>Width:</b> 8 feet 6 inches	
<b>Compatibility:</b> Designed to accept 3rd flip axle - none	
<b>Gooseneck Design:</b> Narrow hydraulic removable non-ground bearing - swing radius of 102 inches (11 ft 11 in overall gooseneck length) - set up for wet line operation	
<b>Loaded Fifth Wheel Height: 50 in nominal loaded fifth wheel height with 5 ride height positions</b>	
<b>Power Source: None</b>	
<b>Deck Design:</b> Flat level deck design	
<b>Deck Length:</b> 29 feet 0 inches clear deck length	
<b>Loaded Deck Height:</b> 18 inches with 6 inches ground clearance	
<b>Crossmembers:</b> On 12 inch centers	
<b>Flooring:</b> 1 3/8 inch nominal wood (full width)	
<b>Recessed Floor Mounted D-Ring Package: None</b>	
<b>Front Ramps: None, front of deck sloped top down to assist in loading with traction cleats</b>	
<b>Extension Brackets:</b> Outriggers - 14 pair - 28 total removable swing type, 1 pair - 2 total removable hook-on type	
<b>Front Bogie Ramp:</b> Sloped steel bogie ramp (full width)	
<b>Deck to Bogie Connection:</b> Fixed	
<b>Number of Axles:</b> 2	
<b>Axle Capacity:</b> 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
<b>Axle Spread:</b> 54.5 inches (between axles)	
<b>Brakes:</b> 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
<b>Spring Brakes:</b> Spring brakes (2 axles)	
<b>Dust Shields: None</b>	
<b>Framework:</b> All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs	
<b>Suspension:</b> Air ride with automatic controls	
<b>ABS:</b> 4S/2M system without diagnostic tool and cable	
<b>Load Scale: None Standard</b>	
<b>Wheels: 8.25 x 22.5 LVL One buffed outside/steel inside - hub-piloted</b>	
<b>Tires:</b> 255/70R 22.5 H ply OEM Standard	
<b>Hubodometer: None Standard</b>	
<b>Tire Inflation: None Standard</b>	
<b>Covered Rear Bogie:</b> Rear bogie platform with 1 1/8 inch wood floor	
<b>Rear Bogie Height:</b> 40 inches	
<b>Bumper:</b> 3 tail light package	
<b>Connections for Future Axle Attachment:</b> Air and electrical connections to go along with connecting ears	

<b>Mini Boom Trough &amp; Traction Cleats: None</b>	
<b>Accent Package:</b> Stainless steel bumper insert	
<b>Liquid Filled Gauge:</b> Included	
<b>Electrical System:</b> DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes	
<b>Marker Lights:</b> 7 marker lights per side including mid-turn	
<b>Electrical Receptacle:</b> J560 7-pin connector	
<b>Additional Marker Lights: None Standard</b>	
<b>Paint: Fontaine black polyurethane enamel</b>	
<b>Lash Rings:</b> 7 pair - 14 total	
<b>Flag Holders:</b> 2 pair flag holders	
<b>VIN Plate:</b> Bilingual VIN plate	
<b>Registration/Document Holder:</b> Registration/document holder installed	
<b>Please Note:</b> Price includes commodity surcharges	
<b>Commercial Terms:</b> Ex Works- Springville, AL, USA	
<b>Flip Axle: None</b>	
<b>Dust Shields on Flip Axle: None</b>	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.