

HALE TRAILER BRAKE & WHEEL



A016830-A016839
VIN: P2891-P2900

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Jacksonville, FL: 800-828-3055
Baltimore, MD: 888-601-7500	Little Rock, AR: 833-424-8944
Boston, MA: 800-854-5310	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Richmond, VA: 866-839-3495
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Rear Axle 51-60 (54.5in. spread) (Model: MAG FA 5160)	
	Est. Wt.: 2,740# +/- 3%
Compatibility: Workhorse 51, 55 and Magnitude 55, 60 class with tridem bogie and EQ1	
Length: 4 feet 6 inches	
Width: 8 feet 6 inches	
Number of Axles: 1 axle	
Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
Axle Spread: 54.5 inches (between axles)	
Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
Dust Shields on Flip Axle: None	
Hydraulic Flip Axle Option: None Standard	
Suspension: Air ride	
Wheels: 8.25 x 22.5 Outer LvL One buffed/steel disc inside - hub-piloted	
Tires: 275/70R 22.5 OEM Standard	
Hubodometer: None Standard	
Tire Inflation: None Standard	
Boom Trough: V-style boom trough with bolt-in V pan	
Manual Dump Valve: Manual Dump Valve (Push Pull)	
Bumper: Heavy duty V-style rear bumper	
Accent Package: None	
Electrical System: DOT sealed beam and harness with LED lights and 4 inch flush mounted amber strobes	
Paint: Fontaine black polyurethane enamel	
Lash Rings: 1 pair - 2 total	
Flag Holders: Flag holders - 1 pair located on rear bumper	
VIN Plate: Bilingual VIN plate	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.