

## SALES | RENTALS | PARTS | SERVICE

800-828-3055 Allentown, PA: 800-383-8894 Jacksonville, FL: Baltimore, MD: 888-601-7500 Little Rock, AR: 833-424-8944 Boston, MA: 800-854-5310 Portland, ME: 800-325-4253 Concord, NC: 800-438-2250 Richmond, VA: 866-839-3495 Scranton, PA: Delmar, DE: 866-486-1400 800-569-1400 Des Moines, IA: 888-673-5011 Springfield, MA: 800-854-5306 Elkton, MD: 800-544-7127 Voorhees, NJ: 866-315-0235

HaleTrailer.com | @haletrailer f y

800-232-6535 \*FINANCING AVAILABLE

BODY:		TAILGATE:		CHASSIS:	
WIDTH (INCHES)	102	HEIGHT	FULL	MODEL	TRIAXLE-REAR LIFTING
LENGTH (FEET)	50	TYPE	SINGLE	TYPE	ALUM SUB FRAME
HEIGHT (INCHES)	106	STYLE	SHEET & POST	AXLE TO AXLE	60" - 60" (15)
SIDE MAT'L	3/16" (7)(8)	MAT'L THICKNESS	3/16"	REAR AXLE SETTING	53"
TOP RAIL	UNLOADER	S / S HINGE ON	PASS. SIDE <b>4-3-4</b>	5TH WHEEL HT	49"
ROOF	NONE	GATESEAL	NONE	PIN SETTING	36" W/ 3/8" PLATE(16)
ROOF MAT'L	NONE	GATE LADDER	CAST- SHIP LOOSE	SUSPENSION	AIRRIDE (14)(17)(18)(19)
BULKHEAD	1/4" (1)(9)(10)	TARP HOOKS	5 FRONT/4 REAR	SPRINGS	AIR
TARP HOOKS	5 FRONT/4 REAR	WINDERS	ONE	AXLES	TP SPINDLES
TARP BASKET	NONE	GATE GUIDE	YES	BRAKES	HENDR. MAXX 22T
TARP	NONE	GATE CONTROL	MECH - BOLT CLAW	DUSTSHIELDS	NONE
CATWALK	YES- STD EAST	POCKETS	FABBED / EXTRUDED	BRAKE CHAMBERS	STD
B.H. LADDER	YES-COMMERCIAL	CROSSPIPE (S)	TWO	ABS	2S/1M
CROSSMEMBER	"I" BEAM -12" C/L		MIDDLE-SPRING	HUBS	10 S <b>DUCTILE</b> STEEL
FLOOR MAKE	KEITH-NYLON T BLKS		REAR- TUBE	DRUMS	N/A
FLOOR MAT'L	2299 W/ 3.5" DRIVE	COMPACTOR:		WHEELS	8.25 X 24.5 6 HP IN/
WEARPADS		SIDE LATCH	NONE		6 MP OUT (22)
HORIZONTALS	NONE	CENTER LATCH	NONE	TIRES	11R 24.5 R268
45° DIRT SHEDDERS	8" SMOOTH	PIN DIA.	NONE		ECOPIA H 16 PLY BS
TARP BAR	YES - SINGLE			DOLLIES	2 SPEED JOST A451
TAPE COLOR	BLACK	HYDRAULICS:		LOCATION	D/S CRANK
LIGHT PANEL	IN TAILGATE (11)	HOSES	TWO 4000PSI	BUMPER	REAR UNDERRIDE
MARKER LIGHTS	LED - (4)	LENGTH	108"	TOW HOOK(S)	TWO
MIDMOUNT SIGNALS	LED - MODEL 60	FITTINGS	WINGNUT	PUSH BLOCKS	YES
MUDFLAPS	YES (20)	HP	1" MALE	PAINT	BLACK
HOSE HANGER	YES	LP	1" FEMALE		
TIRE CARRIER	ONE-MIDDLE P/S	HOSE LOCATION	P/S (13)		
	ACCESS	AIR & ELECTRICAL	CENTER (10)(13)		

## REMARKS: PRICE SUBJECT TO CHANGE 12 WEEKS PRIOR TO ESTIMATED BUILD TIME

1. STANDARD FOUR CAST STEPS ON INSIDE OF BULKHEAD.
--

CHANGE 1

- 2. WELD ENDS OF ALL CROSSMEMBERS TO BOTTOM RAIL
- 3. KEITH ALUMINUM FRAME. STAINLESS STEEL HYDRAULIC TUBING. ADD DRIVE UNIT BRACES.
- 4. 3 PAIR PER SIDE BOTTOM ONLY BOXED IN.
- 5. FILTERED GLAD HANDS.
- 6. ALUMINUM AIR TANKS TO HAVE CABLE OPERATED DRAINS EXTENDED TO D/S BOTTOM RAIL
- 7. SHEET AND POST SIDES TO BE 1/4" LAST 15'.
- 8. THREE EXTRA PAIR OF UPRIGHTS (25 3/4" C/L SPACING APPROXIMATELY)
- 9. MANDOOR IN CENTER OF BULKHEAD
- 10. AUXILIARY ISO 7 WAY PLUG
- 11. LED TAILLIGHTS TO BE OOO 000 OOO IN THE GATE
- 12. NO REMARK FOR #12
- 13. HYDRAULIC HOSE LOCATION TO BE P/S & ELECTRICAL IN THE CENTER-REF 68615.

14 AIR GALIGE (LRS.)	LUMBED TO SUSPENSION AND MOUNTED AT FRONT OF	N D/S- REF 68615
14. AII GAUGE (EDS./)		N D/3- INLI 000 IS.

15. 60' AXLE SPACING BETWEEN AXLES #1 & #2 AND 60" BETWEEN AXLES #2 & #3.

16. 43' KP TO C/L OF REAR AXLE SETTING FOR MAINE.

17. SUSPENSION TO BE AAT30K/E1-2 L LIFT -E3 LE #1 & #2 ARE FIXED AND AXLE #3 IS LIFTING

18. AXLE #3 (LIFT AXLE) TO BE ACTUATED WITH FRAME SWITCH AND ELECTRIC CAB CONTROL & BRAKE RELEASE WIRED TO AUXILIARY PLUG.

19. INSTALL CROSSOVER KIT

20. REAR MUDFLAPS DIRECTLY BEHIND TIRES

21. GALVANIZED HANGERS

22. CUSTOMER WANTS TO MAKE SURE IF THEY SWITCH TO 13.00 X 22.5 6 MP & 425/65R 22.5 M864 SUPER SINGLE THERE WILL BE NO INTERFERENCE W/ CM'S OR ANY ISSUES.

BODY/FAB/INSPECTION/FRAME/INVENTORY/SALES/TIRES/PAINT/ACID

 OVERALL HEIGHT (FT)
 13.42
 EMPTY WEIGHT (#)
 20,613
 CUBIC YARDS
 127

 ( EMPTY WEIGHT VARIANCE +/- 3% )