




A017034-A017042
VIN: 222387-222395

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE APPLICATION	SEMI-TRAILER, STEEL PLATFORM. GALVANIZED SEE SECTION 
DIMENSIONS	
LENGTH	48'-0"
WIDTH	102", 97" between side rails.
HEIGHT	Floor, approximately 60" high at front and 54" at rear.
COUPLING	
COUPLER PLATE	3/8", plug welded structure.
KING PIN LOCATION	30" from front.
KING PIN	Bolted, 2" diameter, Holland KP-0882 (3/8").
COUPLER HEIGHT	48".
STRUCTURE	Frame with "CAMBER".
FLANGES	3/8" x 5", 100 000 psi steel.
WEB	1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel. 26" high at the peak with holes, parachute shaped, to lighten trailer.
GOOSENECK	11 1/4" high, with integrated nose ramp and 48" straight behind king pin.
CROSSMEMBERS	1 beams, 4" @ 3.64 lbs/ft, 80 000 psi steel, 12" centre to centre, installed with stiffeners angle.
FLOOR	Apitong or equivalent, 1 1/8" thick shiplap finished, no preservative.
FLOOR FASTENING	Two screws per board at each crossmember. (With galvanized flatbed or crossmembers)
SIDE RAILS	Formed channel 6" @ 4.6 lbs/ft.
SIDE BOXES	3/16" steel plate, 1 15/16" x 3 1/16" interior, 4" high, for 1 3/4" x 2 3/4" stakes. (Canadian dimensions). N.B.: including boxes at rear bumper.
RUB RAILS	1/2" x 3" flat bars of steel.
CORNERS	Bevelled.
X BRACES	Between main beams, full length.
CHAIN RACK	(4) chain hangers (1/2" plate), hook shaped, welded on the crossmember. Located: ***ROAD SIDE AHEAD FRONT AXLE***.
TIE BAR	3/8" x 2 1/2" shaped steel welded under crossmembers, curb side, located 14" from side rail. Galvanized
ENDS	
FRONT RAIL	Formed steel 1/4".
BUMPER	CMVSS 223-RIG approved (in accordance with Canada & USA regulations). Uprights integrated with frames, 4" x 4" cross bar roll formed tubing at a maximum height of 22" from under tubing to ground.
BUMPER	Aluminum plate, bolted, to close rear completely between the bumper uprights.
PULL PLATE	Pull plates between uprights of bumper.
HEADBOARD	48" high, with fabricated beam and square tubing 1 1/2". *** NO *** ladder. 4" between the tubes, (5.5" c/c) for smaller logs. *** Galvanized ***.(Ref. 210147HA12).
POCKETS	Boxes included.
REAR RAIL	11" high, 9 gauge formed steel, including 3 boxes at rear and 3/8" x 2 1/2"



ITEM	DESCRIPTION
	shaped steel, bolted to frame.
LOGGING BUNKS	Qty: 5 sets, (installed at crossmembers) side rail cut, location: 23 1/2" TO FIRST BUNK THEN 60" SPACING REMAINDER REF#212871
STAKES	No stakes.
ELECTRICAL FRONT CONNECTOR	7 way (SAE J560), Phillips brand.
FRONT ADD. CONNECTOR	7 way (ISO 3731), for auxiliary functions only. ***AIR LIFT***
ELECTRICAL SYSTEM MAIN SYSTEM	Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108. Grote Ultra Blue LED, sealed beams, tail lights with male pins #53252 (10 diodes), markers #47122, 47233 (2 1/2" dia.), licence light #60280-M).
TURN SIGNAL	Sealed beams LED, one lamp including side marker and flasher, each side at middle point, amber.
BACK UP LIGHT(S)	Type sealed beam spot light (Grote #62391 LED), Qty: 2 (in the sill)
TAIL LIGHTS	Sealed beams (Grote LED #53252, 10 diodes) red, rubber rings. Qty: 4 additional, mounted and aligned between the bumper up 1 rights.
TAIL LIGHTS	Sealed beams (Grote DEL #53252, 10 diodes) red. Qty: 1 additional each side. From outside, tail lights and flasher, flasher with parking, brake with parking.
MAIN SYSTEM	With additional vapor proof junction box Truck-Lite #50400. ***LOCATED AT SUSPENSION AREA REF#212871
LANDING GEAR SAND SHOES CRANK	Holland, Mark V (LGS-4F315), with mounting plate, solid axles, galvanized. 10" x 11 1/2", solid axles. Road side.
BOGIE BASIC SUSPENSION	Fixed.
BOGIE SUSPENSION	Hendrickson INTRAAX disc brake AAT-30K HXL5 (MAXX 22T), tridem, 60" spread.
STROKE STOPPERS	Retaining chains for INTRAAX air suspensions with grounded axles.
LIFT DEVICE	Hendrickson "UBL102", bolted (removable) and galvanized, with air system Manac. Quick and brake release valves on air lift included. ***ON FRONT AXLE, CONTROLLED FROM CAB***
SPRINGS AXLE(S) SPIDERS	Air. LDA, 5 3/4" diameter, 30 000 lbs. capacity.
CAM SHAFTS	Welded.
TRACK	77 1/2".
DUST SHIELDS	Steel, clamped.



ITEM	DESCRIPTION
BRAKES BEARINGS SLACK ADJUSTERS SEALS BRAKE CHAMBERS HUBS AND DRUMS	DISC BRAKES MAXX 22t 415mm wabco 233 HM 518445. HXL5 SYNTHETIC GREASE Standard 20/24 10 studs disc hubs, balanced drums 104.5 lbs, outboard mount, 285.75mm B.C., single flange nuts. For dual aluminium wheels. RIMS Alcoa, aluminum, "ULTRA ONE", 24.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts. SPACERS Wheel guard 10 holes. Located between the inside wheel and the drum and between two wheels. TIRES Plant choice 24.5. 11R24.5 43.7 DIA
AIR SYSTEM GLAD HANDS AIR VALVES VALVE VALVE	Fixed. Meritor Wabco, ABS, 2 sensors 1 modulator. Quick and brake release valves on air lift. Manual blow down valve in a control box, WITHOUT auto-reset feature, including Glycerin filled pressure gauge, in P.S.I., to indicate load with a conversion table. CONTROL BOX Stainless steel.
ACCESSORIES REGISTRATION HOLDER WINCHES WINCHES SLIDING TRACK STORAGE BOX(ES) MUD FLAPS EXTRA MUD FLAPS RACK	One plastic, Betts-PS-1 or equivalent. Qty: 2 , KINEDYNE #3820SPC-SV (6.5"), fixed recessed, Located: ROAD SIDE AT 41 1/2" & 65 1/2" Qty: 13, ANCRA #49207-127-XZ, zinc plated slider (6 7/8"). Full length, "LL" extruded aluminum, road side. Qty: 1 , TREBOR aluminum CKPL finish box, double doors, hinges on sides, antirack lock. 24" deep x 24" high x 60" wide. Located at CURBSIDE AHEAD OF SUSPENSION One set, rubber with Manac logo and vertical grooves to reduce spray. Black rubber w/logo Manac, logo toward the front (#303-0011). Located: Under the flanges ahead of the tridem, 48" wide. (To protect air booster & the suspensions). Ref. 212871. Made of 1/4" formed aluminum plate, 98" inside net, bolted to web and crossmembers. Located at: MIDWAY EACH SIDE
FINISHING PAINT AXLE(S) PAINTED HUBS WHEELS OR RIMS RETROREFLECTIVE TAPES PAINT	Ready for Galvanized plateform. Painted with acrylic urethane, color: Black, code : PPG AU37-FP908. Black. Natural. Conspicuity striping in compliance with CMVSS 108. Gray and red each side, fully covers rear sill and horizontal underride protection bar. V.I.N. plate to be stick on an aluminum plate riveted on the frame. Pre-drill the web prior to galvanizing



ITEM	DESCRIPTION
ANNEX(ES) ATTACHED R	Ref: 212871
GALVANIZED CHOICES PLATFORM	Galvanized choices. Galvanized platform. (no paint) ** WARNING: holes parachute shaped required for dripping **
CONFORMITY	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.
<div>DISCLAIMER</div> <div>Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.</div>	