

# HALE

## TRAILER

### BRAKE & WHEEL



A017384-A017385  
VIN: 5A3478-5A3479

#### SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer



**800-232-6535** \*FINANCING AVAILABLE

#### Magnitude 60 MFLD 3+1 Modular (Flat Level Deck) Tridem Bogie (Model: MAGNITUDE 60 MFLD)

	Est. Wt.: 25,080# +/- 3%
<b>Capacity:</b> 60 tons in 12-foot length with 4th axle close coupled or 3+1 axle configuration - GAWR and GVWR determine legal payloads	
<b>Load Base:</b> 12-foot rigid 2-point load centered in deck area	
<b>Length (Trailer Only):</b> 52 feet 9 inches (with standard deck length and axle spread)	
<b>Compatibility:</b> Designed to accept optional 51/60 rear axle, spreader, and/or 36 or 83 inch flip box	
<b>Accent Package:</b> None	
<b>Gooseneck Design:</b> Narrow hydraulic removable non-ground bearing - swing radius of 106 inches (12ft 8in overall gooseneck length) set up for wetline operation	
<b>Loaded Fifth Wheel Height:</b> Dual Cam Pawl Arm Assembly with 7 ride height positions (50 inches nominal)	
<b>Kingpin:</b> Removable kingpin at 86 and 106 inch radius	
<b>Power Source:</b> Set up for wet line operation	
<b>VIN Plate:</b> Bilingual VIN plate	
<b>Registration/Document Holder:</b> Registration/document holder installed	
<b>Hydraulic Fittings:</b> OEM Standard 1/2 inch	
<b>Framework:</b> All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs	
<b>Deck Design:</b> Flat level deck (MFLD) design	
<b>Deck Width:</b> 8 feet 6 inches overall (unless optional deck width is selected)	
<b>Deck Length:</b> Flat Level Deck (FLD) design - 26 feet clear deck length - Standard OAL is 52 feet 9 inches with standard axle spread	
<b>Loaded Deck Height:</b> 22 inches with 6 inches ground clearance	
<b>Crossmembers:</b> On 24 inch centers (nominal)	
<b>Flooring:</b> 2 inch nominal wood	
<b>Front Ramps:</b> Manual front approach ramps with risers	
<b>Extension Brackets:</b> 13 pair - 26 total removable swing type, 1 pair - 2 total heavy duty removable hook-on type	
<b>Tool Box:</b> 2 Fully covered trays in front of deck between mainbeams with lockable covers	
<b>Hammer Plate:</b> None	
<b>Front Bogie Ramp:</b> Included	
<b>Boom Trough:</b> V crossmembers with bolt-in V pan	
<b>Deck to Bogie Connection:</b> Modular	
<b>Bolsters:</b> Recessed	
<b>Covered Rear Bogie:</b> None	
<b>Rear Bogie Height:</b> 40 7/8 inches to top flange - 36 5/8 inches to top of bolsters	
<b>Connections for Future Axle Attachment:</b> Air and electrical connections to go along with connecting ears	
<b>Number of Axles:</b> 3 axles	
<b>Axle Capacity:</b> 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
<b>Axle Spread:</b> 54.5 inches (between axles)	
<b>Dust Shields:</b> None	

<b>Brakes:</b> 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
<b>Spring Brakes:</b> None	
<b>Suspension:</b> Air ride	
<b>ABS:</b> None required	
<b>First Axle Lift:</b> Chain Lift on first axle	
<b>Third Axle Lift:</b> Air lift installed on third axle	
<b>Load Scale:</b> None Standard	
<b>Liquid Filled Gauge:</b> None	
<b>Ride Height Control:</b> 7-position mechanical ride height control system	
<b>Dump Valve:</b> Manual Dump Valve (Push Pull)	
<b>Wheels:</b> 8.25 x 22.5 lvL One buffed/steel disc inside - hub-piloted	
<b>Tires:</b> 275/70R 22.5 OEM Standard	
<b>Hubodometer:</b> None Standard	
<b>Tire Inflation:</b> None Standard	
<b>Electrical System:</b> DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes	
<b>Tail Lights:</b> 3 tail light package	
<b>Electrical Receptacle:</b> J560 7-pin connector	
<b>Marker Lights:</b> 3 marker lights per side including mid turn	
<b>Additional Marker Lights:</b> None Standard	
<b>Paint:</b> Fontaine black polyurethane enamel	
<b>Lash Rings:</b> 17 pair - 34 total (with standard deck selected)	
<b>Flag Holders:</b> 2 pair flag holders	
<b>Flipbox:</b> None included	
<b>Flip Axle (Rear):</b> None	
<b>Hydraulic Flip Axle Option:</b> None Standard	
<b>Dust Shields on Rear Flip Axle:</b> None	
<b>Spreader:</b> None	
<b>Additional Options:</b>	
<b>Suspension 30K GAWR 24,700</b>	

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.  
Equipment availability, prices and specifications are subject to change without notice.