



Hale Trailer Brake & Wheel 017420-017431

Base Model: DF53 3 Axle

components description

CAPACITY Heavy Duty Beam Package - 100,000 lbs. GVWR (80,000 in 10' Span Closed)

OVERALL LENGTH 53' - Base Weight 12,900#

UPPER DECK LENGTH 11'(Requires Min. 3/4" Bottom Flange Neck Only)

LOWER DECK LENGTH 42'

OVERALL WIDTH 8' 6"

KING PIN SETTING 24" - Tapered Front

UPPER COUPLER PLATE 1/4"

UPPER COUPLER HEIGHT 48"

BULKHEAD None

MAIN FRAME 26"-PreCamb.I-Beams-(100K Pkg 1/2"x 5" Top & 3/4" x 5" Bottom & 1/4"Web & TRP)

SIDE RAILS 6" - 6.5# Per Foot

TOP DECK FLOOR SILLS 4" Steel I-Beam - 18" O.C.

LOWER DECK FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg

COIL HAUL PACKAGE None

FLOOR DECKING 1-1/8" Apitong

WINCHES 12

STRAPS None

WINCH TRACK Steel Slide Entire Length of Drivers Side

LANDING GEAR Two Speed

SUSPENSIONS Air Ride - 3 Axle - Hendrickson - 25K - (2)AK780 & (1)AK781

** Hendrickson (2)AK780 & (1)AK781 **

** Lift Center Axle - UBL - 002 **

SUSPENSION LOCATION Set at Rear most Position

AXLES (3) 25K Cap.-Type 30 Chambers-Auto Slacks-ABS-Air Ride-22.5 Tires

** Hendrickson (2)AK780 & (1)AK781 **

** Lift Center Axle - Cal 50 **

AXLE SPACING 61" Spread

LIFT AXLE Air Lift 1 Axle - Center (+195#)

DUMP VALVE Manual-Position In Front of 1st Axle D/S No Box-Dump All Axles(+5#)

SCALES None



PARKING BRAKES All Axles
ABS SYSTEM ABS system 4S/2M
DUST SHEILDS None
WHEELS Disc - Hub Piloted - 22.5 - Steel (672#)
TIRES 255/70R 22.5 - 41" Loaded Deck Height - Double Coin
TIRE INFLATION SYSTEM None
ANTI-SAIL MUD FLAPS Behind Rear Axle
STAKE POCKETS 24" O.C. Sides & 4 Across Front, 5 Across Rear
PIPE SPOOLS Double
RUB BAND STEEL 3/8" X 2-1/2" Recessed for DOT Tape
OILFIELD FRONT None
DOCK BUMPERS Rubber Inboard
OILFIELD REAR NECK None
OILFIELD - PIN POCKETS None
DECK ROLLERS None
TAILROLLERS None
CARGO TIE DOWN None
CONTAINER TWIST LOCKS NONE
TIRE CARRIERS None
TOOLBOX MATERIAL None
TOOLBOX TYPE None
TOOLBOX LOCATION None
LIGHTS Sealed Wiring Harness w/ LED Pkg
CUSTOM LIGHTS None
PAINT Black
CUSTOM 1. None
CUSTOM 2. None
CUSTOM 3. None

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.