



## Hale Trailer Brake & Wheel

017438-017440

Serial #:17438-17440  
components description  
CAPACITY 35 Ton  
OVERALL LENGTH 45'  
OVERALL WIDTH 8' 6"  
DECK LENGTH 27'  
DECK HEIGHT 38" - Loaded  
DECK FLOORING Apitong - 1 1/2" - Covering Entire Deck  
MAINBEAMS 16" Fabricated I-Beam - Positive Camber  
SIDE RAILS 12" Fabricated I-Beams - Positive Camber  
GOOSENECK Flat Deck Wood w/ 21 Degree Slope - Steel & Traction Bars  
KING PIN SETTING 18"  
KING PIN PLATE 5/16 Plate  
KING PIN SWING RADIUS 84"  
KING PIN HEIGHT 48"  
DOVETAIL 4' Steel w/ Traction Bars  
WHEEL WELL Covered w/ Steel Plate & Traction Bars  
LOADING RAMP Spring Assisted - 72" x 24" - Self Cleaning  
LANDING GEAR Two Speed - 50,000 lbs.  
D RING 16  
TOOL BOX IN GOOSENECK Tool Box in Gooseneck  
AXLE (2) 25,000 lb. Capacity w/ 49" Axle Spacings, Auto Slack, ABS  
SUSPENSION Hutchens - 3 Point, 4 SPRING - 56,000 lb Capacity  
WHEELS Disc - Hub Piloted  
TIRES 255/70R22.5  
PARKING BRAKES Type 30/30 Spring Brakes - 2 Axle  
WIRING D.O.T Sealed Wiring Harness  
LIGHTS LED Pkg - Sealed Lights Rubber Mounted  
PAINT Black  
CUSTOM 1 None  
CUSTOM 2 None  
CUSTOM 3 None

### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.