

## SALES SERVICE RENTALS | PARTS Allentown, PA: 800-828-3055 800-383-8894 Jacksonville, FL: Baltimore, MD: Little Rock, AR: 833-424-8944 888-601-7500 Boston, MA: 800-854-5310 Portland, ME: 800-325-4253 Concord, NC: 800-438-2250 Richmond, VA: 866-839-3495 Delmar, DE: 866-486-1400 Scranton, PA: 800-569-1400

HaleTrailer.com | @haletrailer f y 庙 🎯 🔠

888-673-5011

800-544-7127

**800-232-6535** \*FINANCING AVAILABLE

Springfield, MA:

Voorhees, NJ:

800-854-5306

866-315-0235

| Length            | 33                             | BOD             | Y SPECIFICATIONS             | Body             |                              |
|-------------------|--------------------------------|-----------------|------------------------------|------------------|------------------------------|
| Width             | 96" INBOARD                    | Tarp            | NONE                         | Accessories      |                              |
| Side Height       | 64" SOLID                      | Bow Holders     | NONE                         |                  |                              |
| Top Rail          | 9" DUMP                        | Tarp Bows       | NONE                         |                  |                              |
| Side Matl-front   | 4'100 WALL                     | Tarp Basket     | NONE                         |                  |                              |
| -middle           | 23'140 WALL                    | Tarp Hooks      | NONE                         |                  | TAILGATE                     |
| -rear             | 6'180 WALL                     | Bulkhead Mat'l  | 3/16" (10)                   | Height           | FULL - GENESIS               |
| Side Options      | NONE                           | Bulkhead        | D/S-MANDOOR                  | Mat'l Thkness    | .140 WALL                    |
| Floor Mat'l       | 1/4" FULL LENGTH               | Options         | 5" SLOPE PLATES              | Slope            | NONE                         |
|                   |                                | Body Fenders    | 18"                          | Hinges           | OVERSLUNG                    |
| Crsmbr Spacing    | 12"                            | Ladders (Out)   | D/S-REAR                     | Side Swing       | YES -W / GRD CNTRL-P/S HINGE |
|                   |                                |                 |                              | Gateseal         | RUBBER                       |
| Floor Options     | STUB LONGITUDINALS             | Inside          | NONE                         |                  |                              |
|                   |                                |                 |                              | Safety Latch     | ONE EACH SIDE                |
|                   |                                | Shovel Hgr      | INSIDE P/S OF DOGHOUSE       |                  |                              |
| Tailgate Control  | AIR / FRAME + ELEC CC (4)      |                 |                              | Coal/Grain Door  | NONE                         |
| Body Pkg          | NONE                           | Light Panel     | FULL - LED; X=LED B/U LIGHTS |                  |                              |
| Options           |                                |                 | OOOX ooo XOOO (11)           | Coal Chute       | NONE                         |
| Vibrator          | NONE                           | Marker Lights   | LED - 5 PR TOP & BOTTOM      | Gate Options     |                              |
| Mudflaps          | STD + ACROSS REAR (1)          | MMTS            | BELOW RAIL - LED             |                  |                              |
|                   |                                | Apron           | NONE                         |                  |                              |
|                   |                                |                 | CHASSIS SPECIFICATIONS       |                  |                              |
| Model             | TRIAXLE-2 FIXED-FRONT LIFT     | ABS             | 2S/1M                        | Tire Carrier     | NONE                         |
| Beam Mat'l        | ALUMINUM                       |                 |                              | Landing Gear     | 2 SPEED JOST AX150           |
| Length            | 34'                            |                 |                              |                  | D/S CRANK                    |
| Width             | 96"                            | Independ. Susp( | s)                           | Chassis Lights   | NONE                         |
| Hoist             | 85-265 (2)(10)                 |                 |                              |                  |                              |
| Chassis Neck      | STD                            |                 |                              | Elec Coupler     | 7 WAY + ISO 7 WAY LABELED    |
| King Pin Setting  | 18"                            | Distance        | :                            |                  | AUXILIARY (2)                |
| 5th Whl Plate     | 3/8" W/ 3/8"X 3" X 7" MOUNT    | From:           |                              | Hyd Tank         | NONE                         |
| 5th Whl Ht        | 50"                            |                 |                              | Hyd Hose Fitting | WINGNUT                      |
| Overhang          | 6"                             | Controls        |                              | Hyd Hose Length  | 108"                         |
| Rear Axle Setting | 21.5"                          |                 |                              | Tow Hooks        | TWO-ONE EACH SIDE            |
| K/P To Rear Axle  | 411.5"                         |                 |                              | Paint            | BLACK SOFTCOAT               |
| Suspension        | AAT30K / E3-2 L LIFT-E1 (3)(5) | Location        |                              |                  |                              |
| Susp Control      | FRAME + ELEC CC (4)(9)         | Axle(s)         |                              |                  | NONE                         |
| Susp Spacing      | 52" - 52" (6)                  |                 |                              |                  |                              |
| Susp Options      | GALVANIZED HANGERS             | Accessories     |                              | Chassis          | CHASSIS REAR CM: TAPERED     |
| Springs           | AIR                            |                 |                              | Options:         | W/ DIAMOND PLATE COVER       |
| Axles             | TP SPINDLES                    | Brakes          |                              |                  |                              |
| Accessories       | NONE                           | Drums           |                              |                  |                              |
| Brakes            | 16-1/2" x 7"                   | Hubs            |                              |                  |                              |
| Drums             | CAST                           |                 |                              |                  | TIREMAXX PRO INFLATION       |
| Hubs              | 10 STUD STEEL                  | Wheels          |                              |                  | SYSTEM ALL AXLES             |
| Wheels            | 8.25 x 24.5 12 HP              | Tires           |                              |                  |                              |
| Tires             | 11R 24.5 R250 ED 16PLY BS      |                 |                              |                  |                              |

Des Moines, IA:

Elkton, MD:

## **REMARKS:**

| 1. BLACK RUBBER FLAP AHEAD OF AXLE #1 IN THE CENTER. INSTALL 4" FORWARD OF STANDARD POSITION. | WEIGHT: | 14,036 |
|---|---------|--------|
| 2. ADD JUNCTION BOX @ INSIDE FRAME RAIL W/ 7 WIRE FROM AUXIL PLUG IN TO JUNCTION BOX          |         |        |
| 3. RIGHT WEIGH OIL FILLED GAUGE (KG) (FLUSH) ON FRONT CHASSIS CROSSMEMBER.                    |         |        |

- 4. WIRED TO AUXILIARY ISO 7 WAY PLUG
- 5. HEIGHT CONTROL VALVE ON AXLE #2.
  6. LIFT AXLE TO BE CONTROLLED THROUGH FRAME SWITCH & ELEC CC (WIRED TO AUX 7 WAY PLUG) AND TO HAVE BRAKE RELEASE (LIFT AXLE TO SPIN FREELY).
- 7. ALL FRAME SWITCHES TO BE IN POLY BOX ON D/S NEAR LANDING GEAR.- AIR IN THE BOX
- 8. PLASTIC INSULATORS BETWEEN WHEEL/DRUM & WHEEL/HUB ALL AXLES.
- 9. INSTALL CROSSOVER KITS
- 10. NO OUTSIDE ACCESS OR FLAP ON OUTSIDE OF BULKHEAD FOR HOIST-ONLY ON INSIDE DOGHOUSE.
- 11. LED BACK UP LIGHTS WIRED TO AUXILIARY ISO 7 WAY PLUG