

HALE TRAILER BRAKE & WHEEL



A017617-A017636
VIN: 77058-77077

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

FRAME TYPE MVP SS

Model # TRAR34AA640-2024 **Weight** 13860 lbs. *** **Cubic Yards** 51

BODY

LOAD PROFILE	MATERIAL, 80K GVWR
LENGTH	34
WIDTH	96
FLOOR	1/4 IN. W/ 3/8 IN. LAST 10 FT.
STUB LONGITUDINALS	YES
CROSSMEMBER SPACING	12 IN.
COAL BUCKET FLOOR BRACING	NONE
SIDE PLACEMENT	OUTSET SMOOTH SIDE PANEL
FLOOR LINER	NONE
BODY HOLD DOWN	NONE
VIBRATOR	NONE
RUBBER SEAL	YES
REAR HINGE PIN	STANDARD
AIR FAIRINGS	NONE
WALL HEIGHT	64
WALL THICKNESS	67% STANDARD 1.5" PANELS - .150" WALL & 33% - HEAVY 1.5" PANELS - .175" WALL
WALL LINER	NONE
TOP RAIL OPTION	SOLID
SOLID	
REAR POCKET SLOPE	2.75
HOIST	8-5-265 - CUSTOM
REMOTE GREASE	SINGLE POINT REMOTE REAR
BULKHEAD	3/16 IN.
BULKHEAD TYPE	RADIUS CORNERS
BULKHEAD DOOR	BULKHEAD DOOR D.S.
Two handles for mandoor	
BULKHEAD SLOPE PLATES	YES, 18 IN.
5 Incn slope plates in front	
LOWER BULKHEAD WRAP	YES
BULKHEAD STEPS	BULKHEAD STEPS OUT (D.S.)
SIDES STEPS D.S.	LAST INSIDE & OUTSIDE
Use alum angle for inside steps	
SIDES STEPS C.S.	NONE
SHOVEL HANGER	YES, CURB SIDE
FRONT FENDERS WITH FLAPS	6 IN. W/ FLAPS
ALUMINUM ROLL CAP	NONE
REAR END STYLE	SQUARED-OFF

LIGHTS

LIGHT TYPE	GROTE L.E.D. W/ GROMMET
LIGHT PANEL	3 LARGE-3 SMALL-3 LARGE (FULL LIGHT PANEL) OOO ooo OOO
APRON	3/8 IN. X 1-1/2 IN. FULL LIGHT SHIELD
STD. MARKER LIGHTS	(7) EACH SIDE

Add 1 extra pair of led marker lights on bulkhead 8 inches down from top

MID-TURNS	(1) PAIR L.E.D. (NON-COMBO)
BACK-UP LIGHTS	NONE
AUXILIARY CABLE	7 WAY
BACK-UP LIGHT WIRE	NONE
REAR POCKET LIGHTS	1 PAIR

GATE

GATE SHEET THICKNESS	VERTICAL PANELS
GATE OPERATION	ELECTRIC ON BLACK WIRE & BALL VALVE
HINGE TYPE	O. S. SWING C.S. W/ INPOCKET GROUND CONTROL
COAL DOOR	12 IN. STAINLESS HANDLE
CHUTE	NONE
DOUBLE HANDLE DOOR	NONE
GATE BRACING	NO BRACING (SMOOTH SIDE PANELS)
GATE STIFFENER	NONE
PUSHER BLOCK	NONE
HALF ROUND ON GATE	NONE
ANGLE ON TOP OF GATE	NONE
SPREADER CHAINS	NONE
WINDERS / SAFETY LATCH	WINDERS (1) EACH SIDE
GATE STEPS	NONE
TARP HOOKS	NONE
GATE LINER	NONE

PRIMARY AXLES

MODEL	TRI-AXLE
NO. OF PRIMARY AXLES	2
SUSPENSION	HEND. INTRAAX AAT-30K W/ HXL-5
AXLE SPACING	52
AXLES	AXLE FOR INTRAAX ONLY
BRAKES	7 IN. XL, W/ 30-30 CHAMBERS
CAM GUARDS	HEND. INTRAAX
HUB AND DRUM	CAST W/ STEEL HUB HP 10 STUD TP, LS, 7 IN.
TIRES	CONTINENTAL HSR2 11R 24.5 16 PLY
WHEELS	ALUMINUM HP 24.5X8.25 - ALL POLISHED (XP)
PRIMARY AXLE TIRE INFLATION SYSTEM	NONE

LIFT AXLES

NO. OF LIFT AXLES	1
LIFT AXLE SUSPENSION	HEND. INTRAAX AAL 30K (4) TIRES W/HXL-5
LIFT KIT	HEND. UBL-002 (INTRAAX AAL)
LIFT AXLE DISTANCE	52
LIFT AXLE	AXLE FOR INTRAAX ONLY
LIFT AXLE BRAKES	7 IN. XL, W/ 30-30 CHAMBERS
LIFT AXLE CAM GUARDS	HEND. INTRAAX
LIFT AXLE HUB AND DRUM	CAST W/ DURALITE HUB HP OB 10 STUD TP, LS, 7 IN.
LIFT AXLE TIRES	CONTINENTAL HSR2 11R 24.5 16 PLY
LIFT AXLE WHEELS	ALUMINUM HP 24.5X8.25 - ALL POLISHED (XP)
LIFT AXLE CONTROLS	ELECTRIC UP THRU AUX. & BALL VALVE (NO / REG.)
FREE WHEEL VALVE	NONE
LIFT AXLE TIRE INFLATION SYSTEM	NONE

STEERABLE LIFT AXLES

NO. OF STEERABLE AXLES	0
STEERABLE AXLE SUSPENSION	NONE

STEERABLE AXLE DISTANCE	N/A
STEERABLE AXLES	NONE
STEERABLE AXLE BRAKES	NONE
STEERABLE AXLE HUB AND DRUMS	NONE
STEERABLE AXLE TIRES	NONE
STEERABLE AXLE WHEELS	NONE
STEERABLE AXLE CONTROLS	NONE

CHASSIS

FRAME RAILS	17 IN. ALUMINUM BEAMS
RUBBER CUSHION RIDE	YES
NO. OF INCHES FOR GOOSENECK	NO GOOSENECK, 9.25 I.O. IN. HEIGHT
LID FOR GOOSENECK	NONE
PIN SETTING	16
5TH WHEEL PLATE	5/16
5TH WHEEL PLATE HEIGHT	49 IN. HIGH
KING PIN	.500 KING PIN ONLY
NO. OF INCHES FOR REAR OVERHANG	6
TRACTOR DRIVE MODEL	TANDEM DRIVE
GALVANIZED SUSPENSION HANGERS	YES
STIFFENER PLATE	NONE
HOIST & MOUNT STYLE	3 IN. X 6 IN. X 3/8 IN.
SUSPENSION CONTROL	ELECTRIC THRU AUX. & BALL VALVE
ABS FOR TRAILER	(1) 2S1M MERITOR / WABCO
SLACKS	AUTOMATIC
CHROME TOP HATS	NONE
AXLE LUBRICATION	HXL, SYNTHETIC SEMI-FLUID GREASE
HUBODOMETER	NONE
DUST COVERS	NONE
TIRE CARRIER(S)	NONE
DOLLIES - LANDING GEAR - LANDING LEGS	JOST AX-150 - (55,000 LB.) - 10 YEAR ALUMINUM - D.S.
SHIMS	MYLAR
REGISTRATION HOLDER	BETTS PS-1 W/ SIGHT GLASS (ROUND HOLDER)
AIR GAUGE / SYSTEM	NONE
ENCLOSURE FOR SWITCHES	STAINLESS STEEL

mount dside behund dollies

AIR TANKS	ALUMINUM TANK
HYDRAULIC HOSE FITTING	1 IN. X 108 IN. HOSE W/ WING FITTING
FLAPS FRONT OF TIRES	FLAP IN FRONT OF FRONT AXLE
FLAPS REAR OF TIRES	FULL RUBBER ACROSS REAR OF TRAILER
TOW HOOKS	NONE
BUMPER	NONE

TARP

TARP MANUFACTURER	NONE
TARP CONTROL	NONE
TARP COLOR	NONE
BOW HOLDERS	NONE
TARP BRACKET	NONE

PAINT

HANGERS	GALVANIZED
SUSPENSION COLOR	BLACK SOFT COAT
DOLLIES	BLACK (931716)
HOIST COLOR	BLACK (931716)
5TH WHEEL PLATE COLOR	BLACK (931716)
PIN STRIPING	BLACK (931716)
MAC MACHINE FINISH LOGOS	BLACK (931716)
OPTIONAL SIGNS	NONE

ACCESSORIES

NO. OF CHAIN TIE DOWNS (PER PAIR) (CUSTOMER MUST SPECIFY LOCATION)	NONE
TOW MOTOR PACKAGE	NONE
COIL RACK ANGLES	NONE
LOAD LEVEL INDICATOR	NONE
3-1/2 IN. ANGLES UNDER RAIL	NONE

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.