



**A017683-A017686**  
**VIN: S017105-S017108**

**SALES | RENTALS | PARTS | SERVICE**

- |                                     |                                       |
|-------------------------------------|---------------------------------------|
| <b>Allentown, PA:</b> 800-383-8894  | <b>Jacksonville, FL:</b> 800-828-3055 |
| <b>Baltimore, MD:</b> 888-601-7500  | <b>Little Rock, AR:</b> 833-424-8944  |
| <b>Boston, MA:</b> 800-854-5310     | <b>Portland, ME:</b> 800-325-4253     |
| <b>Concord, NC:</b> 800-438-2250    | <b>Richmond, VA:</b> 866-839-3495     |
| <b>Delmar, DE:</b> 866-486-1400     | <b>Scranton, PA:</b> 800-569-1400     |
| <b>Des Moines, IA:</b> 888-673-5011 | <b>Springfield, MA:</b> 800-854-5306  |
| <b>Elkton, MD:</b> 800-544-7127     | <b>Voorhees, NJ:</b> 866-315-0235     |

HaleTrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE



**Trailer Model:** *Kalyn Hydraulic Sliding Axle (KHSA) 2 Axle, 40 Ton, 50' Model*

<u>2 Axle, 40 Ton, 50' Model Standard Equipment</u>	
Net Capacity: 40 Tons	80,000 lbs Distributed in 50 ft, 50,000 lbs Concentrated in 10 ft
Nominal: 50 feet OAL	Kingpin to center of rear axle 40 feet in Transport Mode
8 feet 6 inches Wide	Dump angle 16° Loading angle 7°
<b>GOOSENECK:</b>	<b>SUSPENSION:</b>
10'-8" Gooseneck Length (48' & 50') / 11'-6" (53')	25,000 lb nominal capacity with Oil seals, 5/8" wall, tapered spindles
48" Loaded 5th Wheel Height, 18" Kingpin Setting	50" axle spacing 71" track
86" Swing Radius (48' & 50') / 96" Swing Radius (53')	12-1/4" x 7-1/2" Brakes ABS Module: 2S1M
20,000# Planetary Winch With Air Clutch; 100' of 5/8" Cable	Auto Slack Adjusters and Spring Brakes on all Axles
Work lights on the winch 2 Tool compartments	6.75 x 17.5 Hub Piloted Disc Wheels
Wet Kit: Trailer Operation; 3/4" Hydraulic Couplings	235/75 R 17.5 16PR Tires Manual Dump Valve
Integrated Tool Box in Neck W/ Stainless Hinges and Alum. Door	Suspension: Ridewell or Equivalent Air ride Air Ride
2-Speed Landing Gear , Crank Handle Roadside	Alignment Bracket for Sliding Suspension
<b>DECK:</b>	<b>GENERAL:</b>
Nominal Deck Length: 39.34 feet	12 Volt System with 7 way Sealed Harness
Nominal Deck Width: 102 in	DOT Rubber Mounted Sealed Beam LED Lights
Loaded Deck Height: 37 in	Epoxy Primer & Black Polyurethane Paint
4 Beam design - 100,000 psi yield flanges & 80,000 web minimum	2 Function Wireless Remote for Winch
14" tall main beams and 15" tall side rails	Heavy Duty DOT Approved Bumper
4" I-beam cross members on 9" Centers, 1-3/8" Apitong Deck (full width)	Red & White Conspicuity tape KS Mud Flaps
Double Key Hole Chain Slots in Upper Flange on 36" Centers	3 LED marker lights each side including mid turn
Double Key Hole Chain Slots Along Center of Deck on 36" Centers	Strobe light with toggle switch on rear
Reinforced Rear Approach Plate with 6 Chain Slots	
Cable Roller Centered at Front of Lower Deck	

<u>Kalyn Hydraulic Sliding Axle (KHSA) Optional Equipment</u>	
<b>Models</b>	
<input checked="" type="radio"/> <b>2 Axle, 40 Ton, 50' Model</b>	<input checked="" type="checkbox"/> <b>Aluminum Wheels OS (Polished) all Axle</b>
<b>Options</b>	<input checked="" type="radio"/> <b>OEM 235/75 R 17.5 16PR Tires</b>
<input checked="" type="checkbox"/> <b>6 Function Wireless Remote</b>	<input checked="" type="checkbox"/> <b>AirWeigh Load Scale</b>
	<input checked="" type="checkbox"/> <b>Tire Inflation</b>
	<input checked="" type="checkbox"/> <b>Central Lube - 18 Point Manual</b>
	<input checked="" type="checkbox"/> <b>Fully Galvanized with Black paint webs</b>
Estimated Weight of the Equipment with the options : <b>17,960</b> lbs.	

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.