	SALES	RENTALS	PARTS	SERVICE
	Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
	Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
TRAILER	Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
BRAKE & WHEEL	Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
	Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
A017687-A017688	Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
	Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235
VIN:S017109-S017110	.com   @hale	trailer f У	in Ø Yu	
	800-232	2-6535 *	FINANCING	AVAILABLE



## **Trailer Model:**

## Kalyn Hydraulic Sliding Axle (KHSA) 2 Axle, 40 Ton, 50' Model

		2 Axle, 40 Ton, 3	50' Model Standard Equipment				
Net Capacity:	40 Tons	80,000 lbs [	0,000 lbs Distributed in 50 ft, 50,000 lbs Concentrated in 10 ft				
Nominal:	50 feet OAL	Kingpin to c	Kingpin to center of rear axle 40 feet in Transport Mode				
	8 feet 6 inches Wide		Dump angle 16 °	Loading angle 7			
GOOSENECK:			SUSPENSION:				
10'-8" Gooseneck Le	ngth (48' & 50') / 11'-6" (53')		25,000 lb nominal capacity v	25,000 lb nominal capacity with Oil seals, 5/8" wall, tapered spindles			
48" Loaded 5th Wheel Height, 18" Kingpin Setting			50" axle spacing	50" axle spacing 71" track			
86" Swing Radius (48' & 50') / 96" Swing Radius (53')			12-1/4" x 7-1/2" Brakes	ABS Module: 2S1M			
20,000# Planetary Winch With Air Clutch; 100' of 5/8" Cable		Auto Slack Adjusters and Sp	Auto Slack Adjusters and Spring Brakes on all Axles				
Work lights on the wi	nch 2 Tool co	npartments	6.75 x 17.5 Hub Piloted Disc	6.75 x 17.5 Hub Piloted Disc Wheels			
Wet Kit: Trailer Operation	ation; 3/4" Hydraulic Coupling	S	235/75 R 17.5 16PR Tires	Manual Dump Valve			
Integrated Tool Box in Neck W/ Stainless Hinges and Alum. Door		Suspension: Ridewell or Equ	Suspension: Ridewell or Equivalent Air ride Air Ride				
2-Speed Landing Gear, Crank Handle Roadside			Alignment Bracket for Sliding	Alignment Bracket for Sliding Suspension			
DECK:			GENERAL:				
Nominal Deck Length	: 39.34 feet		12 Volt System with 7 way S	12 Volt System with 7 way Sealed Harness			
Nominal Deck Width:	102 in		DOT Rubber Mounted Seale	DOT Rubber Mounted Sealed Beam LED Lights			
Loaded Deck Height:	37 in		Epoxy Primer & Black Polyu	Epoxy Primer & Black Polyurethane Paint			
4 Beam design - 100	000 psi yield flanges & 80,00	0 web minimum	2 Function Wireless Remote	2 Function Wireless Remote for Winch			
14" tall main beams a	nd 15" tall side rails		Heavy Duty DOT Approved	Heavy Duty DOT Approved Bumper			
4" I-beam cross members on 9" Centers,1-3/8" Apitong Deck(full width)			Red & White Conspicuity tap	Red & White Conspicuity tape KS Mud Flaps			
Double Key Hole Chain Slots in Upper Flange on 36" Centers			3 LED marker lights each sid	3 LED marker lights each side including mid turn			
Double Key Hole Cha	in Slots Along Center of Dec	on 36" Centers	Strobe light with toggle swite	ch on rear			
Reinforced Rear App	roach Plate with 6 Chain Slot	6					
Cable Roller Centere	d at Front of Lower Deck						
<u>1odels</u>	Kalyn Hy	draulic Sliding Axl	e (KHSA) Optional Equipment				
2 Axle, 40 Ton, 50	Model		Aluminum Wheels OS (P	olished) all Axle			
Options			OEM 235/75 R 17.5 16PR Tires				
6 Function Wire	loss Pomoto						
	less Remote		AirWeigh Load Scale				
			✓ Tire Inflation				
			✓ 74,000 lb Dock Levelers (	(Independent Controls)			
		Central Lube - 18 Point M	1anual				
			Fully galvanized with B	lack paint webs			
Estimated Weight of	the Equipment with the c	ptions : <b>18,210</b>	lbs.				