

Velocity 48' Air Slider (Model: HAVSF12SAT)

Length / Width: 48 feet x 102 inches
Suspension Type: Sliding air tandem; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements
Frame Rating: 80,000 lbs distributed - GAWR and tire ratings determine legal payloads
Flooring: 1 1/8 inch wood
Crossmembers: 12 inch centers - 4 inch jr. I-steel
Side Rails: 6 inch structural channel @ 6.5 lbs/ft
Stake Pockets: 3/16 inch steel on 24 inch centers
Pipe Spools: Double between stake pockets
Rubrail: 3/8 inch x 2 1/2 inch steel
Main Beams: 130K load bearing flanges
Kingpin: 30 inches
Loaded Fifth Wheel Height: 49 inches
Landing Gear: OEM Standard with Forward & Rear Bracing
Knee Braces: Fabricated on approx. 60 inch C/C
Bulkheads: Included
Bulkhead Pockets: 4 - F-5 DOT-type steel
Number of Axles: 2
Axle Spindle:Tapered
Brakes:Spring brakes, auto slacks
Air Line Filters:(2) Meritor In-line type installed
ABS: 4S/2M - no cable or tool
Axle Spread: 49 inches
Hub and Drums: 10-hole hub-piloted with outboard cast drums
Wheel Ends: Grease in hubs - *** 5-year wheel end warranty ***
Wheels:22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD
Tires:11R 22.5 14PR OEM standard tires
Tire Inflation System:None standard
Suspension Detail: Hendrickson AAZNT46K Intraax air ride slider - 60 inches adjustable
Air Assist Slide Box Pins:Standard mount of controls on slider frame
Auto Glad Hand Dump:Installed
Front Corners: Tapered
Electrical System:LED: 3 lights/side, 2 lights/side on rear- STANDARD
Paint:Black urethane with Velocity decals - STANDARD
Conspicuity Tape: Per NHTSA specs - installed on rubrails
Bumper: Weld-on type - meets underride requirements
Mudflaps: 1 set OEM standard
Spare Tire Carrier:None standard
Winch Track: Steel on road side
Sliding Winches:12 standard
27 foot Winch Straps:None standard
30 foot Winch Straps:None standard
Dock Bumpers: 1 pair rubber on rear
Hubodometer:None standard
Registration Holder:Install registration holder - OEM standard
Tool Box:None standard
VIN Plate: Bilingual US/Canadian VIN plate

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.

