

RENTALS | PARTS SERVICE 800-383-8894 Jacksonville, FL: 800-828-3055 888-601-7500 Little Rock, AR: 833-424-8944 800-854-5310 Portland, ME: 800-325-4253 800-438-2250 Richmond, VA: 866-839-3495 866-486-1400 Scranton, PA: 800-569-1400 888-673-5011 Springfield, MA: 800-854-5306 Voorhees, NJ: 800-544-7127 866-315-0235

800-232-0535 FINANCING AVAILABLE	
Description Model: Aluminum-A	RA/3A
ARA	
9500 GALLONS	
1 PERCENT (MINIMUM)	
49 CFR 173.247	
ATMOSPHERIC	
ASPHALT TYPE, LIGHT WEIGHT STYLE	
400 DEGREE	
5454-H32 ALUMINUM	
(2) ALUMINUM	
ONE	
3-DISC	
4" FIBERGLASS, 1# DENSITY, NOT COMPRESSED	
0.040" SIDE SHEETS/0.060" HEADS	
6" VALVE W/ 3" LINE & CAMLOCK CAP. INCLUDES 3/4" PORT FOWASHOUT CONNECTION.)R
3" VALVE W/ SWIVEL & INTERNAL LINE, OUTLET TERMINATING A 3" CAMLOCK ADAPTER & CAP. INCLUDES 3/4" PORT FOR WASHOUT CONNECTION AND 8' HOSE TROUGH ON RH FRONT FENDER.	
4" AT REAR UNLOADING LINE	
3" DIAL IN WELL W/ PLEXIGLASS COVER	
20" ASPHALT TYPE	
4 SIDED, ALUMINUM	
BENEATH MANHOLE	
2" EXTERNAL	
NONE	
ALUMINUM-CURBSIDE	
NONE	
20' ALUMINUM, CURBSIDE	
NONE	
ALUMINUM, FRONT & REAR WITH MUDFLAPS ON REAR FENDE MANUAL HOLDER ON FRONT ROADSIDE FENDER	RS.
L.E.D. TYPE WITH ALUMINUM LIGHT BOXES @ REAR	
LOW MOUNT	
WITH SLOPING OUTLET	
ALUMINUM, BOLT-ON	
PER DOT REQUIREMENTS	
ADJUSTABLE	
HD ALUMINUM FRAME	
MARK V HEAVY DUTY	
ADDITIONAL FORWARD BRACING	
	Description ARA 9500 GALLONS 1 PERCENT (MINIMUM) 49 CFR 173.247 ATMOSPHERIC ASPHALT TYPE, LIGHT WEIGHT STYLE 400 DEGREE 5454-H32 ALUMINUM (2) ALUMINUM ONE 3-DISC 4" FIBERGLASS, 1# DENSITY, NOT COMPRESSED 0.040" SIDE SHEETS/0.060" HEADS 6" VALVE W/ 3" LINE & CAMLOCK CAP. INCLUDES 3/4" PORT FOWN WASHOUT CONNECTION. 3" VALVE W/ SWIVEL & INTERNAL LINE, OUTLET TERMINATING A 3" CAMLOCK ADAPTER & CAP. INCLUDES 3/4" PORT FOWN WASHOUT CONNECTION AND 8" HOSE TROUGH ON RH FRONT FENDER. 4" AT REAR UNLOADING LINE 3" DIAL IN WELL W/ PLEXIGLASS COVER 20" ASPHALT TYPE 4 SIDED, ALUMINUM BENEATH MANHOLE 2" EXTERNAL NONE ALUMINUM, FRONT & REAR WITH MUDFLAPS ON REAR FENDE MANUAL HOLDER ON FRONT ROADSIDE FENDER L.E.D. TYPE WITH ALUMINUM LIGHT BOXES @ REAR LOW MOUNT WITH SLOPING OUTLET ALUMINUM, BOLT-ON PER DOT REQUIREMENTS ADJUSTABLE HD ALUMINUM FRAME MARK V HEAVY DUTY



BOGIE	ALUMINUM
SUSPENSION	INTRAAX AAT25K AIR RIDE TANDEM W/MANUAL EXHAUST
ADD ON AXLE	25,000# LIFT/STEERABLE AXLE IN FRONT OF TANDEM, MANUAL CONTROLS
AIR BRAKES	HALDEX DBLT, 25,000 LBS. RATING ON FIXED AXLES. 23,000 LBS. RATING ON LIFTABLE/STEERABLE AXLE
ANTI-LOCK BRAKES	2S/2M SYSTEM (2 SENSORS/2 MODULATORS)
AXLES	25,000# BEAM RATING WITH HP BEARINGS, 77-1/2" TRACK
HUBS	DUCTILE IRON
ALUMINUM DISC WHEELS	ACCURIDE STANDARD POLISHED,10-HOLE, HUB PILOTED
TIRES	11R24.5-H
AUTOMATIC TIRE INFLATION SYSTEM	AXLES PREPARED FOR TIREMAXX PRO, SYSTEM NOT INSTALLED
HUBODOMETER	ON DRIVER'S SIDE REARMOST AXLE
PAINT	STEEL PARTS ONLY-BLACK
CENTER PAINT BAND	14" WIDE BAND-BLACK
PLACARD KIT	SLIDE-IN TYPE W/ " HOT" PLACARD, 4 SIDES
SAMPLE VALVE	3/4"

Etnyre reserves the right to modify pricing on all quotes and orders with material and labor surcharges as needed