

# HALE

## TRAILER

### BRAKE & WHEEL



**A018040-A018045**  
**VIN: 5A3957-5A3962**

#### SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b>	<b>800-383-8894</b>	<b>Jacksonville, FL:</b>	<b>800-828-3055</b>
<b>Baltimore, MD:</b>	<b>888-601-7500</b>	<b>Little Rock, AR:</b>	<b>833-424-8944</b>
<b>Boston, MA:</b>	<b>800-854-5310</b>	<b>Portland, ME:</b>	<b>800-325-4253</b>
<b>Concord, NC:</b>	<b>800-438-2250</b>	<b>Richmond, VA:</b>	<b>866-839-3495</b>
<b>Delmar, DE:</b>	<b>866-486-1400</b>	<b>Scranton, PA:</b>	<b>800-569-1400</b>
<b>Des Moines, IA:</b>	<b>888-673-5011</b>	<b>Springfield, MA:</b>	<b>800-854-5306</b>
<b>Elkton, MD:</b>	<b>800-544-7127</b>	<b>Voorhees, NJ:</b>	<b>866-315-0235</b>

HaleTrailer.com | @haletrailer

**800-232-6535** \*FINANCING AVAILABLE

**Renegade XN20 Extendable Deck, Air Tandem, 20 inch Loaded Deck Height, Narrow Hydraulic Gooseneck (Model: RENEGADE XN20)**

	Est. Wt.: 22,350# +/- 3%
<b>Capacity:</b> 40 tons in 16-foot length - GAWR and GVWR determine legal loads	
<b>Load Base:</b> 16-foot rigid 2-point load centered in deck	
<b>Length (Trailer Only):</b> 50 feet 1 inch (closed); 71 feet 1 inch (open)	
<b>Width:</b> 8 feet 6 inches	
<b>Compatibility:</b> Designed to accept optional third flip axle	
<b>Gooseneck Design:</b> Narrow hydraulic removable non-ground bearing - swing radius of 102 inches (11 ft 11 in overall gooseneck length) - set up for wet line operation	
<b>Loaded Fifth Wheel Height:</b> 50 in nominal loaded fifth wheel height with 5 ride height positions	
<b>Power Source:</b> None	
<b>Deck Design:</b> Flat level telescopic deck design	
<b>Deck Length:</b> 29 feet 0 inches clear deck length (retracted) - 50 feet 0 inches (extended)	
<b>Loaded Deck Height:</b> 20 inches with 6 inches ground clearance	
<b>Flooring:</b> 1 3/8 inch nominal wood (full width)	
<b>Recessed Floor Mounted D-Ring Package:</b> None	
<b>Crossmembers:</b> On 24 inch centers	
<b>Front Ramps:</b> None, front of deck sloped top down to assist in loading with traction cleats	
<b>Extension Brackets:</b> Outriggers - 14 pair - 28 total removable swing type, 1 pair - 2 total removable hook-on type	
<b>Front Bogie Ramp:</b> Sloped steel bogie ramp (full width)	
<b>Deck to Bogie Connection:</b> Fixed	
<b>Number of Axles:</b> 2	
<b>Axle Capacity:</b> 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.	
<b>Axle Spread:</b> 54.5 inches spread (between axles)	
<b>Brakes:</b> 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount	
<b>Dust Shields:</b> None	
<b>Spring Brakes:</b> Spring brakes on 2 axles	
<b>Framework:</b> All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs	
<b>Suspension:</b> Air ride with automatic controls	
<b>ABS:</b> 4S/2M system without diagnostic tool and cable	
<b>Load Scale:</b> None Standard	
<b>Wheels:</b> 8.25 x 22.5 LVL One buffed outside/steel inside - hub-piloted	
<b>Tires:</b> 255/70R 22.5 H ply OEM Standard	
<b>Hubodometer:</b> None Standard	
<b>Tire Inflation:</b> None Standard	
<b>Covered Rear Bogie:</b> Rear bogie platform with 1 1/8 inch wood floor	
<b>Rear Bogie Height:</b> 41 inches	
<b>Bumper:</b> 3 tail light package	
<b>Mini Boom Trough &amp; Traction Cleats:</b> None	

<b>Connections for Future Axle Attachment:</b> Air and electrical connections to go along with connecting ears	
<b>Liquid Filled Gauge:</b> Included	
<b>Accent Package:</b> Stainless steel bumper insert	
<b>Electrical System:</b> DOT sealed beam and harness with LED lights and 4 inch flush mounted battery powered amber strobes	
<b>Electrical Receptacle:</b> J560 7-pin connector	
<b>Marker Lights:</b> 8 marker lights per side including mid-turn	
<b>Additional Marker Lights:</b> None Standard	
<b>Paint:</b> Fontaine black polyurethane enamel	
<b>Lash Rings:</b> 12 pair - 24 total	
<b>Flag Holders:</b> 2 pair flag holders	
<b>VIN Plate:</b> Bilingual VIN plate	
<b>Registration/Document Holder:</b> Registration/document holder installed	
<b>Flip Axle:</b> None	
<b>Dust Shields on Flip Axle:</b> None	

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.