

HALE TRAILER BRAKE & WHEEL








A018099-A018107

VIN: 41875-41883

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Base Model: FC48x102 Air Spread
CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)
OVERALL LENGTH 48' - Base Weight 10,380#
OVERALL WIDTH 8' 6"
KING PIN SETTING 30" - Tapered Front
UPPER COUPLER PLATE 1/4"
UPPER COUPLER HEIGHT 48"
FRONT SKIRT Aluminum Front and Corners
REAR SKIRT Aluminum
BULKHEAD None
MAIN FRAME 26" Fab.-PreCamb.I-Beams-(80K Pkg)
SIDE RAILS 6" - Alum- Extruded W/Double L Track
FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg.
COIL HAUL PACKAGE Single Coil Placement - 5 Extra Stud Sills-Ctr On Trailer
FLOOR DECKING 1-1/8" HD Aluminum W/ 2 Nailer Boards
WINCH TRACK Double L Aluminum- Extruded Siderail C/S & R/S- Both Sides
TIE BAR D/S & C/S - Full Length Both Sides - 3/8" x 2"
WINCHES 12 DOUBLE L (+)#75
STRAPS None
LANDING GEAR Two Speed - Jost A500
SUSPENSIONS Air Ride- Hendrickson - Intraax - 23K 2 Axle - Fixed
SUSPENSION LOCATION Set at Rear most Position - 32.5" Center of Rear Axle to Rear of Trailer
AXLES (2) 22.5K Capacity- Type 30 Chambers- Auto Slacks
HXL 5 Wheel Ends.
AXLE SPACING 10'2" Wide Spread
LIFT AXLE None
DUMP VALVE Elect.-Wired Thru Aux 7way Plug @ Front of Trailer-Dump Rear Axle(+9#)
SCALES None
ABS SYSTEM Wabco ABS System 2S/1M
PARKING BRAKES All Axles
DUST SHEILDS None
TIRE INFLATION SYSTEM Hendrickson Pro
TIRES 295/75R 22.5- DOUBLE COIN
WHEELS Disc - Hub Piloted - 22.5 - Polished Alum on 4 Outside(Only) Wheels(4-Steel Inner) (-148#)
ANTI-SAIL MUD FLAPS Behind All Axles
STAKE POCKETS 24" O.C. Sides & 5 Across Rear
RUB BAND ALUM 3/8" x 3" - Aluminum - Recessed for DOT Tape
SPOOL Triangular Shaped
DOCK BUMPERS Rubber Inboard
CARGO TIE DOWN 14 Pair of Recessed Chain Ties Evenly Spaced
TOOLBOX MATERIAL Aluminum Smooth Box and Doors
TOOLBOX TYPE 24HX24DX60L-ALUM. TOOLBOX DD SMOOTH-LOCKROD (CAM) STYLE (AG263)
TOOLBOX LOCATION Driver Side- Between Spread
CUSTOM LIGHTS None
LIGHTS Grote Ultra Blue Sealed Wiring Harness- 2 Micros Per Side & Mid Turn-3/3/3 Rear
PAINT Black - PPG Epoxy Primer and Acrylic Polyurethane - Shot Blasted

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.