

# HALE TRAILER BRAKE & WHEEL



A018173-A018193  
VIN: 570890-570910

## SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer

**800-232-6535** \*FINANCING AVAILABLE

## Infinity Flat 48' Wide Spread Air (Model: HAICF12WSA)

<b>Length / Width:</b> 48 feet x 102 inches
<b>Suspension Type:</b> Wide spread air
<b>Frame Rating:</b> 80,000 lbs distributed - 55,000 lbs concentrated in 4 feet- GAWR and tire ratings determine legal payloads
<b>Flooring:</b> 1 1/8 inch aluminum with 4 wood nailer strips
<b>Crossmembers:</b> 12 inch centers - 4 inch jr. I-steel
<b>Single Coil Hauling Package:</b> Included
<b>Side Rails:</b> Exclusive Revolutionary RASR Rail Technology -- one piece routed aluminum designed for strength and impact
<b>Chain Cargo Tie Downs:</b> 15 pair recessed in siderails
<b>Stake Pockets:</b> Routed aluminum on 24 inch centers (2 load securement openings between stake pockets)
<b>Rubrail:</b> Integrated with siderail
<b>Main Beams:</b> 130K load bearing flanges
<b>Kingpin:</b> 30 inches
<b>Loaded Fifth Wheel Height:</b> 49 inches
<b>Landing Gear:</b> OEM Standard with Forward & Rear Bracing
<b>Knee Braces:</b> Fabricated on approx. 60 inch C/C
<b>Bulkhead Pockets:</b> 4 DOT type bulkhead pockets only - welded to front
<b>Bulkheads:</b> None standard
<b>Number of Axles:</b> 2
<b>Axle Spindle:</b> Tapered
<b>Brakes:</b> Spring brakes, auto slacks
<b>Air Line Filters:</b> (2) Meritor In-line type installed
<b>ABS:</b> 4S/2M - no cable or tool
<b>Axle Spread:</b> 122 inches - set at rear
<b>Hub and Drums:</b> 10-hole hub-piloted with outboard cast drums
<b>Wheel Ends:</b> Grease in hubs - *** 5-year wheel end warranty ***
<b>Wheels:</b> 22.5 x 8.25 steel disc inside wheels - 4 aluminum Lvl One buffed outside
<b>Tires:</b> 295/75R 22.5 14PR OEM standard tires- STANDARD
<b>Tire Inflation System:</b> None standard
<b>Suspension Detail:</b> Hendrickson AANT23K Intraax air ride
<b>Auto Glad Hand Dump:</b> Installed
<b>Electric Dump Valve:</b> Wired to 7-way auxiliary socket to dump rear axle
<b>Air Lift:</b> None standard
<b>Front Corners:</b> Tapered steel
<b>Electrical System:</b> LED: 3 lights/side, 2 lights/side on rear - STANDARD
<b>Paint:</b> Black urethane on steel parts with Infinity decals - STANDARD
<b>Conspicuity Tape:</b> Per NHTSA specs - installed in recess on rubrails
<b>Bumper:</b> Weld-on type - meets underride requirements - painted steel
<b>Mudflaps:</b> 2 sets America Mighty Warriors; Spring loaded brackets behind front axle
<b>Spare Tire Carrier:</b> None standard
<b>Winch Track:</b> Full length integrated double L type aluminum on both sides -- STANDARD
<b>Sliding Winches:</b> 12: 6 each side; sliding Rope Hook/ Winch Strap Hook Retainers -- STANDARD
<b>27 foot Winch Straps:</b> None standard
<b>30 foot Winch Straps:</b> None standard
<b>Dock Bumpers:</b> 1 pair rubber on rear
<b>Hubodometer:</b> None standard
<b>Registration Holder:</b> Install registration holder - OEM standard
<b>Tool Box:</b> None standard
<b>VIN Plate:</b> Bilingual US/Canadian VIN plate
<b>Unit Numbers &amp; Decals:</b> Patriot and America Mighty Warriors Decals Installed
<b>Fontaine Select Products:</b>
<b>Boxes and Bulkheads</b>
<b>(1) OEM PREMIUM CAM LOCK 24X24X60 Aluminum Double Door Tool Box Installed Between Axles - Road Side</b>

### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.