

HALE TRAILER BRAKE & WHEEL



A018202-A018231
VIN: 571272-571301

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

Velocity 48' Spring Slider (Model: HAVSF12SST)

Length / Width: 48 feet x 102 inches
Suspension Type: Sliding spring tandem; This Trailer Design Does NOT Meet Proposed GHG2 Compliance Requirements
Frame Rating: 80,000 lbs distributed - GAWR and tire ratings determine legal payloads
Flooring: 1 1/8 inch wood
Crossmembers: 12 inch centers - 4 inch jr. I-steel
Side Rails: 6 inch structural channel @ 6.5 lbs/ft
Stake Pockets: 3/16 inch steel on 24 inch centers
Pipe Spools: Double between stake pockets
Rubrail: 3/8 inch x 2 1/2 inch steel
Main Beams: 130K load bearing flanges
Kingpin: 30 inches
Loaded Fifth Wheel Height: 49 inches
Landing Gear: OEM Standard with Forward & Rear Bracing
Knee Braces: Fabricated on approx. 60 inch C/C
Bulkheads:Removable steel 4 post DOT type bulkhead - no turnback - 48 inches high
Bulkhead Pockets: 4 - F-5 DOT-type steel
Number of Axles: 2
Axle Spindle:Tapered
Brakes: Spring brakes, auto slacks
Air Line Filters:(2) Meritor In-line type installed
ABS: 4S/2M - no cable or tool
Axle Spread: 49 inches
Hub and Drums: 10-hole hub-piloted with outboard cast drums
Wheel Ends: Oil in hubs
Wheels:22.5 x 8.25 steel disc wheels - pre-painted white - STANDARD
Tires:11R 22.5 14PR OEM standard tires
Tire Inflation System:None standard
Suspension Detail: OEM Standard 3-leaf spring slider - 60 inches adjustable
Front Corners: Tapered
Electrical System:LED: 3 lights/side, 2 lights/side on rear- STANDARD
Paint:Black urethane with Velocity decals - STANDARD
Conspicuity Tape: Per NHTSA specs - installed on rubrails
Bumper: Weld-on type - meets underride requirements
Mudflaps:1 set OEM standard behind rear axle
Spare Tire Carrier:None standard
Winch Track: Steel on road side
Sliding Winches:12 standard
27 foot Winch Straps:None standard
30 foot Winch Straps:None standard
Dock Bumpers: 1 pair rubber on rear
Hubodometer:None standard
Registration Holder:Install registration holder - OEM standard
Tool Box:None standard
VIN Plate: Bilingual US/Canadian VIN plate

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.