

## Hale Trailer Brake & Wheel 018326-018328

## X-L SPECIALIZED TRAILERS, INC.

**GOOSENECK-**

LENGTH: 10' FULL WIDTH NECK

KING PIN SETTING: 18" SWING CLEARANCE: 82"

**5TH WHEEL HEIGHT**: 40" - 52" WITH AIR HAT BOX - 12" TRAVEL

2 POSITION FRONT ROLLER

DECKING: 1 1/8" APITONG DECKING FLUSH

D-RINGS: 2 BENT D-RINGS PER SIDE- 4 TOTAL

MUD FLAPS: ALUMINUM MUD FLAPS

TOOL BOX: TOOLBOX IN REAR OF GOOSENECK WITH LIGHT AND CHAIN RACK, ALUMINUM COVER

**MAIN DECK-** 3 BEAM DESIGN

LENGTH: 34'

LOADED DECK HGT: 12" W 4" GROUND CLEARANCE

**DECKING:** STEEL DECKING BETWEEN MAIN BEAMS

1 1/8" APITONG DECKING, FLUSH BETWEEN MAIN BEAMS AND OUTER BEAMS

CROSSMEMBER: 4" JR I-BEAM ON 18" CENTERS

SIDE BEAMS: FAB I-BEAMS 8"

**D-RINGS:** 12 BENT D-RINGS PER SIDE- 24 TOTAL

RAMPS: TAPERS TO 4"

CHAIN DROPS: 17 PAIR OF CHAIN SLOTS

OUTRIGGERS: NONE

REAR DECK:

LENGTH: 9' LOADED DECK HEIGHT: 40"

**AXLES:** (2) 25,000 NOMINAL, 77 1/2" TRACKING

SUSPENSION: HEND-TURNER / 25,000 AIR

AXLE SPACING: 54"

ABS: 4S2M WITH SPRING BRAKES ON 2 AXLES

**TIRES:** 255 / 70R / 22.5

WHEELS: 8.25 X 22.5 STEEL INSIDE, ALUMINUM POLISHED OUTSIDE DISC WHEELS

BRAKES: 16 1/2" X 7"

DRUMS: HUB PILOT / OUTBOARD DRUMS

**ELECTRICAL:** 12V SEALED GROTE SYSTEM WITH 3 TAIL LIGHT ALUMINUM PACKAGE

4" AMBER STROBE WITH SWITCH TO MAKE 3 STT

DECKING: 1 1/8" APITONG DECKING, FLUSH
D-RINGS: 2 BENT D-RINGS IN TAIL CHANNEL

ADDITIONAL:

PAINT: BLACK URETHANE WITH 2 PART EPOXY PRIMER

LIQUID FILLED AIR GAUGE WITH CHART

4-WAY PLUG AT REAR

MANUAL RIDE HEIGHT CONTROL

LED LIGHTING

FRAME REINFORCEMENT, AIR, ELECTRIC AND BRACKETS FOR FLIP AXLE

RAISE AND LOWER VALVE