

Model: AC-20 **Capacity in tons:** 20

1. TONGUE

Pintle eye Adjustable pintle eye (3" ID) with 48" chain and grab hooks

Tongue 5'-6" with lockable tool box with aluminum diamond plate lid - move hinge 4"

Drop leg 2-speed, 50,000# crank down dual landing leg, mounted to main beams and

headboard

Electrical receptacle Seven pin connector Headboard 8" high full width

2. DECK

One piece tongue, main beam and beavertail (cold formed) Deck section design

Deck section length 27'-0" (21'-0" flat with 6'-0" beavertail)

Deck section width 8'-6" Loaded deck height 32-1/4"

1-1/2" apitong - individual wheel well covers Flooring

Lash rings 10 total -

> 4 each side on flat deck (straight style), 8 total 1 each side on beavertail (straight style), 2 total

Crossmembers 6" deep hi-tensile Mainbeams 12" deep hi-tensile Sidemembers 8" deep hi-tensile

Beavertail 6'-0" Double break with wood flooring full width

5'-0" with wood flooring with 3 springs per ramp and grab handles Ramps

3. RUNNING GEAR

2 Number of axles

Axle capacity 25,000# Full width track

Brakes 12-1/4" x 7-1/2" air with 2S/1M ABS. Spring brakes on both axles.

Wheels Steel disc with oil seals (6.75 x 17.5) Eight (8) 215/75R17.5 (H) 16PR radials Tires Use valve stem extensions on inside wheels

Suspension 44,800# Hutch spring

4. GENERAL

12 volt LED system (license plate regular), supplied with female 7-way plug on Lights and wiring

tongue, SUPPLY JUMPER CORD FOR TRUCK

Valspar standard Talbert black, R-Cure 800 series paint Paint

Formed step in front of 1st axle both sides of trailer Additional general specifications