

HALE

TRAILER



BRAKE & WHEEL

A018380-A018388
VIN: 227308-227316



SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Jacksonville, FL: 800-828-3055
Baltimore, MD: 888-601-7500	Little Rock, AR: 833-424-8944
Boston, MA: 800-854-5310	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Richmond, VA: 866-839-3495
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

ITEM	DESCRIPTION
TYPE APPLICATION	SEMI-TRAILER, STEEL DROP PLATFORM. GALVANIZED SEE SECTION
DIMENSIONS	
LENGTH	40'-0"
WIDTH	102", 97" between side rails.
HEIGHT	Floor, approximately 60" high at front and 40" at the bumper.
DROP HEIGHT	20", located at 10'-6" from front.
COUPLING	
COUPLER PLATE	5/16", plug welded structure.
KING PIN LOCATION	18" from front.
COUPLER HEIGHT	49".
STRUCTURE	Frame with "CAMBER".
FLANGES	3/8" x 5" , 100 000 psi steel, 23 3/4" high in center and 15 1/2" above suspension.
WEB	1/4" plate in king pin area and the remaining in 3/16", 80 000 psi steel. With holes, parachute shaped, to lighten trailer.
GOOSENECK	11 1/4" high, with 48" straight behind king pin.
CROSSMEMBERS	1 beams 4" @ 3.64 lbs/ft 80 000 psi steel. 12" center to center in gooseneck and the remaining 12" c/c on lower deck. Installed with stiffeners angle.
FLOOR	Aptitong or equivalent, 1 1/8" thick shiplap finished, no preservative.
FLOOR FASTENING	Two screws per board at each crossmember. (With galvanized flatbed or crossmembers)
SIDE RAILS	Formed channel 6" @ 4.6 lbs/ft.
SIDE BOXES	3/16" steel plate, 1 5/8" x 3 5/8" interior, 4" high. (USA Dimensions).
RUB RAILS	3/8" x 2 1/2" shaped steel.
CORNERS	Bevelled.
FENDERS	Over tires at rear, checker plate 1/8".
DIAGONAL BRACES	2" x 2" x 3/16" angles, welded in web and to a crossmember, located each side.
X BRACES	Between main beams, full length.
TIE BAR	3/8" x 2 1/2" shaped steel welded under crossmembers, curb side, located 14" from side rail.
ENDS	
FRONT RAIL	9 gauge formed steel, bolted to frame.
BUMPER	CMVSS 223-RIG approved (in accordance with Canada & USA regulations). Uprights integrated with frames, 4" x 4" cross bar roll formed tubing at a maximum height of 22" from under tubing to ground.
HEADBOARD	48" high, steel, 4 uprights and top made of tubing and 11 gauge steel plate installed inside with retroreflective tapes. (this bulkhead is NOT D.O.T.)
POCKETS	2 bolted galvanised pockets at front for removable headboard.
REAR RAIL	11" high, 9 gauge formed steel, including 3 boxes at rear and 3/8" x 2 1/2" shaped steel, bolted to frame.



ITEM	DESCRIPTION
ELECTRICAL FRONT CONNECTOR ELECTRICAL SYSTEM MAIN SYSTEM TURN SIGNAL	7 way (SAE J560), Phillips brand. Shock proof lights, polycarbonate lenses, in compliance with CMVSS 108. Grote Ultra Blue LED, sealed beams, tail lights with male pins #53252 (10 diodes), markers #47122, 47233 (2 1/2" dia.), licence light #60280-M). Sealed beams LED, one lamp including side marker and flasher, each side at middle point, amber.
LANDING GEAR SAND SHOES CRANK	Holland, Mark V (LGS-4F315), with mounting plate, solid axles, galvanized. 10" x 11 1/2", solid axles. Road side.
BOGIE BASIC SUSPENSION BOGIE SUSPENSION U-BOLTS SPRINGS AXLE(S) SPIDERS CAM SHAFTS TRACK DUST SHIELDS BRAKES BEARINGS SLACK ADJUSTERS SEALS BRAKE CHAMBERS HUBS AND DRUMS RIMS TIRES	Fixed. Hutch H-9700, tandem, underslung, under mount, 49" spread. With nuts at bottom. 3 leaves, model TRA 2740 or 365-00, 12 000 lbs capacity. AXN, TA225T, 22 500 lbs. capacity. Welded. 28 splines. 77 1/2". Steel, clamped. 16 1/2" standard, AXN R20 extended life lining. HM 218248 and HM 212049. Meritor, automatic, 28 splines. Stemco, "Guardian" type, with "Gearlube" mineral oil, SAE 80W90. T.S.E. brake, "Omnibrake" (30-30). (4 years warranty by T.S.E. for parts only). WEBB, 10 studs disc hubs, balanced drums 104.5 lbs, outboard mount, 285.75mm B.C., single flange nuts. For dual aluminum wheels. 22.5 x 8.25, disc (10 holes), 285.75mm B.C., single flange nuts, 2 hand holes. Continental, 255/70 R 22.5 HSR2 SA 16 ply (36.6")
AIR SYSTEM GLAD HANDS AIR VALVES	Fixed. Meritor Wabco, ABS, 2 sensors 1 modulator.
ACCESSORIES REGISTRATION HOLDER WINCHES SLIDING TRACK MUD FLAPS	One plastic, Betts-PS-1 or equivalent. Qty: 12, ANCRA #49207-137-XZ, zinc plated slider (5 7/8"). Full length, "LL" extruded aluminum, road side. One set, rubber with Manac logo and vertical grooves to reduce spray.
FINISHING PAINT	Ready for Galvanized platform.



ITEM	DESCRIPTION
AXLE(S) PAINTED HUBS WHEELS OR RIMS RETROREFLECTIVE TAPES	*** Black *** *** Black *** White. Conspicuity striping in compliance with CMVSS 108. Gray and red, each side, fully covers rear sill and horizontal underride protection bar.
ADDITIONAL OPTIONS	*** Same as U#220862 *** Due to deep backlogs, material/component availability, price fluctuation in fuel and transportation costs, Manac reserves the right to adjust the price based on these instabilities. If needed, Manac will contact the customer a minimum of 3 months prior to assembly with revised pricing or a change in components. At that time, the customer will have the option to accept the change or cancel the order. This will prevent any cancellation fees from our
GALVANIZED CHOICES PLATFORM	Galvanized choices. Galvanized platform. (no paint) ** WARNING: holes parachute shaped required for dripping **
CONFORMITY	This semi-trailer does not comply with GHG regulations. Should GHG regulations come into force prior to the production of the trailer(s), Manac will have the obligation to ensure the trailer(s) produced meet minimum GHG guidelines. Any modifications required to meet the GHG regulations will be added to the initial purchase price and charged back to the customer.

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.