

Hale Trailer Brake & Wheel 018383, 018387, & 018391

X-L SPECIALIZED TRAILERS, INC.

OAL: 53' OAW: 102"

MODEL: XL 120HDE **DIST:** 120,000# 100,000# IN 10' CLOSED CONC.

WEIGHT +/-3% 35117

GOOSENECK-

LENGTH: 12' 5" NARROW NECK

KING PIN SETTING: 16" SWING CLEARANCE: 105"

5TH WHEEL HEIGHT: 52" W/7 VARIABLE RIDE HEIGHT POSITIONS

HYDRAULICS:

FLIP NECK: FRAME REINFORCEMENT, AIR, ELECTRIC AND BRACKETS FOR 72" FLIP NECK EXTENSION

72" FLIP NECK EXTENSION

MAIN DECK-

LENGTH: 31' 1"/ OPENING TO 54' 5"

LOADED DECK HGT: 24" W/6" GROUND CLEARANCE

DECKING: 1 1/8" APITONG DECKING, FLUSH, CENTER COVERED CROSSMEMBER: 6" JR. I-BEAM ON 12" ALTERNATING CENTERS

SIDE BEAMS:

10 BENT D-RINGS PER SIDE TOTAL OF 20 - STAGGER BETWEEN CHAIN DROPS D-RINGS:

OUTRIGGERS: REMOVABLE SWING OUT OUTRIGGERS - 24" O/C

CHAIN DROPS: (10) CHAIN DROPS PER SIDE - OUTSIDE BEAMS ONLY - STAGGER BETWEEN D-RINGS

REAR DECK:

LENGTH: 9' 6" LOADED DECK HEIGHT: 36"

(2) 25,000 NOMINAL, 77 1/2" TRACKING,

SUSPENSION: HEND-TURNER/25,000 AIR

AXLE SPACING:

N/A WITH SPRING BRAKES ON BOTH AXLE ABS:

TIRES: MICHELIN 245/70R/17.5

WHEELS: 6.75 X 17.5 STEEL INSIDE, ALUMINUM POLISHED OUT DISC WHEELS

BRAKES: 12 1/4" X 7 1/2"

DRUMS: HUB PILOT/ OUTBOARD DRUMS

ELECTRICAL: 12V SEALED GROTE SYSTEM WITH 3 TAILLIGHT ALUMINUM PACKAGE

DECKING: 1 1/8" APITONG DECKING FLUSH, COVERED WHEELS WITH OPEN BOOOM TROUGH

2 BENT D-RINGS IN TAIL CHANNEL D-RINGS:

2 PAIR OF PAN STYLE D-RINGS - ONE IN EACH CORNER

ADDITIONAL: PAINT:

(9) TOTAL CLEARANCE LIGHTS PER SIDE - LED BLACK URETHANE WITH 2 PART EPOXY PRIMER

ONE PAIR OF FLAG HOLDERS IN REAR

RAISE & LOWER VALVE AND LIQUID FILLED AIR GAUGE IN ALUM. BOX BETWEEN AXLES

ON DRIVERSIDE (SEE DRAWING)

31" FRONT FLIP RAMPS

FRAME REINFORCEMENT, AIR, BRACKETS, ELECTRICAL FOR TWO AXLE POWER BOOSTER (3+2)

4" AMBER STROBE LIGHT TO BE USED AS 3RD TAIL LIGHT

LED LIGHTING - STANDARD

DETACHABLE WHEEL AREA WITH VERTICAL PINS

PSI TIRE INFLATION SYSTEM LIQUID FILLED AIR GAUGE

DUST SHIELDS

(3) TOTAL MID TURN LIGHTS PER SIDE MANUAL RIDE HEIGHT CONTROL EXTENSION STOPS 24" O/C