

# HALE

## TRAILER

BRAKE & WHEEL



**A018400-A018403**  
**VIN: 007143, 007146,**  
**007156, 007159**

SALES | RENTALS | PARTS | SERVICE

|                                     |                                       |
|-------------------------------------|---------------------------------------|
| <b>Allentown, PA:</b> 800-383-8894  | <b>Jacksonville, FL:</b> 800-828-3055 |
| <b>Baltimore, MD:</b> 888-601-7500  | <b>Little Rock, AR:</b> 833-424-8944  |
| <b>Boston, MA:</b> 800-854-5310     | <b>Portland, ME:</b> 800-325-4253     |
| <b>Concord, NC:</b> 800-438-2250    | <b>Richmond, VA:</b> 866-839-3495     |
| <b>Delmar, DE:</b> 866-486-1400     | <b>Scranton, PA:</b> 800-569-1400     |
| <b>Des Moines, IA:</b> 888-673-5011 | <b>Springfield, MA:</b> 800-854-5306  |
| <b>Elkton, MD:</b> 800-544-7127     | <b>Voorhees, NJ:</b> 866-315-0235     |

HaleTrailer.com | @haletrailer

**800-232-6535** \*FINANCING AVAILABLE

| Item                 | Description  | ALUMINUM-ARA/3A |
|----------------------|--|-----------------|
| TANK CONSTRUCTION    | ARA  |                 |
| CAPACITY             | 9500 GALLONS   |                 |
| OUTAGE               | 1 PERCENT (MINIMUM)  |                 |
| CODE                 | 49 CFR 173.247   |                 |
| DESIGN PRESSURE      | ATMOSPHERIC  |                 |
| VENTING              | ASPHALT TYPE, LIGHT WEIGHT STYLE   |                 |
| TEMPERATURE RATING   | 400 DEGREE   |                 |
| MATERIAL-BARREL      | 5454-H32 ALUMINUM  |                 |
| SURGE PLATES         | (2) ALUMINUM   |                 |
| COMPARTMENTS         | ONE  |                 |
| CAPACITY MARKERS     | 3-DISC   |                 |
| INSULATION           | 4" FIBERGLASS, 1# DENSITY, NOT COMPRESSED  |                 |
| ALUMINUM JACKETING   | 0.040" SIDE SHEETS/0.060" HEADS  |                 |
| REAR DISCHARGE VALVE | 6" VALVE W/ 3" LINE & CAMLOCK CAP. INCLUDES 3/4" PORT FOR WASHOUT CONNECTION.  |                 |
| FRONT PUMP-OFF VALVE | 3" VALVE W/ SWIVEL & INTERNAL LINE, OUTLET TERMINATING WITH A 3" CAMLOCK ADAPTER & CAP. INCLUDES 3/4" PORT FOR WASHOUT CONNECTION AND 8' HOSE TROUGH ON RH FRONT FENDER. |                 |
| GATE VALVE           | 4" AT REAR UNLOADING LINE  |                 |
| THERMOMETER          | 3" DIAL IN WELL W/ PLEXIGLASS COVER  |                 |
| MANHOLE              | 20" ASPHALT TYPE   |                 |
| MANHOLE PLATFORM     | 4 SIDED, ALUMINUM  |                 |
| DEFLECTOR PAN        | BENEATH MANHOLE  |                 |
| MANHOLE OVERFLOW     | 2" EXTERNAL  |                 |
| HEATING SYSTEM       | NONE   |                 |
| LADDER               | ALUMINUM-CURBSIDE  |                 |
| WALKWAY              | NONE   |                 |
| HOSE TROUGH          | 20' ALUMINUM, CURBSIDE   |                 |
| TIRE CARRIER         | NONE   |                 |
| FENDERS              | ALUMINUM, FRONT & REAR WITH MUDFLAPS ON REAR FENDERS. MANUAL HOLDER ON FRONT ROADSIDE FENDER   |                 |
| LIGHTS               | L.E.D. TYPE WITH ALUMINUM LIGHT BOXES @ REAR   |                 |
| GLAD HANDS           | LOW MOUNT  |                 |
| BUMPER-SPLIT TYPE    | WITH SLOPING OUTLET  |                 |
| BUMPER UNDERRIDE     | ALUMINUM, BOLT-ON  |                 |
| CONSPICUITY MARKING  | PER DOT REQUIREMENTS   |                 |
| UPPER COUPLER        | ADJUSTABLE   |                 |
| LANDING LEGS         | HD ALUMINUM FRAME  |                 |
| LANDING LEGS         | MARK V HEAVY DUTY  |                 |
| LANDING LEGS         | ADDITIONAL FORWARD BRACING   |                 |



|                                 |  |
|---------------------------------|--|
| BOGIE                           | ALUMINUM   |
| SUSPENSION                      | INTRAAAX AAT25K AIR RIDE TRIDEM W/MANUAL EXHAUST                                     |
| SUSPENSION                      | INSTALL LIFT BRACKETS ON SUSPENSION ARMS FOR FUTURE ADDITION OF LIFT KIT, FRONT AXLE |
| AIR BRAKES                      | HALDEX DBLT, 25,000 LBS. RATING  |
| ANTI-LOCK BRAKES                | 2S/2M SYSTEM (2 SENSORS/2 MODULATORS)  |
| AXLES                           | (3) 25,000# BEAM RATING WITH HP BEARINGS, 77-1/2" TRACK                              |
| HUBS                            | DUCTILE IRON   |
| ALUMINUM DISC WHEELS            | ACCURIDE STANDARD POLISHED, 10-HOLE, HUB PILOTED                                     |
| TIRES                           | 11R24.5-H  |
| AUTOMATIC TIRE INFLATION SYSTEM | AXLES PREPARED FOR TIREMAXX PRO, SYSTEM NOT INSTALLED                                |
| HUBODOMETER                     | ON DRIVER'S SIDE REARMOST AXLE   |
| PAINT                           | STEEL PARTS ONLY-BLACK   |
| CENTER PAINT BAND               | 14" WIDE BAND-BLACK  |
| PLACARD KIT                     | SLIDE-IN TYPE W/ " HOT" PLACARD, 4 SIDES   |
| SAMPLE VALVE                    | 3/4"   |

Etnyre reserves the right to modify pricing on all quotes and orders with material and labor surcharges as needed

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.