

Item	Description Model: Aluminum-ARA/3A
TANK CONSTRUCTION	ARA
CAPACITY	9500 GALLONS
OUTAGE	1 PERCENT (MINIMUM)
CODE	49 CFR 173.247
DESIGN PRESSURE	ATMOSPHERIC
VENTING	ASPHALT TYPE, LIGHT WEIGHT STYLE
TEMPERATURE RATING	400 DEGREE
MATERIAL-BARREL	5454-H32 ALUMINUM
SURGE PLATES	(2) ALUMINUM
COMPARTMENTS	ONE
CAPACITY MARKERS	3-DISC
INSULATION	4" FIBERGLASS, 1# DENSITY, NOT COMPRESSED
ALUMINUM JACKETING	0.040" SIDE SHEETS/0.060" HEADS
REAR DISCHARGE VALVE	6" VALVE W/ 3" LINE & CAMLOCK CAP. INCLUDES 3/4" PORT FOR WASHOUT CONNECTION.
FRONT PUMP-OFF VALVE	3" VALVE W/ SWIVEL & INTERNAL LINE, OUTLET TERMINATING WITH A 3" CAMLOCK ADAPTER & CAP. INCLUDES 3/4" PORT FOR WASHOUT CONNECTION AND 8' HOSE TROUGH ON RH FRONT FENDER.
GATE VALVE	4" AT REAR UNLOADING LINE
THERMOMETER	3" DIAL IN WELL W/ PLEXIGLASS COVER
MANHOLE	20" ASPHALT TYPE
MANHOLE PLATFORM	4 SIDED, ALUMINUM
DEFLECTOR PAN	BENEATH MANHOLE
MANHOLE OVERFLOW	2" EXTERNAL
ALUMINUM HEAT COILS	1.9" O.D., ALUMINUM, 2-PASS
LADDER	ALUMINUM-CURBSIDE
WALKWAY	NONE
HOSE TROUGH	20' ALUMINUM, CURBSIDE
TIRE CARRIER	NONE
FENDERS	ALUMINUM, FRONT & REAR WITH MUDFLAPS ON REAR FENDERS. MANUAL HOLDER ON FRONT ROADSIDE FENDER
LIGHTS	L.E.D. TYPE WITH ALUMINUM LIGHT BOXES @ REAR
GLAD HANDS	LOW MOUNT
BUMPER-SPLIT TYPE	WITH SLOPING OUTLET
BUMPER UNDERRIDE	ALUMINUM, BOLT-ON
CONSPICUITY MARKING	PER DOT REQUIREMENTS
UPPER COUPLER	ADJUSTABLE
LANDING LEGS	2-SPEED, CURBSIDE CRANK WITH HORIZONTAL BRACE BETWEEN LANDING LEGS
LANDING LEGS	HD ALUMINUM FRAME
LANDING LEGS	MARK V HEAVY DUTY



LANDING LEGS	ADDITIONAL FORWARD BRACING
BOGIE	ALUMINUM
SUSPENSION	INTRAAX AAT25K AIR RIDE TRIDEM W/MANUAL EXHAUST
SUSPENSION	INSTALL LIFT BRACKETS ON SUSPENSION ARMS FOR FUTURE ADDITION OF LIFT KIT, FRONT AXLE
AIR BRAKES	HALDEX DBLT, 25,000 LBS. RATING
ANTI-LOCK BRAKES	2S/2M SYSTEM (2 SENSORS/2 MODULATORS)
AXLES	(3) 25,000# BEAM RATING WITH HP BEARINGS, 77-1/2" TRACK
HUBS	DUCTILE IRON
ALUMINUM DISC WHEELS	ACCURIDE STANDARD POLISHED,10-HOLE, HUB PILOTED
TIRES	11R24.5-H
AUTOMATIC TIRE INFLATION SYSTEM	AXLES PREPARED FOR TIREMAXX PRO, SYSTEM NOT INSTALLED
HUBODOMETER	ON DRIVER'S SIDE REARMOST AXLE
PAINT	STEEL PARTS ONLY-BLACK
CENTER PAINT BAND	14" WIDE BAND-BLACK
PLACARD KIT	SLIDE-IN TYPE W/ " HOT" PLACARD, 4 SIDES
SAMPLE VALVE	3/4"

Etnyre reserves the right to modify pricing on all quotes and orders with material and labor surcharges as needed