

XL SPECIALIZED TRAILERS

XL 70 MFG: Mini-Deck

OVERALL LENGTH OVERALL WIDTH CAPACITY WEIGHT +/- 3% 53'

16"

84"

49"

TAPERS TO 4"

CHAIN DROPS ON 18" CENTERS

10' FULL-WIDTH NECK

SHIMMABLE NECK - SHIMS INCLUDED

102" 70,000 LB DISTRIBUTED; 60,000 LB IN 16' CONCENTRATED 0,000 LB

GOOSENECK

KINGPIN SETTING SWING CLEARANCE 5TH WHEEL HEIGHT

DECKING D-RINGS

MUD FLAPS TOOLBOX

MAIN DECK

LENGTH LOADED DECK HEIGHT DECKING

CROSSMEMBER BEAMS D-RINGS OUTRIGGERS RAMPS CHAIN DROPS:

AIR SUPPORT ARM 1 1/8' APITONG DECKING FLUSH (2) BENT PER SIDE (1) PAN STYLE IN EACH CORNER ALUMINUM MUD FLAPS TOOLBOX IN REAR OF GOOSENECK WITH LIGHT AND CHAIN RACK, ALUMINUM TRIPLE DONUTS 3 BEAM DESIGN 34' (33'CLEAR)

34' (33' CLEAR) HT 12" W 4" GROUND CLEARANCE STEEL DECKING BETWEEN MAIN BEAMS WITH DURBAK 1 1/8" APITONG DECKING, FLUSH BETWEEN MAIN BEAMS AND OUTER BEAMS 4" JR. I-BEAM ON 18" CENTERS FABRICATED BEAMS (12) BENT PER SIDE NONE

REAR DECK

LENGTH	9'
LOADED DECK HEIGHT	40"
AXLES	(2) 25,000 LBS NOMINAL (5/8" WALL)
SUSPENSION	HENDRICKSON / 25,000 CAPACITY / AIR RIDE
AXLE SPACING	54"
ABS	4S2M WITH SPRING BRAKES ON 2 AXLES
TIRES	255 / 70R / 22.5 (H)
WHEELS	8.25 X 22.5 10-HOLE STEEL INSIDE, ALUMINUM POLISHED OUTSIDE DISC WHEELS
BRAKES	16 1/2" X 7"
DRUMS	OUTBOARD
ELECTRICAL	12V SEALED GROTE SYSTEM WITH (3) TAILLIGHT ALUMINUM PACKAGE
	4" AMBER STROBE TO BE USED AS 3RD TAILLIGHT
DECKING	1 1/8" APITONG DECKING, FLUSH
D-RINGS	(2) BENT IN TAIL CHANNEL
	(1) PAN STYLE IN EACH CORNER
PAINT	BLACK

ADDITIONAL

LIQUID FILLED AIR GAUGE WITH CHART 4-WAY PLUG AT REAR MANUAL RIDE HEIGHT CONTROL PREP FOR FLIP AXLE RAISE AND LOWER VALVE (2) PAIR OF FLAG HOLDERS

SIMILAR TO 22014

DISCLAIMER