

Hale Trailer Brake & Wheel 018604 - 018608

X-L SPECIALIZED TRAILERS, INC.

GOOSENECK-

LENGTH: 13' SCRAPER STYLE RELIEF NECK

KING PIN SETTING: 16" 42" SWING CLEARANCE: 110" 84"

5TH WHEEL HEIGHT: 51" W/ 5 VARIABLE RIDE HEIGHT POSITIONS

HYDRAULICS: RUN OFF WET LINE

BRACKETS FOR POWER UNIT WORK LIGHT ON NECK

MAIN DECK-

LENGTH: 26'

LOADED DECK HGT: 15" W/ 4 1/2" GROUND CLEARANCE

DECKING:1 3/8" APITONG DECKING, RAISED - CENTER OPENCROSSMEMBER:6" & 4" STUBBED JR. I-BEAM 12" ALTERNATING CENTERS

SIDE BEAMS: 4 BEAMS 10 1/2"

OUTRIGGER: SWING OUT OUTRIGGERS - 24" O/C - H.D. FLAT BACK FRONT

D-RINGS: 7 BENT D-RINGS PER SIDE - 14 TOTAL

CHAIN DROPS: (13) CHAIN DROPS PER SIDE - OUTSIDE BEAMS

REAR DECK:

LENGTH: 14' WITH 32* REAR TRANSITION

LOADED DECK HEIGHT: 41"

AXLES: (3) 25,000 NOMINAL, 77 1/2" TRACKING **SUSPENSION:** HEND - TURNER / 25,000 CAPACITY / AIR

AXLE SPACING: 54 1/

ABS: N/A SPRING BRAKES ON 1 AXLES

TIRES: 275 / 70R / 22.5

WHEELS: 8.25 X 22.5 / STEEL INSIDE, ALUMINUM POLISHED OUTSIDE / DISC / PILOTED HUBS

BRAKES: 16 1/2" X 7

DRUMS: HUB PILOT/OUTBOARD DRUMS

ELECTRICAL: 12V SEALED GROTE SYSTEM WITH 3 TAIL LIGHT ALUM. PACKAGE

4" AMBER STROBE WITH SWITCH TO MAKE 3 STT

BATTERY BACKUP

DECKING: OPEN WHEELS BOLSTER STYLE, OPEN BOOM TROUGH

BOLSTERS DROPPED 4" DOWN

CHAIN DROPS: (2) CHAIN DROPS PER FULL WIDTH BOLSTER
D-RINGS: ONE PAIR OF FLAT D-RINGS ON MAIN BEAMS -AT REAR
STAKE POCKETS: (2) STAKE POCKETS AT REAR FOR WIDE LOAD SIGN

ADDITIONAL:

PAINT: RED URETHANE WITH 2 PART EPOXY PRIMER

FRAME REINFORCEMENT, AIR, ELECTRIC AND BRACKETS FOR FLIP AXLE

RAISE AND LOWER VALVE LED LIGHTING - STANDARD

BUCKET WELL AT REAR OF MAIN DECK WITH PLATE ON BOTTOM WITH 4 FLAT D-RINGS

4-WAY PLUG AT REAR TO RUN BATTERY BACKUP FOR STROBE

TOOL BOX IN FRONT OF MAIN DECK WITH 4 D-RINGS

LIQUID FILLED AIR GAUGE 2 PAIR OF FLAG HOLDERS

AIR LIFT AXLE ON 3RD AXLE ON REAR

31" FRONT FLIP RAMPS