



Resale Inventory
A018749-A018751
778401,778402,778405

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894 **Jacksonville, FL:** 800-828-3055
Baltimore, MD: 888-601-7500 **Little Rock, AR:** 833-424-8944
Boston, MA: 800-854-5310 **Portland, ME:** 800-325-4253
Concord, NC: 800-438-2250 **Richmond, VA:** 866-839-3495
Delmar, DE: 866-486-1400 **Scranton, PA:** 800-569-1400
Des Moines, IA: 888-673-5011 **Springfield, MA:** 800-854-5306
Elkton, MD: 800-544-7127 **Voorhees, NJ:** 866-315-0235

HaleTrailer.com | @haletrailer
800-232-6535 *FINANCING AVAILABLE

Fifth wheel height : 48	<input checked="" type="checkbox"/> Flat Extendable <input checked="" type="checkbox"/> Drop
King Pin <input checked="" type="checkbox"/> Other : 28.5	Length : 54' to 219' with bumper
Location : <input checked="" type="checkbox"/> Bolt-on	Width : <input checked="" type="checkbox"/> 102"
Coupler <input checked="" type="checkbox"/> 1/2" HTS	Steering axles : <input checked="" type="checkbox"/> 3
Plate:	Suspension : <input checked="" type="checkbox"/> Turner HT-250U
Gooseneck: <input checked="" type="checkbox"/> Hinged	<input checked="" type="checkbox"/> Scale-O-Matic
Frame : Extendable with camber	<input checked="" type="checkbox"/> Shut-off valve <input checked="" type="checkbox"/> COLAS Valve
Extendable boxed beams (caisson): <input checked="" type="checkbox"/> 3+1	Axle Location :
Removable blade support on beams: <input checked="" type="checkbox"/> 1	Steering mecanism :
X-Member : Fabricated special	<input checked="" type="checkbox"/> Forced steer with front turn table
Nose corners : <input checked="" type="checkbox"/> 45°	<input checked="" type="checkbox"/> Suspension and axles with turn tables
Side Rail : <input type="checkbox"/> 6" rolled channel	Steering control : <input checked="" type="checkbox"/> Automatic <input checked="" type="checkbox"/> Manual
<input type="checkbox"/> At front <input type="checkbox"/> Full length <input type="checkbox"/> Formed steel	<input checked="" type="checkbox"/> 13 HP Honda power pack
Rub rail : <input type="checkbox"/> 1/4" x 2" St. FB <input type="checkbox"/> 3/8" x 2" St. FB	Axles : <input type="checkbox"/> D-22 <input type="checkbox"/> F-24 for 22,5 or 24,5 wheels
<input type="checkbox"/> None <input type="checkbox"/> Other:	<input type="checkbox"/> D-22 <input type="checkbox"/> F-24 for 19,5 wheels
Stake pocket : <input checked="" type="checkbox"/> None	<input checked="" type="checkbox"/> D-22 <input type="checkbox"/> F-24 for 17,5 wheels
At front bolster : <input checked="" type="checkbox"/> N	Axle track : <input checked="" type="checkbox"/> Other : 79
Winches : Total : <input checked="" type="checkbox"/> None	Brake type: <input checked="" type="checkbox"/> Drum brakes <input type="checkbox"/> Disc brakes
Floor : <input checked="" type="checkbox"/> Other : Steel covered with rubber	Seals : Stemco Guardian HP Bearings : Stemco
Bumper : <input checked="" type="checkbox"/> Long <input checked="" type="checkbox"/> Steel Extendable 20'	Brake Chambers: TSE 30/30T
Mud flaps : <input checked="" type="checkbox"/> Témisko	Automatic Slack adjuster : <input checked="" type="checkbox"/> TSE <input type="checkbox"/> Haldex
Location : Back of gooseneck and at each axle	Brake valve : Rockwell Wabco
Land. gear : <input checked="" type="checkbox"/> Holl. Mark V	A.B.S. Brake : <input checked="" type="checkbox"/> 2S/1M
Crank : <input checked="" type="checkbox"/> R/S	<input checked="" type="checkbox"/> Blue wire on first axle <input type="checkbox"/> A.B.S. Plug <input type="checkbox"/> Y <input checked="" type="checkbox"/> N
Lights : <input checked="" type="checkbox"/> Truck-lite round type (2/s) <input checked="" type="checkbox"/> 45° flasher	Hubs : <input checked="" type="checkbox"/> Dura Light 8 studs steel piloted hubs
<input checked="" type="checkbox"/> LED lights	Drums : <input checked="" type="checkbox"/> Standard
<input checked="" type="checkbox"/> Other: Beacon light at rear bumper	Rims : Qty : 12 <input checked="" type="checkbox"/> Alum. machined finish
Title hold : <input checked="" type="checkbox"/> Truck-lite	<input checked="" type="checkbox"/> 17.5 x 6.75 <input type="checkbox"/> 19.5 x 7.5
Location :	<input checked="" type="checkbox"/> Plastic spacer (rim & rim) <input checked="" type="checkbox"/> Plastic spacer (hub & rim)
Tool box : <input checked="" type="checkbox"/> Alum. Témisko FAB	Tires : Qty : 12 <input type="checkbox"/> 14 Ply <input type="checkbox"/> 16 Ply <input type="checkbox"/> S.B.C.
Dimensions : 25" X 24" X 48"	Model: Michelin XTA2 ENERGY Size : 245/70R17.5
Location : In front of tridem, on both sides	<input type="checkbox"/> Other: Size:
	Tire carrier Témisko Fab :
	<input checked="" type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> C/S
	Hubodometer : <input checked="" type="checkbox"/> None
	Location :
	Paint : Colour : Black
	Colour code: RAL 9005 <input checked="" type="checkbox"/> Tape 100%
	Trim : <input checked="" type="checkbox"/> None
	Rim : <input checked="" type="checkbox"/> Natural
	Rack : <input checked="" type="checkbox"/> None <input type="checkbox"/> Corner board holder
	Dim. :
Special	
Visual lock indicators for inter beam locking	
Aluminum checkerplate on front coupler, Aluminum checkerplate front fenders	
(4) supports for air and hydraulic lines/beam	
Power pack in aluminum box on R/S	
Double redundant hydraulic steering circuit.	
On board steering control, Plug in remote control and wireless remote control (Lodar) + antenna	
dual Hydraulic drop leg to facilitate extending	
"D" rings on each side of the front and rear loading platforms, total of 2X loading bunks	
180 ft of hydraulic lines from front to back	
Oversized sign at rear	

DISCLAIMER

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.