



# Hale Trailer Brake & Wheel

## 018782 & 018786

### X-L SPECIALIZED TRAILERS, INC.

OAL: 27' 9"  
OAW: 102"

MODEL: XL100JPS      DIST: 100,000      CONC.      WEIGHT +/-3%      0

#### 2 AXLE JEEP

##### GOOSENECK-

LENGTH: 11' 5"  
KING PIN SETTING: 16" 35"  
SWING CLEARANCE: 105" 86"  
5TH WHEEL HEIGHT: 50"  
D-RINGS: 1 PAIR OF BENT D-RINGS  
LANDING GEAR: 2 SPEED LANDING GEAR WITH HANDLE ON DRIVERSIDE

##### REAR DECK:

5TH WHEEL: PURCHASED 72" SLIDER  
LOADED 5TH WHEEL HEIGHT: 51"  
AXLES: ( 2 ) 25,000 NOMINAL, 77 1/2" TRACKING  
SUSPENSION: HEND-TURNER / 25,000 AIR  
AXLE SPACING: 60"  
ABS: N/A , SPRING BRAKES PER 1 AXLE  
TIRES: 275 / 70R / 22.5  
WHEELS: 8.25 X 22.5 STEEL INSIDE, ALUMINUM POLISHED OUTSIDE DISC WHEELS  
BRAKES: 16 1/2" X 7"  
DRUMS: OUTBOARD  
ELECTRICAL: 12V SEALED GROTE SYSTEM WITH 2 TAIL LIGHT PACKAGE  
D-RINGS: 1 PAIR OF BENT D-RINGS  
RAISE AND LOWER VALVE

##### ADDITIONAL:

PAINT: BLACK URETHANE ENAMEL WITH 2 PART EPOXY PRIMER  
LIQUID FILLED AIR GAUGE  
FRAME REINFORCEMENT, AIR ,ELECTRIC AND BRACKETS FOR AN ADDITIONAL AXLE  
MANUAL RIDE HEIGHT CONTROL VALVE

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.