

HALE

TRAILER

BRAKE & WHEEL



A018787-A018811
VIN: 552401-552425

SALES | RENTALS | PARTS | SERVICE

Allentown, PA: 800-383-8894	Jacksonville, FL: 800-828-3055
Baltimore, MD: 888-601-7500	Little Rock, AR: 833-424-8944
Boston, MA: 800-854-5310	Portland, ME: 800-325-4253
Concord, NC: 800-438-2250	Richmond, VA: 866-839-3495
Delmar, DE: 866-486-1400	Scranton, PA: 800-569-1400
Des Moines, IA: 888-673-5011	Springfield, MA: 800-854-5306
Elkton, MD: 800-544-7127	Voorhees, NJ: 866-315-0235

HaleTrailer.com | @haletrailer
800-232-6535 *FINANCING AVAILABLE

GVWR

GVWR: Trailer to meet 68,000 Pound GVWR
 VIN PLATE: US - VIN Plate to Read in English (Standard)
 * Product Type: HT Steel Duralite

GEOMETRY

Length - Exterior: 48'-0" Rev. B
 Width - Exterior: 102.36"
 Fifth Wheel Height: 47"
 * King Pin Location: 30" Rev. C
 * Landing Gear Location: 108" from King Pin (+ 1"/-1/4") Rev. C
 Duralite Front Deck Height: 59-3/4" (± 1/2")
 Duralite Rear Deck Height: 54-5/16" (± 1/2")

TIRES & WHEELS

Tire Furnished: Factory Furnished
 * Tire Manufacturer: Hankook TL21(G), Low Rolling Resistance Tire
 * Tire Size: 11R22.5 Rev. C
 Wheel Furnish: Factory Furnished
 Wheel Material: All Steel Wheel
 Wheel Manufacturer: HT Standard (TCC 361)
 Wheel Size: 8.25 x 22.5, 5-Hand Hole (Steel, Inner & Outer)
 Wheel Finish for Steel: Powder Coated White Steel Disc
 Tire Stem Valve Position: Dual Wheel Steel / Aluminum / Combo (STD 180°outboard & straight inboard)
 Wheel Finish for Aluminum: None (Due to All Steel Wheel Application)
 * Valve Stem & Cap: Myers TR-572-F19 Valve stem

UPPER COUPLER

Approach Plate: 1/4" Thick 80,000 PSI Yield (Duralite)
 King Pin & Manufacturer: Standard (Jost) AAR Cruciform King Pin

DURALITE OPTIONS

* Cross Members: 4" Steel I-Beams (80,000 PSI) : 12" C/L
 Main Web: 3/16" Thick. Welded One Piece Type (100 KSI Domex)
 Top Flange: 3/8" Thick, 100 KSI Domex, 5" Wide One Piece Type
 Bottom Flange: 3/8" Thick, 100 KSI Domex, 5" Wide One Piece Type
 Holes on Main web: Diamond Shape
 Gusset Type: Pipe Type
 Gusset Specification: (3) on Each Side (HT STD)
 * Front Sill: HT Standard 3/16" Steel
 * Front Stake Pockets: 4 EA for Steel Bulkhead Installation
 * Bulkhead: Steel Removable Type - Hot Dip Galvanized
 * Bulkhead Specification: 48" High x No Wrap
 * Rear Sill: HT Standard 3/16" Steel
 * Side Rail: HT Standard Steel Channel
 Side Stake Pockets: 24" Centers on Each Side (STD)
 Side Pipe Spools: Double Spools between Stake Pockets (STD)
 * Side Rub Rail: 3/8" Thick, 3" Rails on Both Sides Rev. C
 * Winch Rail: Aluminum Winch Rail for Sliding Winches OR Combination (SLD+ FIX) Winches

* Winches:	Sliding Steel Winches, (12) on Road Side
Sliding Winch Stoppers:	Stoppers at Front and Rear (Flatbed STD for Sliding Winches)
Fastener Options:	Standard Fasteners

FLOOR

* Duralite Floor Specification:	1-5/16" Apitong Wood Floor (Steel STD)
Floor Screws:	HT Duralite Standard (2 Screws Per Board on I-beams)

FRONT

Gladhands:	Phillips Qwik-E with Filters Control Line Only. Overlaid Straight Type
Front Receptacle(7-Way):	HT Duralite Standard (Phillips 7-Way Integrated with Main Harness)
Gladhand/7-Way Location:	(Interior Harness Routing) Overlaid on Lower Centerline Front

REAR

Rear Underride Guard:	4" Tube Bolt on Assembly w/ Bolt on Perforated(Pooched) Horizontal
Dock Bumper:	Pair Heavy Duty Dock Bumper (Ref. Buyers B4500)
Rubber Bumper Location:	HT Duralite Standard Location

LANDING GEAR

L/Gear Spec.:	Jost 420
L/Gear Shoes:	10" X 10" X 4" Sand Shoe (HT Duralite STD)
L/Gear Crank Handle:	Roadside
L/Gear Cross Brace Design:	HT Standard Cross Brace attachment Design

RUNNING GEAR

Bogie Type:	Sliding Tandem(2) Axle Bogie
Axle Spacing:	49" Axle Spacing
Axle ABS System:	Tandem Axle w/2S1M ABS System
* Duralite Bogie & Axle Location:	HT Fixed Axle STD Location (CA Requirement; KP to Rear Most Axle 40#)
* Susp. Manufacturer:	Hutchens
Suspension Capacity:	Standard Duty
* Duralite Susp. Specification:	Hutchens H9001 4-Pin Platform Slider
Surelok (Anti-Dock):	No Surelok (No Anti-Dock)
* Locking Pin Mechanism:	Manual Pin Puller (Flexi Pull) or (EZ Pull)
* Type of Susp Spring:	Mechanical Leaf Spring
* Spring Specification:	3 Leaf - Medium Arch (H355-00)
* Axle Supplier:	Meritor
* Axle-General Spec.:	Axle - Tandem (2) Axle w/ 2S1M or 2S2M System
Axle-Track Length:	77-1/2"
Axle-Spindle Type:	Parallel Spindle
Brake Lining Size:	16.5" X 7"
* Brake Lining Spec.:	Meritor MA212 Q+ (Meritor STD)
Brake Control System:	2S/1M Wabco ABS
Spring Brake Control:	Sealco 110500 Springbrake Priority
Drain Valve & Other:	Parker DC604-4 Drain Cock
Slack Adjuster Spec.:	Gunitite Auto-5.5", 28 Spline
Brake Chamber Spec.:	TSE 3030 Tamper Resist (HT standard)
Stroke Length:	MFG's Standard Stroke Length
Hub Specification:	HT Standard (KIC) 10 Stud Hub Piloted Outboard Iron Hub
Drum Specification:	HT Standard (KIC) Cast Drum
Hub/Drum-Opt(Nut&Other):	Standard
Bearing Specification:	Stemco
Lubrication Spec.:	Chev Delo Gear EP5 80-90 oil
Wheel Seals Spec.:	Stemco Platinum Performance Plus, Discover Seals, Sentinel Hub Cap, Pro-Torq Nut

ELECTRICAL

Harness-General Spec.:	Molded Color Code Phillips Harness (Sta-Dry)
Harness-Special Feature:	Manufacturer's Standard Feature
ID/Marker Light Spec:	(3) Trucklite 30 Series ID Light / Trucklite 33 Series Marker Light

S/T/Tail Light-Detail Spec: (4) Trucklite 44326R LED (Super 44 Black) Flange Mounted w/ Stainless Steel Rivets
Main Mid-Turn Light-Detail Spec: (2) Trucklite 60420Y LED Flange Mounted w/ Stainless Steel Ring
* ABS Light Detail Spec: (1) Trucklite 33275Y LED PC Rated w/ Grommet 33725 w/ anti-theft hardware
License Light: (1) Trucklite 33210C LED with 33815 Anti-Theft Flange

MARKING/DECALS

Decal Package: Factory Furnished Hyundai Information & Regulatory Decal Package with FMCSA Specified in Notes
Conspicuity Markings: Hyundai Standard Conspicuity with Logo Applied to Side Bottom Rail
License Plate: Temporary For Delivery. Fasten On HDG Mounting Plate
License Plate Brk't Install: HT DuraLite Standard Location
Furnish Document Holder: Factory Furnished
Document Holder Detail Spec: (1) Phillips 16-802
Document Holder/Manifest Loc.: Overlaid on Lower R/S Front

PAINT/FINISH

** Axle & Components Finish: Primed and Black Gloss Undercoating by HT Rev.C
* Susp. Sub-Frame Finish: Painted to Match Product Finish (Duralite Fixed Suspension) Rev.C
L/Gear(K-Bracing) Finish: Hot Dip Galvanized
L/Gear(Upper Leg) Finish: Black Undercoating
Rear Underride-Finish & Spec.: Hot Dip Galvanized & Bolted Horizontal Member
Duralite Product Finish: Hot Dip Galvanized

MISCELLANEOUS

Mudflap Provider: Factory Furnished Mudflaps
Mudflap Specification: 24"x24" White Plain Plastic with Hyundai Logo 3/8# thick with Anti-spray ribs
Mudflap Mounting Method/Install: STD Location w/ H.D Washer Retainer

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.