



Hale Trailer Brake & Wheel

018788 & 018789

Model: XL 80 SA
Weight +/- 3%:

XL 80 Slide Axle: Standard Specs

<p>XL 80 SA CAPACITY: 80,000 LB OVERALL CONCENTRATED: 50,000 LB IN 10' OAL: 48' OAW: 102"</p> <p>UPPER DECK 10' 5" FULL WIDTH NECK 49" 5TH WHEEL HEIGHT 82" SWING CLEARANCE 21" KING PIN SETTING 1 3/4" RAISED APITONG DECKING 2 TOOL BOXES IN UPPER DECK WITH STEEL DOORS 1 RECESSED CABLE ROLLER, BACK OF NECK CHAIN DROPS ON 48" CENTERS, BOTH SIDES HYDRAULICS RUN OFF OF WET KIT HYDRAULIC CONTROL LEVERS 2 SPEED LANDING GEAR 20,000 HYDRAULIC WINCH WITH MANUAL KICKOUT, & 100' WITH 5/16" CABLE WITH LOOP, PLANETARY DRIVE 2 FUNCTION WIRELESS REMOTE</p>	<p>MAIN DECK T-1 FLANGE, 80K WEB FAB I-BEAM (4 BEAM TRAILER) 38" LOADED DECK HEIGHT 1 RECESSED CABLE ROLLER IN FRONT 1 3/4" RAISED APITONG DECKING 4" JR. I-BEAM & 3" I-BEAM ON 8" CTRS CHAIN DROPS ON 24" CENTERS, EACH SIDE DOUBLE CHAIN DROPS DOWN THE CENTER ENERGY CHAIN TO PROTECT AIR, ELECTRIC, AND HYDRAULIC LINES 6 1/2 DEGREE LOAD ANGLE 48' OAL: 17 DEGREE DUMP ANGLE 51' OAL: 16 DEGREE DUMP ANGLE 53' OAL: 15 DEGREE DUMP ANGLE</p>	<p>SUSPENSION 25,000 LB AIR RIDE MANUAL DUMP VALVE</p> <p>AXLES (2) 25,000 LB NOMINAL 50" SPACING HUB PILOT, OUTBOARD DRUMS 12 1/4" X 7 1/2" BRAKES AUTO SLACK ADJUSTERS LIMIT CHAINS ON ALL AXLES 251M SPRING BRAKES ON 1 AXLE GREASELESS ROLLERS ON SLIDING AXLE ASSEMBLY</p>	<p>WHEELS AND TIRES 6.75 X 17.5 STEEL RIMS 245/ 70R/ 17.5 H RATED TIRES</p> <p>LIGHTING 12V SEALED GROTE HARNESS D.O.T APPROVED 7 YEAR WARRANTY RUBBER MOUNTED LED LIGHTS 1 MID-TURN SIGNAL PER SIDE 2 CLEARANCE LIGHTS PER SIDE 7 POLE ELECTRICAL SOCKET 2 TAIL LIGHT PACKAGE</p>
---	--	---	--

XL 80 Slide Axle Options

OAL Base Prices

51' OAL (California Legal)

Upper Deck

6 Function wireless winch remote control

Wheels/Tires

PSI Tire inflation system

Aluminum polished wheels (outside)

Paint/Decals

Black

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.