

# HALE






## TRAILER

BRAKE & WHEEL

Resale Inventory  
 A018843-A018845  
 VIN: 339981-339983

SALES | RENTALS | PARTS | SERVICE

Allentown, PA:	800-383-8894	Jacksonville, FL:	800-828-3055
Baltimore, MD:	888-601-7500	Little Rock, AR:	833-424-8944
Boston, MA:	800-854-5310	Portland, ME:	800-325-4253
Concord, NC:	800-438-2250	Richmond, VA:	866-839-3495
Delmar, DE:	866-486-1400	Scranton, PA:	800-569-1400
Des Moines, IA:	888-673-5011	Springfield, MA:	800-854-5306
Elkton, MD:	800-544-7127	Voorhees, NJ:	866-315-0235

HaleTrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

# Transcraft®

<b>Body Type/Base</b>
• Steel Drop Deck
<b>Frame</b>
• 804 (80,000# in 4' Beam Rating)
• 53' Overall Length
• 102" Wide, Width approx. 102"
• 10 Foot Upper Deck
• 1/4" Steel Coupler Plate - Standard
• 18" King Pin Setting
• Weld In King Pin
• Aluminum Drop Plate - Standard
• 48" Tractor 5th Wheel (Coupler Plate Height from Ground)
• Jost A420 Landing Gear - Standard
• Standard Camber Beams
• FHWA Inspection - Standard
• Sales Approval Drawing Required
• ---- Order Quantity
• GVWR >= 100,000# ILO Std.
<b>Suspension/Axle</b>
• GAWR >= 20,000# Standard
• (3) AANL23K Air Suspension (Restricted Lift Height / Lift in Unloaded Condition Only)
• Transcraft Warranty - Standard
• Tridem w/ 60.5" Axle Spacing
• Suspension set at Rearmost Position - Standard
• 3 axles (Tridem)
• (2) Lift Axles w/Air Lift Control
• Lift Axles Located Center and Rear
• Cast Brake Drums (Tridem)
• Ductile Iron Hubs

- Parallel (P) Spindle/Bearing - Standard
- Bearing Lube, 80/90 Oil
- Haldex Slack Adjusters
- No Hubometer - Standard
- Mudflaps Behind Rear Axle Only - Standard
- Mudflaps Factory Supplied - Standard

### Front Plate/Rear Plate

- Steel Front Plate - Standard
- Square Front Corners - Standard
- Center Tractor Controls in Front Plate - Standard
- No Bulkhead - Standard
- Steel Rear Plate w/ 3 Internal Stake Pockets
- 2 Post Steel Bumper - Standard
- No Rear Filler Plate - Standard
- No Filler Plate Lights - Standard

### Deck Side Rail

- 1-1/8" Apitong Wood Floor - Standard
- 4" Steel Floor Crossmembers - Standard
- 12" Crossmember Spacing
- Steel Side Rail w/ Pockets on 24" Centers with Double Spools - Standard

### Load Securement

- Double "L" Winch Track R/S
- No Winch Strap Tie Bar - Standard
- Sliding Winches, Standard Profile
- Winch Quantity: 15
- No Winch Straps - Standard
- No D-Rings - Standard
- No Chain Ties - Standard
- No Rope Hooks - Standard

### Tires and Wheels

- Cooper 255/70R22.5 RM272 LRH
- Steel Disc Wheels
- No Tire Inflation System - Standard

### Air Controls

- WABCO 4S/2M ABS - Standard
- No Aux Plumbing Controls - Standard
- Steel Air Tank - Standard

### Electrical

- 5 Marker/Turns Per Side w/TruckLite Harness System - Standard
- No Center Turn Lamps - Standard
- Round Stop/Turn/Tail Lamps - Standard
- No Strobes - Standard

<b>Storage Box</b>
• Storage Box Between Spread R/S: None - Standard
• Storage Box Between Spread C/S: None - Standard
• Storage Box Mid Trailer R/S: None - Standard
• Storage Box Mid Trailer C/S: None - Standard
• Storage Box Behind Landing Gear R/S: None - Standard
• Storage Box Behind Landing Gear C/S: None - Standard
<b>Accessories</b>
• No Tire Carrier Installed - Standard
• No Dunnage Rack - Standard
• No Certificate Holder - Standard
• No Flag Holders - Standard
• No Pintle Hitch - Standard
<b>Coatings/Markings</b>
• Black - Standard
• No Customer Decals Installed - Standard

**DISCLAIMER**

Specifications are for the equipment at the time it was produced and may not accurately reflect its current condition. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.