

HALE TRAILER BRAKE & WHEEL



A018868-A018902
VIN: 551801-551835

SALES | RENTALS | PARTS | SERVICE

| | | | |
|------------------------|--------------|--------------------------|--------------|
| Allentown, PA: | 800-383-8894 | Jacksonville, FL: | 800-828-3055 |
| Baltimore, MD: | 888-601-7500 | Little Rock, AR: | 833-424-8944 |
| Boston, MA: | 800-854-5310 | Portland, ME: | 800-325-4253 |
| Concord, NC: | 800-438-2250 | Richmond, VA: | 866-839-3495 |
| Delmar, DE: | 866-486-1400 | Scranton, PA: | 800-569-1400 |
| Des Moines, IA: | 888-673-5011 | Springfield, MA: | 800-854-5306 |
| Elkton, MD: | 800-544-7127 | Voorhees, NJ: | 866-315-0235 |

HaleTrailer.com | @haletrailer     

800-232-6535 *FINANCING AVAILABLE

GVWR: Trailer to meet 68,000 Pound GVWR
VIN PLATE: US - VIN Plate to Read in English (Standard)
Product Type: HT Combo Duralite

GEOMETRY

| | | |
|-----------------------------|---------------------------------|-------|
| Length - Exterior: | 48'-0" | Rev.B |
| Width - Exterior: | 102.36" | |
| Fifth Wheel Height: | 47" | |
| * King Pin Location: | 30" | Rev.C |
| * Landing Gear Location: | 108" from King Pin (+ 1"/-1/4") | Rev.C |
| Duralite Front Deck Height: | 59-3/4" (± 1/2") | |
| Duralite Rear Deck Height: | 54-5/16" (± 1/2") | |

TIRES & WHEELS

| | | |
|----------------------------|---|-------|
| Tire Furnished: | Factory Furnished | |
| * Tire Manufacturer: | Hankook TL21(G), Low Rolling Resistance Tire | |
| * Tire Size: | 11R22.5 | Rev.C |
| Wheel Furnish: | Factory Furnished | |
| Wheel Material: | All Steel Wheel | |
| Wheel Manufacturer: | HT Standard (TCC 361) | |
| Wheel Size: | 8.25 x 22.5, 5-Hand Hole (Steel, Inner & Outer) | |
| Wheel Finish for Steel: | Powder Coated White Steel Disc | |
| Tire Stem Valve Position: | Dual Wheel Steel / Aluminum / Combo (STD 180°outboard & straight inboard) | |
| Wheel Finish for Aluminum: | None (Due to All Steel Wheel Application) | |
| * Valve Stem & Cap: | Myers TR-572-F19 Valve stem | |

UPPER COUPLER

| | |
|--------------------------|--|
| Approach Plate: | 1/4" Thick 80,000 PSI Yield (Duralite) |
| King Pin & Manufacturer: | Standard (Jost) AAR Cruciform King Pin |

DURALITE OPTIONS

| | | |
|-------------------------|--|-------|
| * Cross Members: | 4" Steel I-Beams (80,000 PSI) : 12" C/L & 8" C/L @Middle 10' of Trailer Bay Area (Coil Package) | |
| Main Web: | 3/16" Thick, Welded One Piece Type (100 KSI Domex) | |
| Top Flange: | 3/8" Thick, 100 KSI Domex, 5" Wide One Piece Type | |
| * Bottom Flange: | 1/2" Thick, 100 KSI Domex, 5" Wide One Piece Type | |
| Holes on Main web: | Diamond Shape | |
| Gusset Type: | Pipe Type | |
| Gusset Specification: | (3) on Each Side (HT STD) | |
| Front Sill: | HT Standard Aluminum Extrusion | |
| Rear Sill: | HT Standard Aluminum Extrusion | |
| * Side Rail: | HT Integrated Aluminum High Impact Side Rail | |
| Side Stake Pockets: | 24" Centers on Each Side (STD) | |
| Winch Rail: | Integrated Aluminum Winch Rail with Side Rail | |
| * Winches: | Sliding Steel Winches, (12) on Road Side | Rev.C |
| Sliding Winch Stoppers: | Stoppers at Front and Rear (Flatbed STD for Sliding Winches) | |
| Fastener Options: | Standard Fasteners | |

FLOOR

Duralite Floor Specification: 1-1/8" Aluminum with 4 Apitong Nailer Strips (Combo STD)
 Floor Screws: HT Duralite Standard (2 Screws Per Board on I-beams)

FRONT

Gladhands: Phillips Qwik-E with Filters Control Line Only. Overlaid Straight Type
 Front Receptacle(7-Way): HT Duralite Standard (Phillips 7-Way Integrated with Main Harness)
 Gladhand/7-Way Location: (Interior Harness Routing) Overlaid on Lower Centerline Front

REAR

Rear Underride Guard: 4" Tube Bolt on Assembly w/ Bolt on Perforated(Pooched) Horizontal
 Dock Bumper: Pair Heavy Duty Dock Bumper (Ref. Buyers B4500)
 Rubber Bumper Location: HT Duralite Standard Location

LANDING GEAR

L/Gear Spec.: Jost 420
 L/Gear Shoes: 10" X 10" X 4" Sand Shoe (HT Duralite STD)
 L/Gear Crank Handle: Roadside
 L/Gear Cross Brace Design: HT Standard Cross Brace attachment Design

RUNNING GEAR

Bogie Type: Sliding Tandem(2) Axle Bogie
 Axle Spacing: 49" Axle Spacing
 Axle ABS System: Tandem Axle w/2S1M ABS System
 Duralite Bogie & Axle Location: HT Sliding Axle STD Location (CA Compliant; KP to Rear Most Axle 40#) Rev.C
 Susp. Manufacturer: Hendrickson
 Suspension Capacity: Standard Duty
 Duralite Susp. Specification: Hendrickson AAZNT46K Air Ride (Tandem Sliding)
 Surelok (Anti-Dock): No Surelok (No Anti-Dock)
 * Susp. Dump Valve: Auto Dump Valve Rev.C
 Locking Pin Mechanism: Air-Assist Pin Puller or Quik Draw
 Type of Susp Spring: Air Bag
 Spring Specification: Air Bag
 Axle Supplier: Hendrickson
 Axle-General Spec.: Axle - Tandem (2) Axle included in Suspension (For 2S1M or 2S2M System)
 Axle-Track Length: 77-1/2"
 Axle-Spindle Type: Parallel Spindle
 Brake Lining Size: 16.5" X 7"
 Brake Lining Spec.: Hendrickson Extended Service (Abex-3030-197)
 Brake Control System: 2S/1M Wabco ABS
 Spring Brake Control: Sealco 110500 Springbrake Priority
 Drain Valve & Other: Parker DC604-4 Drain Cock
 Slack Adjuster Spec.: Gunite Auto-5.5", 28 Spline
 Brake Chamber Spec.: TSE 3030 Tamper Resist (HT standard)
 Stroke Length: MFG's Standard Stroke Length
 Hub Specification: HT Standard (KIC) 10 Stud Hub Piloted Outboard Iron Hub
 Drum Specification: HT Standard (KIC) Cast Drum
 Hub/Drum-Opt(Nut&Other): Standard
 Bearing Specification: Stemco
 Lubrication Spec.: Chev Delo Gear EP5 80-90 oil
 Wheel Seals Spec.: Stemco Platinum Performance Plus, Discover Seals, Sentinel Hub Cap, Pro-Torq Nut

ELECTRICAL

Harness-General Spec.: Molded Color Code Phillips Harness (Sta-Dry)
 Harness-Special Feature: Manufacturer's Standard Feature
 ID/Marker Light Spec: (3) Trucklite 30 Series ID Light / Trucklite 33 Series Marker Light
 S/T/Tail Light-Detail Spec: (4) Trucklite 44326R LED (Super 44 Black) Flange Mounted w/ Stainless Steel Rivets
 Main Mid-Turn Light-Detail Spec: (2) Trucklite 60420Y LED Flange Mounted w/ Stainless Steel Ring
 * ABS Light Detail Spec: (1) Trucklite 33275Y LED PC Rated w/ Grommet 33725 w/ anti-theft hardware

License Light: (1) Trucklite 33210C LED with 33815 Anti-Theft Flange
* Option Related Lamps/Harness: Additional Trucklite 33 LED Series Marker Lights. (5) on Each Sides Rev.C

MARKING/DECALS

Decal Package: Factory Furnished Hyundai Information & Regulatory Decal Package with FMCSA Specified in Notes
Conspicuity Markings: Hyundai Standard Conspicuity with Logo Applied to Side Bottom Rail
License Plate: Temporary For Delivery. Fasten On HDG Mounting Plate
License Plate Brk't Install: HT DuraLite Standard Location
Furnish Document Holder: Factory Furnished
Document Holder Detail Spec: (1) Phillips 16-802
Document Holder/Manifest Loc.: Overlaid on Lower R/S Front

PAINT/FINISH

** Axle & Components Finish: Primed and Black Gloss Undercoating by HT Rev.C
Susp. Sub-Frame Finish: Black Undercoating
L/Gear(K-Bracing) Finish: Hot Dip Galvanized
L/Gear(Upper Leg) Finish: Black Undercoating
Rear Underride-Finish & Spec.: Hot Dip Galvanized & Bolted Horizontal Member
Duralite Product Finish: Hot Dip Galvanized

MISCELLANEOUS

Mudflap Provider: Factory Furnished Mudflaps
Mudflap Specification: 24"x24" White Plain Plastic with Hyundai Logo 3/8# thick with Anti-spray ribs
Mudflap Mounting Method/Install: STD Location w/ H.D Washer Retainer

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical.
Equipment availability, prices and specifications are subject to change without notice.