



Hale Trailer Brake & Wheel
018966-018970

X-L SPECIALIZED TRAILERS, INC.

29' 6"
OAW: 102"

MODEL: XL 100JPS

DIST: 100,000

CONC.

WEIGHT +/-3% 11200lbs

2 AXLE JEEP

GOOSENECK-

LENGTH: 13' 2"
KING PIN SETTING: 16"
SWING CLEARANCE: 126"
5TH WHEEL HEIGHT: 49"
D-RINGS: 1 PAIR OF BENT D-RINGS
LANDING GEAR: 2 SPEED LANDING GEAR, HANDLE ON DRIVER SIDE

REAR DECK:

5TH WHEEL: PURCHASED 72" SLIDER 70,000 lbs CAP
LOADED 5TH WHEEL HEIGHT: 50"
AXLES: (2) 25,000 NOMINAL, 77 1/2" TRACKING
SUSPENSION: HEND-TURNER / 25,000 AIR
AXLE SPACING: 60"
ABS: N/A , SPRING BRAKES PER 1 AXLE
TIRES: 275 / 70R / 22.5
WHEELS: 8.25 X 22.5 ALUMINUM POLISHED OUT MILLED IN DISC WHEELS
BRAKES: 16 1/2" X 7"
DRUMS: OUTBOARD
ELECTRICAL: 12V SEALED GROTE SYSTEM WITH 2 TAIL LIGHT PACKAGE
D-RINGS: 1 PAIR OF BENT D-RINGS
RAISE AND LOWER VALVE

ADDITIONAL:

PAINT: BLACK URETHANE ENAMEL WITH 2 PART EPOXY PRIMER
AIR WEIGH DIGITAL SCALE
FRAME REINFORCEMENT, AIR, BRACKETS, ELECTRICAL FOR PIN ON AXLE
PSI SYSTEM ON ALL AXLES

GOES WITH 18966

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.