

# HALE

## TRAILER

### BRAKE & WHEEL



**A019018-A019019**  
**VIN: 23527 & 23530**

#### SALES | RENTALS | PARTS | SERVICE

<b>Allentown, PA:</b>	<b>800-383-8894</b>	<b>Jacksonville, FL:</b>	<b>800-828-3055</b>
<b>Baltimore, MD:</b>	<b>888-601-7500</b>	<b>Little Rock, AR:</b>	<b>833-424-8944</b>
<b>Boston, MA:</b>	<b>800-854-5310</b>	<b>Portland, ME:</b>	<b>800-325-4253</b>
<b>Concord, NC:</b>	<b>800-438-2250</b>	<b>Richmond, VA:</b>	<b>866-839-3495</b>
<b>Delmar, DE:</b>	<b>866-486-1400</b>	<b>Scranton, PA:</b>	<b>800-569-1400</b>
<b>Des Moines, IA:</b>	<b>888-673-5011</b>	<b>Springfield, MA:</b>	<b>800-854-5306</b>
<b>Elkton, MD:</b>	<b>800-544-7127</b>	<b>Voorhees, NJ:</b>	<b>866-315-0235</b>

HaleTrailer.com | @haletrailer     

**800-232-6535** \*FINANCING AVAILABLE

## XL SPECIALIZED TRAILERS

### XL 120 Step Deck Extendable

<b>OVERALL LENGTH</b>	53'
<b>OVERALL WIDTH</b>	102"
<b>CAPACITY</b>	120,000 LB DISTRIBUTED; 100,000 LB IN 10' CLOSED
<b>WEIGHT +/- 3%</b>	0,000 LB

#### GOOSENECK

<b>LENGTH</b>	11' 6" NARROW GOOSENECK
<b>KINGPIN SETTING</b>	16" REMOVABLE
<b>SWING CLEARANCE</b>	102"
<b>5TH WHEEL HEIGHT</b>	52"
<b>DECKING</b>	NONE
<b>STAKE POCKETS</b>	NONE
<b>LANDING GEAR</b>	2 SPEED W/ HANDLE ROAD SIDE
<b>FLIP NECK</b>	PREP FOR 72" FLIP NECK 72" FLIP NECK

#### MAIN DECK

<b>LENGTH</b>	41' 6" EXTENDING TO 64' 4"
<b>LOADED DECK HEIGHT</b>	33" WITH OPEN WHEELS
<b>DECKING</b>	1 1/8" APITONG DECKING, FLUSH
<b>CROSSMEMBER</b>	4" JR. I-BEAM ON 12" CENTERS
<b>BEAMS</b>	6" MILLED SIDE RAILS
<b>STAKE POCKETS</b>	24" CENTERS WITH 5/16" X 2" RUB RAIL W/ SINGLE PIPE SPOOLS
<b>D-RINGS</b>	( 7 ) PAIR OF PAN STYLE D-RINGS ON MAIN DECK - EVENLY SPACED ( 7 ) PAIR OF FLAT D-RINGS AT BOTTOM KNEE BRACES
<b>AXLES</b>	( 3 ) 25,000 LBS. NOMINAL, (5/8" WALL)
<b>SUSPENSION</b>	HENDRICKSON / 25,000 CAPACITY / AIR RIDE
<b>AXLE SPACING</b>	60"
<b>ABS</b>	NA WITH SPRING BRAKES ON ( 1 ) AXLE
<b>TIRES</b>	MICHELIN 245 / 70R / 17.5 ( H )
<b>WHEELS</b>	6.75 X 17.5 8-HOLE, PILOT MOUNT, STEEL INSIDE, ALUMINUM POLISHED OUTSIDE DISC
<b>BRAKES</b>	12 1/4" X 7 1/2"
<b>DRUMS</b>	OUTBOARD
<b>ELECTRICAL</b>	12V SEALED GROTE SYSTEM WITH ( 3 ) TAILLIGHT ALUMINUM PACKAGE 4" AMBER STROBE TO BE USED AS 3RD TAILLIGHT
<b>D-RINGS</b>	( 1 ) PAIR OF BENT D-RINGS IN TAIL CHANNEL

#### PAINT

BLACK

#### ADDITIONAL

RAISE AND LOWER VALVE LOCATED IN REAR DRIVER SIDE BOLSTER  
 LIQUID FILLED AIR GAUGE LOCATED IN REAR DRIVER SIDE BOLSTER  
 ( 1 ) PAIR OF EXTRA CLEARANCE LIGHT AT START OF MAIN DECK  
 DUST SHIELDS  
 PREP FOR 2 AXLE POWER BOOSTER  
 MANUAL RIDE HEIGHT CONTROL  
 ( 1 ) 4-WAY PLUG IN EACH CORNER OF MAIN DECK  
 ( 1 ) 4-WAY PLUG IN REAR BOLSTER - BOTH SIDES  
 LIMIT CHAINS ON ALL 3 AXLES  
 PSI TIRE INFLATION SYSTEM ON ALL 3 AXLES

SIMILAR TO 23031 MINUS PCO

TO FIT: 22 FA INT 23528 , 22 FA REAR 23529,  
 42 PMB SO 75923

#### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.