



Hale Trailer Brake & Wheel

019124

X-L SPECIALIZED TRAILERS, INC.

OAL: 37' 3"

OAW: 120"

MODEL: XL 100JPS

DIST: 100,000

CONC.

WEIGHT +/-3% 11700

3 AXLE JEEP

GOOSENECK-

LENGTH: 14' 4"
KING PIN SETTING: 16" 24"
SWING CLEARANCE: 135" 127"
5TH WHEEL HEIGHT: 49"
D-RINGS: 1 PAIR OF BENT D-RINGS
LANDING GEAR: HEAVY DUTY 2 SPEED LANDING GEAR, HANDLE ON DRIVER SIDE
JOST LANDING GEAR, PART NUMBER JOSA 400.T.17
BUMP UP RAMPS TO HAT BOX FIFTH WHEEL

REAR DECK:

10' WIDE
5TH WHEEL: HYDRAULIC HAT BOX
LOADED 5TH WHEEL HEIGHT: 54" TO 72"
AXLES: (3) 30,000 NOMINAL, 97 1/2" TRACKING
SUSPENSION: CUSH / 25,000 AIR
AXLE SPACING: 60"
ABS: N/A , SPRING BRAKES PER 1 AXLE
TIRES: 245/70R/17.5 MICHELINS
WHEELS: 6.75 X 17.5 ALUMINUM MILLED INSIDE & OUTSIDE, DISC WHEELS
BRAKES: DISC
DRUMS:
ELECTRICAL: 12V SEALED GROTE SYSTEM WITH 2 TAIL LIGHT PACKAGE
D-RINGS: 1 PAIR OF BENT D-RINGS
RAISE AND LOWER VALVE

ADDITIONAL:

PAINT: BLACK
13HP HONDA POWER UNIT
PSI TIRE INFLATION SYSTEM
MINIMIZER FENDERS
DIGITAL AIR WEIGH SYSTEM
LIMIT CHAINS

GOES WITH 19125-26

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.