



Hale Trailer Brake & Wheel

019125

**X-L SPECIALIZED TRAILERS, INC.**

OAL: 65' 9"  
OAW: 120"

MODEL: XL 170 MG DIST: 170,000# CONC. 170,000# IN 10' WEIGHT +/-3% 39105

**GOOSENECK-**

LENGTH: 14' 3"  
KING PIN SETTING: 16"  
SWING CLEARANCE: 115"  
5TH WHEEL HEIGHT: 59"  
FLIP NECK: FRAME REINFORCEMENT, AIR, ELECTRIC AND BRACKETS FOR 142" FLIP NECK EXT.  
142" FLIP NECK EXTENSION

**MAIN DECK-**

10' WIDE  
LENGTH: 30'  
LOADED DECK HGT: 26" W/ 6" GROUND CLEARANCE  
DECKING: 2" APITONG DECKING, RAISED, CENTER COVERED  
CROSSMEMBER: FAB 12" X-MEMBERS ON 24" O/C  
SIDE BEAMS: 4 BEAMS 20"  
D-RINGS: 15 BENT D-RINGS PER SIDE, 30 TOTAL  
OUTRIGGERS: BRACKETS ONLY FOR HEAVY DUTY SWINGOUT OUTRIGGERS ON 24" CENTERS

**REAR DECK:**

LENGTH: 21' 6"  
LOADED DECK HEIGHT: 44"  
AXLES: ( 3 ) 30,000 NOMINAL, 97 1/2" TRACKING,  
SUSPENSION: CUSH / 25,000 CAPACITY / AIR  
AXLE SPACING: 60"  
ABS: N/A SPRING BRAKES ON ALL 1 AXLE  
TIRES: MICHELIN 245/70R/17.5  
WHEELS: 6.75 X 17.5 / ALUMINUM MILLED INSIDE & OUTSIDE / DISC / PILOTED HUBS  
BRAKES: DISC  
DRUMS:  
ELECTRICAL: 12V SEALED GROTE SYSTEM WITH 3 TAIL LIGHT ALUM. PACKAGE  
4" AMBER STROBE WITH SWITCH TO MAKE 3 STT  
DECKING: NO BOLSTERS  
D-RINGS: 2 BENT D-RINGS IN TAIL CHANNEL

**ADDITIONAL:**

BELLY PIN AT FRONT OF MAIN DECK  
PAINT: BLACK  
FRAME REINFORCEMENT FOR THREE AXLE BOOSTER BRACKETS, AIR & ELEC.  
AIR BAG SHUT OFFS  
MINIMIZER FENDERS  
DIGITAL AIR WEIGH SCALE  
MANUAL RIDE HEIGHT CONTROL  
RAISE AND LOWER VALVE  
CA LEGAL WEST COAST SET UP  
DETACHABLE WHEEL AREA WITH HORIZONTAL PINS  
PSI TIRE INFLATION SYSTEM  
LIMIT CHAINS ON ALL AXLES  
LED LIGHTING  
BRACKETS IN WHEEL AREA FOR SHIMS  
REST BLOCK FOR SETTING BOOSTER ON THE WHEEL AREA  
GOES WITH 19124 & 19126

**DISCLAIMER**

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.