



## Hale Trailer Brake & Wheel 019135-019136

### components description

OVERALL LENGTH 45'

OVERALL WIDTH 8'

**\*\*96" Wide Trailer.\*\***

OVERALL HEIGHT FRONT 13'-1"= Flat Top Tarp System Included in Height

UPPER COUPLER HEIGHT 48"

UPPER COUPLER PLATE 1/4" Plate

KING PIN SETTING 36"

SWING CLEARANCE 90"= 36KP

LANDING GEAR Two Speed

SUSPENSIONS Spring Ride - Hutchens-2 Axle

SUSPENSION LOCATION Set at Rear Most Position

AXLES (2) 22,500K Capacity - Type 30 Chambers - Auto Slacks - ABS

AXLE SPACING 49"

LIFT AXLE None

WHEELS Disc - Hub Piloted- 22.5- (-56#)

TIRES 11R22.5-Manufacturer Choice

FRONT TYPE 18" Diagonal

FRONT MATERIAL Aluminum .050 - Pre Painted White Aluminum

LADDERS Steel Nose & Rear Door

REAR DOOR TYPE Heavy Duty Aluminum Top Hinged Chip Gate W/Wear Pads

REAR DOOR MATERIAL Heavy Duty Galvanized Mesh

SIDE SHEET MATERIAL .050 Aluminum - Smooth

INTERIOR LINING None

SIDE SHEET COLOR Pre-Painted White

SIDE POST Extruded Aluminum on 16" Centers

LOWER RAIL Heavy Duty Aluminum Lower Rail

FLOOR Corr Fabricated Aluminum

FLOOR SILLS 4" Steel - Wax-Dipped I-Beam w/ Undercoating

SILL SPACING 12"/16"/12" STD

PARKING BRAKES All Axles

DUST SHEILDS None

ANTI-SAIL MUD FLAPS Behind Rear Axle

BUMPER H. D. 3" x 4" Push Bumper

TARP SYSTEM Shur-Co Brand Mesh Lock and Roll-Frt&RrCap-0Bows-22oz-2Straps-45'

**\*\*Mesh Tarp.\*\***

TARP COLOR None

LIGHTS Sealed Wiring Harness W/ LED PKG

PAINT Black - Ladder, Fifth Wheel, and Rear Frame

### DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.