

Hale Trailer Brake & Wheel 019174-019177



components description

CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)

OVERALL LENGTH 53' - Base Weight 13,990# - Including Length of Beavertail

UPPER DECK LENGTH 10'6"

LOWER DECK LENGTH 38'1"

DOVETAIL 53.13" - Steel Smooth Plate & Traction Bars

Prep Rear Skirt For 3rd Ramp.

OVERALL WIDTH 8'6"

KING PIN SETTING 24" - Tapered Front

UPPER COUPLER PLATE 1/4"

UPPER COUPLER HEIGHT 48"

MAINFRAME 26" Fab.-PreCamb.I-Beams-(80K Pkg)

BULKHEAD None

SIDE RAILS 6" - 6.5# Per Foot

TOP DECK FLOOR SILLS 4" Steel I-Beam - 18" O.C.

LOWER DECK FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg

COIL HAUL PACKAGE Single Coil Placement - 5 Extra Stud Sills-Ctr On Trailer

Coil Package.

FLOOR DECKING 1-1/8" Apitong

WINCHES 12

WINCH TRACK Steel Slide Entire Length of Drivers Side

STRAPS None

LANDING GEAR Two Speed

SUSPENSIONS Air Ride - Cush - CP25U - 2 Axles

SUSPENSION LOCATION King Pin to Center of Rear Axle 43'

AXLES (2) 25K Capacity - Type 30 Chambers - Auto Slacks - ABS - 22.5 Tires (1463#)

AXLE SPACING 49" (+35#)

Closed Tandem.

DUMP VALVE Manual-Position In Rear Skirt Gusset D/S-Dump All Axles

LIFT AXLE None

SCALES None

PARKING BRAKES All Axles

ABS SYSTEM ABS System 2S/1M

DUST SHEILDS None

WHEELS Disc - Hub Pilot-22.5 (2-AX)-Polish ALUMINUM 4 Outside Wheels(4-Steel Inside) (-148#)

TIRES 255/70R 22.5 - 41" Loaded Deck Height - Double Coin

TIRE INFLATION SYSTEM None

STAKE POCKETS 24" O.C. & 4 Across Front

ANTI-SAIL MUD FLAPS Behind 2 Axles

PIPE SPOOLS Double

RUB BAND STEEL 3/8" X 2-1/2" Recessed for DOT Tape

DOCK BUMPERS None

LOADING RAMPS (2)-Spring Assisted

CONTAINER TWIST LOCKS None

CARGO TIE DOWN None

TIRE CARRIERS None

TOOLBOX MATERIAL Aluminum

TOOLBOX TYPE 18Hx18Dx60L-Alum Box-Barn Style Double Door-Dia TP Alum Door(+93#)

TOOLBOX LOCATION Driver Side- Between Spread

LIGHTS Sealed Wiring Harness w/ LED Pkg

CUSTOM LIGHTS None

PAINT Black