



Hale Trailer Brake & Wheel 019316-019317



components description

CAPACITY Standard Beam Pkg - 80,000 GVWR (60,000 in 10' Span)
OVERALL LENGTH 42'
OVERALL WIDTH 8' 6"
KING PIN SETTING 30" - Tapered Front
UPPER COUPLER PLATE 1/4"
UPPER COUPLER HEIGHT 48"
BULKHEAD Removable Steel - 48" - No Side Return - 4 Posts DOT - (+387#)
MAIN FRAME 26" Fab.-PreCamb.I-Beams-(80K Pkg)**44" Frame Centers**
SIDE RAILS 6" - 6.5# Per Foot
FLOOR SILLS 4" Steel I-Beam 12" O.C. HD Pkg. (+325#)
COIL HAUL PACKAGE None
FLOOR DECKING 1-1/8" Apitong
WINCH TRACK Steel Slide Entire Length of Drivers Side
WINCHES 12
STRAPS None
LANDING GEAR Two Speed
SUSPENSIONS Air Ride- Hendrickson - Intraax - 23K 2 Axle- Slider
SUSPENSION LOCATION Slider/Variable
LIFT AXLE None
DUMP VALVE None
SCALES None
AXLES (2) 22.5K Capacity- Type 30 Chambers- Auto Slacks
ABS SYSTEM ABS System 2S/1M
AXLE SPACING 49" (+35#)
PARKING BRAKES All Axles
DUST SHEILDS None
TIRE INFLATION SYSTEM None
TIRES 11R22.5- DOUBLE COIN
WHEELS Disc - Hub Piloted - 22.5 Steel
ANTI-SAIL MUD FLAPS Behind Rear Axle
STAKE POCKETS 24" O.C. Sides & 4 Across Front, 5 Across Rear
RUB BAND STEEL 3/8" X 2-1/2" Recessed for DOT Tape
PIPE SPOOLS Double
DOCK BUMPERS Rubber Inboard
CARGO TIE DOWN None
TOOLBOX MATERIAL None
TOOLBOX TYPE None
TOOLBOX LOCATION None
TIRE CARRIERS None
CONTAINER TWIST LOCKS None
LIGHTS Sealed Wiring Harness W/LED Pkg-Micro(2)Front/(2)Rear Sides-3 Ctr Rear
CUSTOM LIGHTS None
FORK LIFT KIT MODELS None
COUNTER BALANCE None
PAINT Black

DISCLAIMER

Specifications are believed to be correct, but may contain errors and/or omissions. Photographs are the representative of the subject equipment but may not be identical. Equipment availability, prices and specifications are subject to change without notice.